



BSI Standards Publication

Plain bearings — Quality assurance of thin-walled half bearings — Selective assembly of bearings to achieve a narrow clearance range

National foreword

This British Standard is the UK implementation of ISO 13778:2017. It supersedes BS ISO 13778:1999, which is withdrawn.

The UK participation in its preparation was entrusted to Technical Committee MCE/12, Plain bearings.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2017
Published by BSI Standards Limited 2017

ISBN 978 0 580 92912 0

ICS 21.100.10

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 30 April 2017.

Amendments/corrigenda issued since publication

Date	Text affected
------	---------------

INTERNATIONAL
STANDARD

ISO
13778

Second edition
2017-03-15

**Plain bearings — Quality assurance of
thin-walled half bearings — Selective
assembly of bearings to achieve a
narrow clearance range**

*Paliers lisses — Assurances qualité des demi-coussinets minces —
Assemblage sélectif des paliers pour obtenir un jeu faible*



Reference number
ISO 13778:2017(E)

© ISO 2017



COPYRIGHT PROTECTED DOCUMENT

© ISO 2017, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

Page

Foreword	iv
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Housing swell and thermal expansion	2
5 Measurement and identification	2
5.1 Housings and journals.....	2
5.2 Bearings.....	2
6 Suggested schemes for fitting	3
6.1 General.....	3
6.2 Scheme 1: Standard application, without grading.....	3
6.3 Scheme 2: Grading of bearings.....	4
6.4 Scheme 3: Grading of bearings and journals or housings.....	4
6.5 Scheme 4: Unmixed bearings (Matrix scheme).....	5
6.6 Scheme 5: Mixed bearings (Matrix scheme).....	6
6.7 Scheme 6: Mixed bearings (fine matrix).....	6

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 123, *Plain bearings*, Subcommittee SC 5, *Quality analysis and assurance*.

This second edition cancels and replaces the first edition (ISO 13778:1999), which has been technically revised.

Plain bearings — Quality assurance of thin-walled half bearings — Selective assembly of bearings to achieve a narrow clearance range

1 Scope

This document specifies the selective assembly of bearings (in accordance with ISO 3548-1).

The bearing diametral clearance is determined by the housing diameter, journal diameter and the wall thickness of the two half bearings. Typically, these components will have a total tolerance “stack up” of 50 µm to 60 µm. Current engine development and in particular, the desire for improved engine refinement, has provided a need to decrease the clearance range due to the tolerance “stack up”. This document suggests various schemes of selective assembly to achieve such ranges.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 3548-1, *Plain bearings — Thin-walled half bearings with or without flange — Part 1: Tolerances, design features and methods of test*

ISO 4378-1, *Plain bearings — Terms, definitions, classification and symbols — Part 1: Design, bearing materials and their properties*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 4378-1 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

3.1

theoretical bearing diametral clearance

C

difference between the housing diameter, D_H , less twice the half bearing wall thickness (3.3), s_3 , and the journal diameter (3.4), D_J

$$C = D_H - (2s_3 + D_J)$$

3.2

housing diameter

D_H

diameter of the housing with no bearing fitted measured perpendicular to the split line

3.3 bearing wall thickness

s_3
wall thickness measured at 90° from the split line (at the “crown”)

Note 1 to entry: If two measurements are made, the larger of the two is used.

3.4 journal diameter

D_j
diameter of the finished shaft measured at a position to give maximum diameter

3.5 tolerance

range between the upper and lower limits specified on the drawing

3.6 housing swell

expansion of a housing bore caused by the interference fit of the bearings

4 Housing swell and thermal expansion

Housing swell is defined as the “expansion of a housing bore, caused by the interference fit of the bearings”. When two half bearings are assembled into a housing and the housing is bolted up, the assembled bore will be slightly greater than the arithmetical subtraction of the two bearing wall thicknesses from the housing diameter as measured before the bearing is fitted. Housing swell is generally of the order of a few micrometres. Maximum housing swell will occur with a combination of maximum bearing overstand (nip) and minimum housing diameter. It is prudent to measure actual housing swell by carrying out fitting tests. Actual housing deformation may also be affected by the degree of control of bolt tension.

With light alloy housings, the housing swell may be larger, due not only to the lower modulus of elasticity but also to thermal expansion.

Allowance for housing swell and thermal expansion has to be made when setting the bearing diametral clearance.

5 Measurement and identification

5.1 Housings and journals

Specific measurement of each housing and journal may be necessary in more complex grading schemes. While bearings will be graded according to only the crown wall thickness, journals in particular may have to be measured in several places, both axially and circumferentially, to ascertain the mean journal diameter. The crown housing diameter may be the only housing measurement necessary. With grade tolerances of a few micrometres, accurate measurement with minimal dirt and constant temperature is necessary.

Traditionally, crankshaft journals of different grades have been identified with a dab of paint or ink adjacent to the journal. Housings have been similarly identified. Such a method relies upon the visual discrimination of the operator and this may on occasions be unreliable. One alternative is to bar or dot code the housing and/or journal with either adhesive labels or by etching. Another is to store the data on computer for retrieval at assembly stage.

5.2 Bearings

If bearing grades with wall thickness tolerances of less than the normal process capability are required, then consideration shall be given as to how the bearings are graded and identified. The part number is

stamped upon the bearing prior to final wall thickness machining. Additional stamping after bearing grading is not feasible as this will create high spots of wall thickness. The usual practice is to mark the bearing side face after grading with a permanent colour code or with other suitable methods.

6 Suggested schemes for fitting

6.1 General

The selective assembly of bearings shall be in accordance with ISO 3548-1.

Before choosing the scheme for selectively fitting bearings, it is first necessary to set the desired clearance range. As a general rule, the narrower the clearance range, the more complex the grading scheme will be and the tighter the tolerance on each component. As an example, if a clearance range of 24 µm is required, this could entail grade tolerances of 6 µm, while with a clearance range of 32 µm, grade tolerances of 8 µm would be acceptable.

While it may be desirable from the design viewpoint to achieve a very narrow clearance range, there may come a point at which perceived performance gains from working very close to the desired mean clearance become offset by the cost and complexity of the selective fitting scheme.

While such schemes are feasible for OE engine assembly, they are not practical for replacement bearings where the bearings are packed in sets of similar sizes.

Other points to consider are as follows.

- a) Due to the normal distribution of journal and housing sizes, the required quantity of each bearing grade will not necessarily be equal. Carefully controlled scheduling will be necessary in order to minimize bearing stocks and prevent shortages of particular bearing grades.
- b) Intermediate grades can be formed by fitting together half bearings from adjacent grades. This can significantly increase the flexibility of the system.
- c) If it is necessary to grade bearings by measurement after final wall thickness machining, then overlapping bearing grades are permissible and in fact allow the bearing supplier flexibility in achieving correct quantities of each bearing grade.
- d) When choosing a grading scheme, the difference in process capability for wall thickness between bimetallic and multi-layer should be taken into account.

The schemes described in [6.2](#) to [6.7](#) are examples only.

6.2 Scheme 1: Standard application, without grading

The clearance shall be determined by the limitations of normal process capability (see [Table 1](#)).

Housing diameter, D_H : not graded

Journal diameter, D_J : not graded

Bearing wall thickness, s_3 : not graded

Table 1 — Standard application; without grading

Dimensions in millimetres

Grade	Without grading
D_H	50,000 to 50,018
D_J	46,000 to 46,018

Grade	Without grading
s_3	1,972 to 1,978
C	0,026 to 0,074

6.3 Scheme 2: Grading of bearings

Scheme 2 is applicable where a slight reduction in the clearance tolerance is required. The bearings are graded to effectively reduce the tolerance of the grade (see [Table 2](#)).

- Housing diameter, D_H : not graded
 Journal diameter, D_J : not graded
 Bearing wall thickness, s_3 : three grades of 4 μm

Table 2 — Grading of bearings

Dimensions in millimetres

Grade	A	B	C
D_H^a	50,000 to 50,018		
D_J^a	46,000 to 46,018		
s_3	1,970 to 1,974	1,974 to 1,978	1,978 to 1,982
C^b	0,026 to 0,070		
^a Without grading. ^b According to the selection procedure.			

Depending on the selection procedure, fit as a bearing pair, either two of grade B or one of grade A and one of grade C.

NOTE 1 The scheme is simple to administer.

NOTE 2 Compared to scheme 1, the clearance range of 0,026 mm to 0,074 mm is reduced to 0,026 mm to 0,070 mm.

6.4 Scheme 3: Grading of bearings and journals or housings

The housing or the journal is graded, usually into two or three grades and the bearings are graded into a similar number of grades (see [Table 3](#)).

- Housing diameter, D_H : not graded
 Journal diameter, D_J : three grades of 6 μm grade tolerance
 Bearing wall thickness, s_3 : three grades of 4 μm grade tolerance

Table 3 — Grading of bearings and journals or housings

Dimensions in millimetres

Grade	A	B	C
D_H^a	50,000 to 50,018		
D_J	46,000 to 46,006	46,006 to 46,012	46,012 to 46,018
^a Without grading.			

Grade	A	B	C
s_3	1,984 to 1,980	1,981 to 1,977	1,978 to 1,974
C	0,026 to 0,058		
^a	Without grading.		

NOTE 1 The spacing of each bearing grade is determined by the spacing of each journal grade in order to achieve an identical clearance range for each combination.

NOTE 2 Compared to scheme 2, the clearance range of 0,026 mm to 0,070 mm is reduced to 0,026 mm to 0,058 mm.

NOTE 3 Overlapping grades are used effectively.

NOTE 4 The scheme is simple to administer.

6.5 Scheme 4: Unmixed bearings (Matrix scheme)

Housing and journal diameter both graded with equal grade tolerances. With an equal number of housing and journal grades, the matrix is symmetrical and the distribution of bearings will be even. The bearing wall thickness grade tolerance is half that of the housing to journal diameter grade tolerance (see [Table 4](#) and [Table 5](#)).

Housing diameter, D_H : three grades of 6 μm grade tolerance

Journal diameter, D_J : three grades of 6 μm grade tolerance

Bearing wall thickness, s_3 : five grades of 3 μm grade tolerance

Table 4 — Unmixed bearings

Dimensions in millimetres

Grade	A	B	C	D	E
D_H	50,000 to 50,006	50,006 to 50,012	50,012 to 50,018	—	—
D_J	46,000 to 46,006	46,006 to 46,012	46,012 to 46,018	—	—
s_3	1,975 to 1,978	1,978 to 1,981	1,981 to 1,984	1,984 to 1,987	1,987 to 1,990
C	0,026 to 0,044				

Table 5 — Bearing grades

Journal grade	Bearing grade according to Table 4		
	Housing grade		
	A	B	C
A	C + C	D + D	E + E
B	B + B	C + C	D + D
C	A + A	B + B	C + C

NOTE 1 Many bearing grades may be required, giving difficulty in discerning the colour shades involved.

NOTE 2 Compared to scheme 3, the clearance range 0,026 mm to 0,058 mm is reduced to 0,026 mm to 0,044 mm.

Achieved clearance range may be narrow but bearing grade wall thickness tolerance shall be small.

6.6 Scheme 5: Mixed bearings (Matrix scheme)

Housing and journal diameter are both graded with equal grade tolerances. Bearing wall thickness grade tolerance is the same as for the housing and journal diameter (see [Table 6](#) and [Table 7](#)).

Housing diameter, D_H : three grades of 6 μm grade tolerance

Journal diameter, D_J : three grades of 6 μm grade tolerance

Bearing wall thickness, s_3 : three grades of 6 μm grade tolerance

Table 6 — Mixed bearings (Matrix scheme)

Dimensions in millimetres

Grade	A	B	C
D_H	50,000 to 50,006	50,006 to 50,012	50,012 to 50,018
D_J	46,000 to 46,006	46,006 to 46,012	46,012 to 46,018
s_3	1,972 to 1,978	1,978 to 1,984	1,984 to 1,990
C	0,026 to 0,050		

Table 7 — Bearing grades

Journal grade	Bearing grade according to Table 6		
	Housing grade		
	A	B	C
A	B + B	B + C	C + C
B	A + B	B + B	B + C
C	A + A	A + B	B + B

NOTE 1 Compared to scheme 4, the clearance range 0,026 mm to 0,044 mm is increased to 0,026 mm to 0,050 mm because there are two less bearing grades required.

NOTE 2 Achieved bearing clearance range is narrow.

NOTE 3 In order to increase usage of bearing grades at either end of the range, intermediate pairs such as B + B can be replaced by A + C.

6.7 Scheme 6: Mixed bearings (fine matrix)

In this scheme, the housing and journal diameters are measured to the nearest micrometre and depending on their respective positions on the fine matrix, the bearings will be fitted (see [Table 8](#), [Table 9](#) and [Table 10](#)).

Table 8 — Mixed bearings (fine matrix)

Journal diameter	Housing diameter ^a																		
	min. 50,000									max. 50,018									
min. 46,000	d	d	d	c	c	c	c	c	c	b	b	b	b	b	b	a	a	a	a
	d	d	d	d	c	c	c	c	c	c	b	b	b	b	b	b	a	a	a
	d	d	d	d	d	c	c	c	c	c	c	b	b	b	b	b	b	a	a
	d	d	d	d	d	d	c	c	c	c	c	c	b	b	b	b	b	b	a
	e	d	d	d	d	d	d	c	c	c	c	c	c	b	b	b	b	b	b
	e	e	d	d	d	d	d	d	c	c	c	c	c	c	b	b	b	b	b
	e	e	e	d	d	d	d	d	d	c	c	c	c	c	c	b	b	b	b
	e	e	e	e	d	d	d	d	d	d	c	c	c	c	c	c	b	b	b
	e	e	e	e	e	d	d	d	d	d	d	c	c	c	c	c	c	b	b
	e	e	e	e	e	e	d	d	d	d	d	d	c	c	c	c	c	c	b
	f	e	e	e	e	e	e	d	d	d	d	d	d	c	c	c	c	c	c
	f	f	e	e	e	e	e	e	d	d	d	d	d	d	c	c	c	c	c
	f	f	f	e	e	e	e	e	e	d	d	d	d	d	d	c	c	c	c
	f	f	f	f	e	e	e	e	e	e	d	d	d	d	d	d	d	c	c
	f	f	f	f	f	e	e	e	e	e	e	d	d	d	d	d	d	d	c
	f	f	f	f	f	f	e	e	e	e	e	e	d	d	d	d	d	d	c
	g	f	f	f	f	f	f	e	e	e	e	e	e	d	d	d	d	d	d
	g	g	f	f	f	f	f	f	e	e	e	e	e	e	d	d	d	d	d
	max. 46,018	g	g	g	f	f	f	f	f	e	e	e	e	e	e	d	d	d	d

^a Letters, see [Table 9](#).

Table 9 — Combinations

Letters according to Table 8	Combinations
a	A + A
b	A + B
c	B + B
d	B + C
e	C + C
f	C + D
g	D + D

NOTE This scheme requires more complex logistics.

Table 10 — Bearing wall thickness

Grade	Bearing wall thickness mm
A	1,994 to 1,988
B	1,988 to 1,982
C	1,982 to 1,976
D	1,976 to 1,970

NOTE Clearance range: 0,026 mm to 0,044 mm.

British Standards Institution (BSI)

BSI is the national body responsible for preparing British Standards and other standards-related publications, information and services.

BSI is incorporated by Royal Charter. British Standards and other standardization products are published by BSI Standards Limited.

About us

We bring together business, industry, government, consumers, innovators and others to shape their combined experience and expertise into standards-based solutions.

The knowledge embodied in our standards has been carefully assembled in a dependable format and refined through our open consultation process. Organizations of all sizes and across all sectors choose standards to help them achieve their goals.

Information on standards

We can provide you with the knowledge that your organization needs to succeed. Find out more about British Standards by visiting our website at bsigroup.com/standards or contacting our Customer Services team or Knowledge Centre.

Buying standards

You can buy and download PDF versions of BSI publications, including British and adopted European and international standards, through our website at bsigroup.com/shop, where hard copies can also be purchased.

If you need international and foreign standards from other Standards Development Organizations, hard copies can be ordered from our Customer Services team.

Copyright in BSI publications

All the content in BSI publications, including British Standards, is the property of and copyrighted by BSI or some person or entity that owns copyright in the information used (such as the international standardization bodies) and has formally licensed such information to BSI for commercial publication and use.

Save for the provisions below, you may not transfer, share or disseminate any portion of the standard to any other person. You may not adapt, distribute, commercially exploit, or publicly display the standard or any portion thereof in any manner whatsoever without BSI's prior written consent.

Storing and using standards

Standards purchased in soft copy format:

- A British Standard purchased in soft copy format is licensed to a sole named user for personal or internal company use only.
- The standard may be stored on more than 1 device provided that it is accessible by the sole named user only and that only 1 copy is accessed at any one time.
- A single paper copy may be printed for personal or internal company use only.
- Standards purchased in hard copy format:
- A British Standard purchased in hard copy format is for personal or internal company use only.
- It may not be further reproduced – in any format – to create an additional copy. This includes scanning of the document.

If you need more than 1 copy of the document, or if you wish to share the document on an internal network, you can save money by choosing a subscription product (see 'Subscriptions').

Reproducing extracts

For permission to reproduce content from BSI publications contact the BSI Copyright & Licensing team.

Subscriptions

Our range of subscription services are designed to make using standards easier for you. For further information on our subscription products go to bsigroup.com/subscriptions.

With **British Standards Online (BSOL)** you'll have instant access to over 55,000 British and adopted European and international standards from your desktop. It's available 24/7 and is refreshed daily so you'll always be up to date.

You can keep in touch with standards developments and receive substantial discounts on the purchase price of standards, both in single copy and subscription format, by becoming a **BSI Subscribing Member**.

PLUS is an updating service exclusive to BSI Subscribing Members. You will automatically receive the latest hard copy of your standards when they're revised or replaced.

To find out more about becoming a BSI Subscribing Member and the benefits of membership, please visit bsigroup.com/shop.

With a **Multi-User Network Licence (MUNL)** you are able to host standards publications on your intranet. Licences can cover as few or as many users as you wish. With updates supplied as soon as they're available, you can be sure your documentation is current. For further information, email subscriptions@bsigroup.com.

Revisions

Our British Standards and other publications are updated by amendment or revision.

We continually improve the quality of our products and services to benefit your business. If you find an inaccuracy or ambiguity within a British Standard or other BSI publication please inform the Knowledge Centre.

Useful Contacts

Customer Services

Tel: +44 345 086 9001

Email (orders): orders@bsigroup.com

Email (enquiries): cservices@bsigroup.com

Subscriptions

Tel: +44 345 086 9001

Email: subscriptions@bsigroup.com

Knowledge Centre

Tel: +44 20 8996 7004

Email: knowledgecentre@bsigroup.com

Copyright & Licensing

Tel: +44 20 8996 7070

Email: copyright@bsigroup.com

BSI Group Headquarters

389 Chiswick High Road London W4 4AL UK