

BS ISO 14200:2012



BSI Standards Publication

Space environment (natural and artificial) — Guide to process-based implementation of meteoroid and debris environmental models (orbital altitudes below GEO + 2 000 km)

bsi.

...making excellence a habit.™

National foreword

This British Standard is the UK implementation of ISO 14200:2012.

The UK participation in its preparation was entrusted to Technical Committee ACE/68/-/4, Space systems and operations - Space environment (natural and artificial).

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2012. Published by BSI Standards Limited 2012

ISBN 978 0 580 67955 1

ICS 49.140

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 December 2012.

Amendments issued since publication

Date	Text affected
------	---------------

Space environment (natural and artificial) — Guide to process-based implementation of meteoroid and debris environmental models (orbital altitudes below GEO + 2 000 km)

Environnement spatial (naturel et artificiel) — Lignes directrices pour une mise en oeuvre fondée sur les processus des modèles environnementaux des météoroïdes et des débris (altitudes d'orbite inférieures à GEO + 2 000 km)





COPYRIGHT PROTECTED DOCUMENT

© ISO 2012

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative reference	1
3 Terms and definitions	1
4 Abbreviated terms	3
5 Guidelines for the implementation of meteoroid and space debris environmental models	4
5.1 Overview of the implementation concept.....	4
5.2 Impact fluxes estimation into a project.....	4
5.3 Meteoroid and debris model implementation procedure.....	4
5.4 Capabilities of meteoroid and space debris environment models.....	5
6 Traceability assurance	5
6.1 Overview of traceability concept.....	5
6.2 Assurance of traceability in a project.....	5
7 International project	5
Annex A (informative) Capability of meteoroid environment models	6
Annex B (informative) Capability of space debris environment models	8
Annex C (informative) Example of Comparison of Debris Flux Values among ORDEM2000, MASTER-2005 and MASTER2009	12
Bibliography	15

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 14200 was prepared by Technical Committee ISO/TC 20, *Aircraft and space vehicles*, Subcommittee SC 14, *Space systems and operations*.

Introduction

Every spacecraft or launch vehicle orbital stage in an Earth orbit is exposed to a certain flux of micrometeoroids and man-made space debris. Collisions with these particles take place with hypervelocity. The impact risk is evaluated in the design phases of a spacecraft or the launch vehicle orbital stage. Many meteoroid and space debris environment models have been studied and developed which describe populations of meteoroids and/or space debris. These models can be used as interim solutions for impact risk assessments and shielding design purposes. However, there are different methods in existence for reproducing the observed environment by means of mathematical and physical models of release processes, for propagating orbits of release products, and for mapping the propagated environment onto spatial and temporal distributions of objects densities, transient velocities, and impact fluxes. Until a specific standard for the space debris environment is defined, a common implementation process of models should be indicated for impact risk assessment and design of a spacecraft.

Space environment (natural and artificial) — Guide to process-based implementation of meteoroid and debris environmental models (orbital altitudes below GEO + 2 000 km)

1 Scope

This International Standard specifies the common implementation process for meteoroid and debris environment models for risk assessment of spacecraft and launch vehicle orbital stages. This International Standard gives guidelines for the selection process of models for impact risk assessment and ensures the traceability of using models throughout the design phase of a spacecraft or launch vehicle orbital stage.

2 Normative reference

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 17666:2003, *Space systems — Risk management*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 17666 and the following apply.

3.1

engineering model

environment model that provides clear and concise information that engineers need

3.2

geostationary Earth orbit

Earth orbit having zero inclination and zero eccentricity; whose orbital period is equal to the Earth's sidereal rotation period

[SOURCE: ISO 24113:2011, definition 3.8]

3.3

geosynchronous Earth orbit

Earth orbit with an orbital period equal to the Earth's sidereal rotation period

3.4

gravitational focusing

force of the Earth's gravitational field that attracts meteoroids, changes their trajectories, and therefore increases the flux

3.5

impact flux

number of impacts per unit area and per unit period

3.6

impact risk

risk of impact against meteoroids and debris on spacecraft

- 3.7**
interplanetary
applicable regime of the meteoroid environment model from Earth with astronomical units (AU)
- 3.8**
launch vehicle orbital stage
stage of a launch vehicle that is designed to achieve orbit
[SOURCE: ISO 24113:2011, definition 3.9]
- 3.9**
low earth orbit
Earth orbit with an apogee altitude that does not exceed 2 000 km
- 3.10**
mass density
mass per unit volume
- 3.11**
meteoroid
particles of natural origin that result from the disintegration and fragmentation of comets and asteroids which orbit round the sun
- 3.12**
meteorid / (space) debris environment(al) model
tool that simulates realistic descriptions of the meteoroid and debris environment of Earth, and performs risk assessment via flux predictions on user defined target orbit
- 3.13**
space debris
(orbital debris) man-made objects, including fragments and elements thereof, in Earth's orbit or re-entering the atmosphere, that are non-functional
[SOURCE: ISO 24113:2011, definition 3.17]
- 3.14**
space system
system consisting of a space segment that includes a launch segment, spacecraft segment and a ground segment with a tracking control segment and a mission segment
[SOURCE: ISO 23041:2007]
- 3.15**
spacecraft
system designed to perform specific tasks or functions in space
[SOURCE: ISO 24113:2011, definition 3.18]
- 3.16**
traceability
ability to trace the history, application or location of that which is under consideration
[SOURCE: ISO 9000:2005]

4 Abbreviated terms

AU	Astronomical Units
CME	Chemistry of Meteoroid Experiment
DISCOS	Database and Information System Characterising Objects in Space
ESA	European Space Agency
EuReCa	EUropean REtrievable CARrier
GEO	Geostationary Earth Orbit
GUI	Graphical User Interface
HAX	Haystack Auxiliary Radar
HST	Hubble Space Telescope
HST-SA	Hubble Space Telescope Solar Array
HST (SM1)	Hubble Space Telescope (Service Mission 1)
HST (SM3B)	Hubble Space Telescope (Service Mission 3B)
IDES	Integrated Debris Evolution Suite
IMEM	Interplanetary Meteoroid Engineering Model
ISO	International Organization for Standardization
ISS	International Space Station
LDEF	Long Duration Exposure Facility
LEGEND	LEO- to -GEO Environment Debris Model
LEO	Low Earth Orbit
MASTER	Meteoroid and Space Debris Terrestrial Environment Reference
MEM	Meteoroid Engineering Model
MSFC	Marshall Space Flight Center
NASA	National Aeronautics and Space Administration
ORDEM	Orbital Debris Engineering Model
PROOF	Program for Radar and Observation Forecasting
SDMP	Space Debris Mitigation Plan
SSN	Space Surveillance Network
SSP	Space Station Program
STS	Space Transportation System

5 Guidelines for the implementation of meteoroid and space debris environmental models

5.1 Overview of the implementation concept

5.1.1 If an impact flux assessment is required, it shall be performed in accordance with the risk management process specified by ISO 17666.

5.1.2 The results of an impact flux assessment, the methodology used, and any assumptions made shall be documented.

NOTE Impact flux assessments are sometimes performed in order to satisfy the requirements of a Space Debris Mitigation Plan (SDMP). See Reference [1] for a description of the content of an SDMP.

5.2 Impact fluxes estimation into a project

When a spacecraft or launch vehicle orbital stage is designed or planned, the risk caused by impacts of meteoroids and space debris shall be evaluated. For the risk assessment, impact fluxes of meteoroids and space debris on the spacecraft or launch vehicle orbital stage shall be estimated.

5.3 Meteoroid and debris model implementation procedure

5.3.1 General

Impact fluxes on a spacecraft or launch vehicle orbital stage are calculated using a combination of design data (i.e. configuration, orbit), meteoroid environment model and space debris environment model. When the meteoroid environment model and space debris environment model applies to a spacecraft or launch vehicle orbital stage design; the following procedure should be followed.

5.3.1.1 Step 1: Model selection agreement

The model(s) which is (are) applied to a spacecraft or launch vehicle orbital stage design is (are) selected by mutual agreement between the customer and the supplier of the spacecraft or launch vehicle orbital stage. Moreover, the traceability of the model(s) application shall be ensured.

5.3.1.2 Step 2: Model selection

To select a suitable environment model for the mission of a spacecraft or launch vehicle orbital stage, the customer and the supplier should consider the capabilities of candidate models. Model capabilities are described in 5.4.

When selecting a model, consideration should be given to the fact that environment models have uncertainties which can lead to large differences in the flux results. It is recommended that the customer and the supplier compare the flux results from several models.

5.3.1.3 Step 3: implementation of meteoroid and space debris environment models on a project

When implementing an environment model on a project there are several important considerations, such as traceability of the development of the model, its maintenance, and user convenience. The following approaches are recommended to estimate the impact fluxes on a spacecraft design and/or component design:

- a) Engineering models (analysis codes) which are institutionally maintained by national agencies are considered as candidates for applicable models for the design.
- b) When a critical component is designed, the model which produces the maximum risk (the worst case) is selected among candidate models.

The use of models other than those listed in 5.4 is permissible.

5.4 Capabilities of meteoroid and space debris environment models

5.4.1 Meteoroid environment models

Capabilities of meteoroid environment models are described in Annex A. Comparison of impact fluxes among models are described in Reference [4].

5.4.2 Space debris environment models

Capabilities of space debris environment models are described in Annex B. Comparison of impact fluxes among three engineering models, which are published by NASA and ESA, are described in References [5], [6], [7]. An example of comparison impact flux among three models is described in Annex C for information.

6 Traceability assurance

6.1 Overview of traceability concept

Traceability of the meteoroid and space debris model application process shall be guaranteed in all design phases of a spacecraft.

6.2 Assurance of traceability in a project

6.2.1 Risk assessments of meteoroid and space debris impacts

When risk assessments of meteoroid and space debris impacts are required, the following items shall be recorded in each design phase of the spacecraft or launch vehicle orbital stage:

- a) the justification for the selected spacecraft risk assessment model;
- b) all input and output parameters and their values;
- c) any assumptions made regarding the input design parameters, and the reasons for those assumptions;
- d) any corrections made to output parameters, reasons for the corrections and any assumptions made, and details of correction methods and correction results.

NOTE Output parameters can be corrected by applying a safety factor, life factor or margin of safety. Such corrections can also take into account new information on the debris population. For example, since the publication of space debris environment models, such as ORDEM2000 and MASTER-2005, there have been a number of important debris generation events. These events could have a significant influence on a risk assessment.

6.2.2 Design Review

The contents of the items listed in 6.2.1, and their validity, shall be evaluated and confirmed by reviewers during the Design Review (DR) in each phase of the design.

7 International project

For an international project, it is recommended that the following items be agreed amongst member bodies before starting the project:

- a) applied meteoroid and space debris environment model(s) to the project;
- b) method of maintenance of the meteoroid and space debris environment model(s);
- c) the procedure for impact risk assessment.

Annex A (informative)

Capability of meteoroid environment models

A.1 Model overview

A.1.1 Grün et al. model

The Grün model^[6] assumes an isotropic meteoroid distribution which is based on lunar crater, zodiacal light and *in situ* measurement data.

A.1.2 Divine model

The Divine model^[7] assumes a non-isotropic distribution which is based on five populations in particle mass, inclination, eccentricity and perihelion distance.

A.1.3 Divine-Staubach model

The Divine-Staubach model^[8] is a follow-up of the Divine model, using new data from GALILEO and ULYSSES dust detectors.

A.1.4 NASA SSP-30425 model

The SSP-30425 (Space Station Program Natural Environment Definition for Design) model^[9] describes a space environment for ISS design.

A.1.5 IMEM model

Dikarev used an improved and controlled data set and applied refined mathematical methods in order to describe three-dimensional distributions of orbital elements (instead of the mathematically separable distributions of Divine).^[10]

A.1.6 MEM model

Near 1 AU fluxes are calibrated from the Grün model. A constant mass density of 1,0 g/cm³ is assumed and the velocity distributions are independent from the particle sizes.^[11]

A.2 Model specifications

Table A.1 — Meteoroid model specifications

Model specifications	Model					
	Grün et al. Reference [6]	Divine Reference [7]	Divine- Staubach Reference [8]	SSP 30425 (ISS) Reference [9]	IMEM (ESA) Reference [10]	MEM (MSFC) Reference [11]
Sporadic or stream	Sporadic	Sporadic	Sporadic	Sporadic	Sporadic	Sporadic
Interplanetary	No	0,1 to 20 AU	0,1 to 20 AU	No	0,1 to 10 AU	0,2 to 2 AU
NOTE It was found that the Divine-Staubach approach fits the requirements of the MASTER model best. Thus, only the Divine approach and the extensions introduced by Staubach are implemented in the model [12].						

Table A.1 (continued)

Model specifications	Model					
	Grüen et al. Reference [6]	Divine Reference [7]	Divine- Staubach Reference [8]	SSP 30425 (ISS) Reference [9]	IMEM (ESA) Reference [10]	MEM (MSFC) Reference [11]
Mass/range	10 ⁻¹⁸ to 10 ² g	10 ⁻¹⁸ to 1 g	10 ⁻¹⁸ to 1 g	10 ⁻¹⁸ to 10 ² g	10 ⁻¹² to 10 ² g	10 ⁻⁶ to 10 g
Near Earth	Yes	Yes	Yes	Yes	Yes	Yes
Gravitational focusing	No	Earth only	Earth only	Earth only	Earth only	Earth only
Planetary shielding	No	Earth only	Earth only	Earth only	Earth only	Earth only
Sources of meteoroids	Not identified explicitly	-Asteroidal, -Core, -Halo, -Inclined, -Eccentric populations	-A, B, C , -Asteroidal, -Core, -Inter-stellar dust populations	Not identified explicitly	-Asteroids, -"Jupiter-crossing comets", -Inter-stellar dust (<10 ⁻⁹ g)	6 radar/photographic meteor sources (Helion, Anti-Helion, North Apex, South Apex, North Toroidal, South Toroidal)
Velocity distribution	Single value (20 km/s)	Yes	Yes	Yes (Kessler)	Yes	Yes
Mass density	Single value (2,5 g/cm ³)	2 g/cm ³ (m < 10 ⁻⁶ g); 1 g/cm ³ (10 ⁻⁶ - 10 ⁻² g); 0.5 g/cm ³ (m > 10 ⁻² g)	2 g/cm ³ (m < 10 ⁻⁶ g); 1 g/cm ³ (10 ⁻⁶ - 10 ⁻² g); 0.5 g/cm ³ (m > 10 ⁻² g)	2 g/cm ³ (m < 10 ⁻⁶ g); 1 g/cm ³ (10 ⁻⁶ - 10 ⁻² g); 0.5 g/cm ³ (m > 10 ⁻² g)	Single value (2,5 g/cm ³)	Single value (1 g/cm ³)
Primary data source	-In situ experiments, -zodiacal light, lunar crater record. -Gruen et al. flux is identical to the 1970 Zook flux for m > 10 ⁻⁷ g	-Zodiacal light, -Harvard Radio Meter Project (HRMP) data	-Staubach refit the probability densities, taking account into Ulysses and Galileo spacecraft	Not identified explicitly	-In situ experiments (Ulysses, Galileo), -COBER IR, -lunar crater record. -No zodiacal light data. -Disregard AMOR data	Canadian Meteor Orbit Radar (CMOR) data
Key assumptions	Flux on Earth is isotropic	Calibrated to the Grüen flux	Calibrated to the Grüen flux	Grüen flux with Kessler's velocity distribution and modified mass density	Calibrated to the Grüen flux	Calibrated to the Grüen flux
Release data	1985	1993	1996	1994 (Revision)	2004	2006 (MEM 1.6, EarthMEM 1.0)
NOTE It was found that the Divine-Staubach approach fits the requirements of the MASTER model best. Thus, only the Divine approach and the extensions introduced by Staubach are implemented in the model [12].						

Annex B (informative)

Capability of space debris environment models

B.1 General

This Annex provides guidance for engineers in the selection and use of models that are suitable for his/her specific mission needs.

In regards to impact risk assessment, debris flux models (See B.2) should be considered for spacecraft or launch vehicle orbital stage design. Debris propagation (evolutionary) models (See B.3) should be considered for the study of a long-term debris environment and should not be applicable for impact risk assessment in the design phase.

B.2 Debris flux models

B.2.1 Model overview

B.2.1.1 DAMAGE model

The DAMAGE model^{[13] [14] [15]} aims to account for the unique characteristics involved in modelling the full LEO to GEO environment.

B.2.1.2 IDES model

The IDES model^{[16] [17] [18] [19] [20] [21]} is able to study historical, current and future space debris populations, in addition to providing directional collision risk assessments for satellites in the full LEO to GEO debris environment.

B.2.1.3 MASTER2005 model

The MASTER2005 model^[12] is based on semi-deterministic analysis that includes orbit propagation of debris from all major debris sources and can estimate the meteoroid environment. The applicable scope of MASTER2005 is an altitude between 186 km and 36 786 km and an impact object diameter between 1 µm and 10 m.

B.2.1.4 MASTER2009 model

The MASTER2009 model^[22] is an upgraded version of MASTER2005. The applicable scope of MASTER2009 is an altitude between 186 km and 36 786 km and an impact object diameter between 1 µm and 10 m.

B.2.1.5 ORDEM2000 model

The ORDEM2000 model^[23] is an empirical model based on ground-based observation data and surface inspection results of objects retrieved from orbit. The applicable scope of ORDEM2000 is an altitude between 200 km and 2 000 km and a debris diameter between 10 µm and 1 m.

B.2.1.6 SPDA model

The SPDA model^{[12] [22] [23]} is a semi-analytical stochastic model for medium- and long-term forecast of the debris environment (larger than 1 mm), for construction of spatial density, and velocity distribution in LEO and GEO, as well as, for risk evaluation.

B.2.2 Model specifications

Table B.1 — Debris flux model specifications

Model specifications	Model					
	DAMAGE References [13] [14] [15]	IDES References [16] [17] [18] [19] [20] [21]	MASTER 2005 Reference [12]	MASTER 2009 Reference [22]	ORDEM 2000 Reference [23]	SPDA Reference [12] [22] [23]
Source	Southampton University	DERA	ESA	ESA	NASA	RSA
Modelling approach	Statistical and near-deterministic methods	Semi deterministic analysis	Semi deterministic analysis	Semi deterministic analysis	Measurement data	Semi deterministic analysis
Applicable regime						
a) minimum size	1 mm	> 10 µm	> 1 µm	> 1 µm	> 10 µm	> 1 mm
b) orbital regime	120 to 37 786 km	LEO to GEO	186 to 36 786 km	186 to 36 786 km	200 to 2 000 km	400 to 2 000, 35 300 to 36 200 km
c) evolutionary period	Long term	Short and long term	1958 to 2050	1957 to 2055	1991 to 2030	Medium and long term
Input parameter	Target orbit semi-major axis: - -Eccentricity, -Inclination, -Right ascension of ascending node, -Argument of perigee	—	Target orbit scenario: -Semi-major axis, -Eccentricity, -Inclination, -Right asc. of asc. node, -Argument of perigee Inertial Volume Scenario: -Geocentric distance, -Right ascension, -Declination Spatial Density Scenario: -Lower/upper altitude limit, -Lower/upper decline. limit	Target orbit scenario: -Semi-major axis, -Eccentricity, -Inclination, -Right asc. of asc. node, -Argument of perigee Inertial Volume Scenario: -Geocentric distance, -Right ascension, -Declination Spatial Density Scenario: -Lower/upper altitude limit, -Lower/upper decline. limit	-Apo/Peri -Altitude -Semi-major axis -Eccentricity -Inclination -Argument of perigee	—

Table B.1 (continued)

Model specifications	Model					
	DAMAGE References [13] [14] [15]	IDES References [16] [17] [18] [19] [20] [21]	MASTER 2005 Reference [12]	MASTER 2009 Reference [22]	ORDEM 2000 Reference [23]	SPDA Reference [12] [22] [23]
Output data	-Spatial density versus altitude, -Spatial density versus inclination, -Number of objects versus time, -Cumulative number of collisions versus time	—	Flux versus size, -Mass, -Semi-major axis, -Eccentricity, -Inclination, -Altitude, -Latitude, -Impact velocity, -Impact declination, -Time, etc. Spatial density versus size: -Mass, -Altitude, -Declination, -Time	Flux versus size, -Mass, -Semi-major axis, -Eccentricity, -Inclination, -Altitude, -Latitude, -Impact velocity, -Impact declination, -Time, etc. Spatial density versus size: -Mass, -Altitude, -Declination, -Time	-Flux versus size, -Orbit position, -Altitude, -Latitude	—
Debris source terms						
a) TLE background	Yes (or simulated from historical launch and fragmentation data)	—	Yes	Yes	All sources together	All sources together
b) Fragments	Yes	—	Yes	Yes	All sources together	All sources together
c) SRM dust/slag	TBC	—	Yes	Yes	All sources together	All sources together
d) NaK droplets	TBC	—	Yes	Yes	All sources together	All sources together
e) Paint flakes	no (TBC)	—	Yes	Yes	All sources together	All sources together
f) West ford needles	TBC (Currently included if catalogued)	—	Yes	Yes	All sources together	All sources together
g) MLI fragments	—	—	None	Yes	All sources together	All sources together
Meteoroid						
a) background	None	None	Divine-Staubach	Diving-Staubach	None	None
b) streams	None	None	Jenniskens-McBride, Cour-Palais	Jenniskens-McBride, Cour-Palais	None	None
Primary data source/validation	-DISCOS Database, -IDES, -MASTER, -LEGEND	—	-LDEF, -CME, -HST (SM1, SM3B), -EuReCa, -PROOF 2005	-LDEF, -CME, -HST (SM1, SM3B), -EuReCa, -PROOF 2009	-SSN, catalogue, -LDEF, -Haystack radar, -HST-SA. -STS window and radiator, -HAX, -Goldstone radar	—

Table B.1 (continued)

Model specifications	Model					
	DAMAGE References [13] [14] [15]	IDES References [16] [17] [18] [19] [20] [21]	MASTER 2005 Reference [12]	MASTER 2009 Reference [22]	ORDEM 2000 Reference [23]	SPDA Reference [12] [22] [23]
Model features	-LEO-to-GEO (including GTO), -Mitigation and removal strategies, -GUI	—	-Flux to spheres, -Orientated surf., -GUI, -Time browser	-Flux to spheres, -Orientated surf., -GUI, -Time browser	—	—
Engineering model available for intentional use	No engineering model but Particles-in-a-box model (called FADE) is available (Further details on request).	No	Yes	Yes	Yes	No

B.3 Debris propagation (evolutionary) models

B.3.1 Model overview

B.3.1.1 LEGEND model

The LEGEND model^{[27] [28]} is capable of reproducing the historical debris environment as well as performing future debris environment projection. The applicable scope of LEGEND is an altitude between 200 and 40 000 km and outputs debris distributions in one-dimensional (altitude), two-dimensional (altitude, latitude), and three-dimensional (altitude, latitude, longitude) formats.

B.3.1.2 LEODEEM model

The LEODEEM model^{[29] [30]} calculates LEO debris evolution (less than 2 000 km altitude of perigee) taking into account collisions, and future launch traffic. It becomes possible to predict a long term LEO environment and investigate future mission hazard evaluation by using this model.

B.3.1.3 GEODEEM model

The GEODEEM model^[31] calculates GEO debris evolution taking into account collisions, and future launch traffic. Emphasis has been placed on the rate of collisions in the geosynchronous Earth orbit and in the higher collection orbits and on the significance of cross-regime contamination.

NOTE Some models identified in B.2 (DAMAGE, IDES, SPAD) can also be used for long-term evolutionary analyses.

Annex C (informative)


Example of Comparison of Debris Flux Values among ORDEM2000, MASTER-2005 and MASTER2009

Figure C.1 provides examples of debris flux results from three different models (i.e. ORDEM2000, MASTER2005 and MASTER2009). Details are discussed in References [12], [22], [23].


The calculation conditions, shown in Table C.1, are altitudes between 300 km and 2 000 km with a step size of 100 km, inclinations of 100 degrees, circular orbit, and an epoch of 2 000. The calculation results of the cumulative flux of debris > 10 µm in diameter, > 100 µm, > 1 mm, > 1 cm, > 10 cm, and > 1 m, as the function of altitude are shown in Figure C.1.

Table C.1 — Calculation conditions of models comparison


Parameter	Calculation condition
Altitude (km)	300 - 2 000
Inclination (degree)	110
Size range (m)	10 ⁻⁵ - 1
Step size ^a (km)	100
Step size ^b (log scale)	1
Resulting data	Cumulative flux
Debris	Yes
Meteoroids	None
^a Altitude ^b Size range	




a) Diameter > 10 µm




b) Diameter > 100 µm




c) Diameter > 1 mm



d) Diameter > 1 cm



e) Diameter > 10 cm



f) Diameter > 1 m

Figure C.1 — Flux against altitude at inclination 100°

Bibliography

- [1] ISO 24113:2011, *Space systems — Space debris mitigation requirements*
- [2] ISO 23041:2007, *Space systems — Unmanned spacecraft operational procedures — Documentation*
- [3] ISO 9000:2005, *Quality management systems — Fundamentals and vocabulary*
- [4] DROLSHAGEN G., DIKAREV V., LANDGRAF M., KRAG H., KUIPER W., Comparison of Meteoroid Flux Models for Near Earth Space. *Earth Moon Planets*. 2008, 102 (1-4), pp. 191–197
- [5] FUKUSHIGE S., AKAHOSHI Y., KITAZAWA Y., GOKA T., Comparison of Debris Environment Models; Ordem2000, Master2001 and Master2005. In *Engineering Review*. 2007, 40 (1), pp. 31–41
- [6] GRUEN E. et al., Collisional Balance of Meteoritic Complex. *Icarus*. 1985, 62, pp. 244–272
- [7] DIVINE N. Five Populations of Interplanetary Meteoroids. *J. Geophys. Res.*, 1993, 98, (No. E9), pp. 17,029–17,048
- [8] DIKAREV V. et al., Towards a New Model of the Interplanetary Meteoroid Environment. *Adv. Space Res.* 2002, 29, (28), pp. 1171–1175
- [9] KESSLER D.J., “Space Station Program Natural Environment Definition for Design, International Space Station Alpha.” In: NASA SSP 30425, Revision B. National Aeronautics and Space Administration Space Station Program Office, Houston, 1994
- [10] DIKAREV V. et al. The New ESA Meteoroid Model. *Adv. Space Res.* 2005, 35, pp. 1282–1289
- [11] MCNAMARA H. et al., Meteoroid engineering model (mem): a meteoroid model for the inner solar system. *Earth Moon Planets*. 2004, 95, pp. 123–139
- [12] OSWALD, M. et al., MASTER-2005 Final Report, Institute of Aerospace Systems, April 2006
- [13] LEWIS H.G. et al., “Damage: A Dedicated Geo Debris Model Framework”, In: Proceedings of the Third European Conference on Space Debris, Darmstadt, Germany, 19–21 March, 2001
- [14] LEWIS H.G. et al., “Active Removal Study for On-Orbit Debris Using Damage”, In: Proceedings of the Fifth European Conference on Space Debris, Darmstadt, Germany, 30 March – 2 April 2009, ESA SP-672, July 2009
- [15] NÖLKE, D., REIMERDES, H.-G., “Risk Analysis and Damage Prediction of Small Spacecraft”, In Proceedings of the Fifth European Conference on Space Debris, Darmstadt, Germany, 30 March –2 April 2009, ESA SP-672, July 2009
- [16] LEWIS, H.G. et al., “Debris Spatial Density Dependence on Control Volume Resolution in the Geosynchronous Environment”, 35th COSPAR Scientific Assembly, 18-25 July 2004, in Paris, France, pp. 2912
- [17] WALKER, R. et al., “Enhancement and Validation of the Ides Orbital Debris Environment Model”, Springer Netherlands, 1, Number 1, 1999, pp. 1-19(19)
- [18] JEHN R. et al. Comparison of the 1999 Experiment Results with Beam-Park Space Debris Models. *Adv. Space Res.* 2001, 28, pp. 1367–1375
- [19] WALKER R. et al., Long-term Collision Risk Prediction for Low Earth Orbit Satellite Constellations. *Acta Astronaut.* 2000, 47, pp. 707–717
- [20] WALKER R. et al., “Studying the Meo & Geo Space Debris Environments with the Integrated Debris Evolution Suite (Ides) Model”, In: Proceedings of the Third European Conference on Space Debris, Noordwijk, Netherlands, 2001

- [21] WALKER R. et al., "A Comparison of Ides Model Predictions with Debris Measurement Data", Second European Conference on Space Debris, Organised by ESA, held 17-19 March, 1997, ESOC, Darmstadt, Germany, ESA-SP 393, pp. 239
- [22] Flegel, S. et al., MASTER2009 Final Report, Institute of Aerospace Systems, June, 2011
- [23] LIOU J.-C. et al., "The New NASA Orbital Debris Engineering Model ORDEM2000", NASA/TP-2002-210780, 2002. <http://orbitaldebris.jsc.nasa.gov/model/engrmodel.html>
- [24] SDUNNUS H. et al., Comparison of Debris Flux Models. *Adv. Space Res.* 2004, **34**, pp. 1000–1005
- [25] ANDREY I. et al. "Engineering Model of Space Debris Environment", In: Proceedings of the Third European Conference on Space Debris, 19-21 March 2001, Darmstadt, Germany. Ed.: Huguette Sawaya-Lacoste. ESA SP-473, Vol. 1, Noordwijk, Netherlands: ESA Publications Division, ISBN 92-9092-733-X, 2001, pp. 293-298
- [26] NAZARENKO A.I. "Collision of Spacecraft with Debris Particles Assessment", In: Proceedings of 17th International Symposium on SPACE FLIGHT DYNAMICS, 16-20 June 2003, Russia, Moscow
- [27] LIOU J.-C. A Statistical Analysis of the Future Debris Environment. *Acta Astronaut.* 2008, **62**, pp. 264–271
- [28] LIOU J.-C. et al., LEGEND - A Three-dimensional LEO-to-GEO Debris Evolutionary Model. *Adv. Space Res.* 2004, **34**, pp. 981–986
- [29] NARUMI T. et al. *Space Debris Environmental Evolutionary Model in Low Earth Orbit*. The Japan Society for Aeronautical and Space Sciences, **7**, 2008, pp. 1–17.
- [30] MANIWA K. et al., *Instability of the Current Space Debris Population in Low Earth Orbit*, The Japan Society for Aeronautical and Space Sciences, **58**, No. 674, 2010, pp. 83-89
- [31] HANADA T., *Consequences of Continued Growth in the GEO and GEO Disposal Orbital Regimes*, The Japan Society for Aeronautical and Space Sciences, **50**, No. 577, 2002, pp. 48-55
- [32] KANEMITSU Y., AKAHOSHI Y., NARUMI T., MATSUMOTO H., KITAZAWA Y. *Comparison of Space Debris Environment Models*, The Japan Society for Aeronautical and Space Sciences Western Branch. JSASS, 2011, pp. 2011–S014
- [33] KANEMITSU Y., AKAHOSHI Y., NARUM T., FAURE P., MATSUMOTO H., KITAZAWA Y., Comparison of Space Debris Environment Models: ORDEM2000, MASTER-2001, MASTER-2005 and MASTER-2009, JAXA-RM-11-020E, 2012

British Standards Institution (BSI)

BSI is the national body responsible for preparing British Standards and other standards-related publications, information and services.

BSI is incorporated by Royal Charter. British Standards and other standardization products are published by BSI Standards Limited.

About us

We bring together business, industry, government, consumers, innovators and others to shape their combined experience and expertise into standards-based solutions.

The knowledge embodied in our standards has been carefully assembled in a dependable format and refined through our open consultation process. Organizations of all sizes and across all sectors choose standards to help them achieve their goals.

Information on standards

We can provide you with the knowledge that your organization needs to succeed. Find out more about British Standards by visiting our website at bsigroup.com/standards or contacting our Customer Services team or Knowledge Centre.

Buying standards

You can buy and download PDF versions of BSI publications, including British and adopted European and international standards, through our website at bsigroup.com/shop, where hard copies can also be purchased.

If you need international and foreign standards from other Standards Development Organizations, hard copies can be ordered from our Customer Services team.

Subscriptions

Our range of subscription services are designed to make using standards easier for you. For further information on our subscription products go to bsigroup.com/subscriptions.

With **British Standards Online (BSOL)** you'll have instant access to over 55,000 British and adopted European and international standards from your desktop. It's available 24/7 and is refreshed daily so you'll always be up to date.

You can keep in touch with standards developments and receive substantial discounts on the purchase price of standards, both in single copy and subscription format, by becoming a **BSI Subscribing Member**.

PLUS is an updating service exclusive to BSI Subscribing Members. You will automatically receive the latest hard copy of your standards when they're revised or replaced.

To find out more about becoming a BSI Subscribing Member and the benefits of membership, please visit bsigroup.com/shop.

With a **Multi-User Network Licence (MUNL)** you are able to host standards publications on your intranet. Licences can cover as few or as many users as you wish. With updates supplied as soon as they're available, you can be sure your documentation is current. For further information, email bsmusales@bsigroup.com.

BSI Group Headquarters

389 Chiswick High Road London W4 4AL UK

Revisions

Our British Standards and other publications are updated by amendment or revision.

We continually improve the quality of our products and services to benefit your business. If you find an inaccuracy or ambiguity within a British Standard or other BSI publication please inform the Knowledge Centre.

Copyright

All the data, software and documentation set out in all British Standards and other BSI publications are the property of and copyrighted by BSI, or some person or entity that owns copyright in the information used (such as the international standardization bodies) and has formally licensed such information to BSI for commercial publication and use. Except as permitted under the Copyright, Designs and Patents Act 1988 no extract may be reproduced, stored in a retrieval system or transmitted in any form or by any means – electronic, photocopying, recording or otherwise – without prior written permission from BSI. Details and advice can be obtained from the Copyright & Licensing Department.

Useful Contacts:

Customer Services

Tel: +44 845 086 9001

Email (orders): orders@bsigroup.com

Email (enquiries): cservices@bsigroup.com

Subscriptions

Tel: +44 845 086 9001

Email: subscriptions@bsigroup.com

Knowledge Centre

Tel: +44 20 8996 7004

Email: knowledgecentre@bsigroup.com

Copyright & Licensing

Tel: +44 20 8996 7070

Email: copyright@bsigroup.com



...making excellence a habit.™