

BS ISO 14878:2015



BSI Standards Publication

Cycles — Audible warning devices — Technical specification and test methods

bsi.

...making excellence a habit.™

National foreword

This British Standard is the UK implementation of ISO 14878:2015.

The UK participation in its preparation was entrusted to Technical Committee GME/25, Cycles.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2015.
Published by BSI Standards Limited 2015

ISBN 978 0 580 78924 3

ICS 43.150

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 December 2015.

Amendments/corrigenda issued since publication

Date	Text affected
------	---------------

INTERNATIONAL
STANDARD

ISO
14878

First edition
2015-12-15

**Cycles — Audible warning devices
— Technical specification and test
methods**

*Cycles — Dispositifs avertisseurs sonores — Spécifications techniques
et méthodes d'essai*



Reference number
ISO 14878:2015(E)

© ISO 2015



COPYRIGHT PROTECTED DOCUMENT

© ISO 2015, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

Page

Foreword	iv
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Symbols and abbreviated terms	2
5 Instrumentations	2
5.1 Instruments for acoustical measurement.....	2
5.1.1 General.....	2
5.1.2 Calibration.....	2
5.1.3 Compliance with requirements.....	2
5.1.4 Meteorological Instrumentation.....	2
6 Acoustical environment, meteorological conditions, and background noise	3
6.1 Test site.....	3
6.2 Meteorological conditions.....	3
6.3 Background noise.....	3
6.4 Mounting of the AWD.....	4
6.5 Microphone and AWD positions.....	4
7 Measurement of the sound pressure level	4
7.1 Actuation of the AWD.....	4
7.2 Measurement readings and reported values.....	4
7.2.1 General.....	4
7.2.2 Data compilation.....	4
7.3 Required sound pressure.....	5
7.4 Low battery indicator.....	5
8 Test of durability	5
8.1 Test procedure.....	5
8.1.1 Stability mechanical test.....	5
8.1.2 Corrosion test.....	6
8.2 Test result.....	6
9 Test report	6
10 Marking	6

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: [Foreword - Supplementary information](#)

The committee responsible for this document is ISO/TC 149, *Cycles*, Subcommittee SC 1, *Cycles and major sub-assemblies*.

Cycles — Audible warning devices — Technical specification and test methods

1 Scope

This International Standard lays down the technical specifications, such as the sound pressure level and the durability, and specifies the corresponding test method for audible warning devices (AWD) which may be fitted to cycles.

This International Standard applies to all types of audible warning devices (AWD) for use on bicycles.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 9227, *Corrosion test in artificial atmosphere — Salt spray tests*

ISO 26101, *Acoustics — Test methods for the qualification of free-field environments*

IEC 60942, *Electroacoustics — Sound calibrators*

IEC 61672-1, *Electroacoustics — Sound level meters — Part 1: Specifications*

IEC 61672-3, *Electroacoustics — Sound level meters — Part 3: Periodic tests*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

cycle

any vehicle that has at least two wheels and is propelled solely or mainly by the muscular energy of the person on that vehicle, in particular by means of pedals

3.2

bicycle

two-wheeled cycle

3.3

audible warning device

AWD

device designed for the purpose to warn people by an audible signal

Note 1 to entry: Including all types of technologies (i.e. bells, horns, electronic audible warning device).

3.4

audible warning device class I

AWD designed for general purpose

3.5

audible warning device class II

AWD designed for purpose of use in area primarily shared by pedestrians and cyclists, such as a pedestrian zone

4 Symbols and abbreviated terms

AWD Audible warning device

5 Instrumentations

5.1 Instruments for acoustical measurement

5.1.1 General

The apparatus used for measuring the sound pressure level shall be a sound level meter or equivalent measurement system meeting the requirements of class 1 instruments (inclusive of the recommended windscreen, if used). These requirements are described in IEC 61672-1.

The entire measurement system shall be checked by means of a sound calibrator that fulfils the requirements of class 1 sound calibrators according to IEC 60942.

Measurements shall be carried out using the time weighting “F” of the acoustic measurement instrument and the “A” frequency weighting curve also described in IEC 61672-1. When using a system that includes a periodic monitoring of the A-weighted sound pressure level, a reading should be made at a time interval not greater than 30 ms.

The instruments shall be maintained and calibrated in accordance to the instructions of the instrument manufacturer.

When no general statement or conclusion can be made about conformance of the sound level meter model to the full specifications of IEC 61672-1, the apparatus used for measuring the sound pressure level shall be a sound level meter or equivalent measurement system meeting the requirements of class 1 instruments as described in IEC 61672-3.

NOTE The tests of IEC 61672-3 cover only a limited subset of the specifications in IEC 61672-1 for which the scope is large (temperature range, frequency requirements up to 20 kHz, EMC tests). It is economically impossible to verify the whole IEC 61672-1 standard requirements one each item of a computerized data acquisition systems model.

5.1.2 Calibration

At the beginning and at the end of every measurement session, the entire acoustic measurement system shall be checked by means of a sound calibrator as described in [5.1.1](#). Without any further adjustment, the difference between the readings shall be less than or equal to 0,5 dB. If this value is exceeded, the results of the measurements obtained after the previous satisfactory check shall be discarded.

5.1.3 Compliance with requirements

Compliance of the sound calibrator with the requirements of IEC 60942 shall be verified once a year.

Compliance of the instrumentation system with the requirements of IEC 61672-3 shall be verified at least every two years.

All compliance testing shall be conducted by a laboratory which is authorized to perform calibrations traceable to the appropriate standards.

5.1.4 Meteorological Instrumentation

The meteorological instrumentation used to monitor the environmental conditions during the test shall meet the following specifications:

— ± 1 °C or less for a temperature measuring device;

- $\pm 1,0$ m/s for a wind speed-measuring device;
- ± 5 hPa for a barometric pressure measuring device;
- ± 5 % for a relative humidity measuring device.

6 Acoustical environment, meteorological conditions, and background noise

6.1 Test site

The AWD shall be tested in an anechoic environment. Alternatively, it may be tested in a semi anechoic chamber or in an open space. In this case, precautions shall be taken to avoid reflections from the ground within the measuring area (for instance, by erecting a set of absorbing screens).

The test facility shall meet requirements of ISO 26101 with the following qualification criteria and measurement requirement appropriate to this test method as recommended by ISO 26101:

- space to be deemed anechoic shall be at least a 5-metre radius volume;
- test sound source location shall position in the middle of the space to be deemed anechoic, on the floor;
- microphone transverses shall be from the centre of the source to each microphone position;
- the maximum spacing of the measurement points shall depend on the size of the space to be deemed anechoic. A minimum of 10 points shall be used for spatial resolution of measurement;
- qualification band width shall be defined to cover the typical of the spectral range of interest that will be measured. Without any information, it is recommended from 100 Hz to 10 000 Hz;
- generation of sound shall be a broadband noise and a 1/3 octave filter for measurement requirements.

For indoor test site, the test facility shall have a cut-off frequency lower than the frequency of the lowest component of the sound emitted by the AWD under test.

In the vicinity of the microphone, there shall be no obstacle that could influence the acoustic field and no person shall remain between the microphone and the noise source. The meter observer shall be positioned so as not to influence the meter reading.

NOTE It is expected that users of this International Standard will understand that valid measurements can only be made when the cut-off frequency is lower than the lowest frequency of interest. A specific numerical requirement for cut-off frequency is not given due to the range of variation of appropriate cut-off frequencies depending upon the measured article.

6.2 Meteorological conditions

The meteorological instrumentation shall deliver data representative for the test site and shall be positioned adjacent to the test area at a height representative of the height of the measuring microphone.

The measurements shall be made when the ambient air temperature is within the range from 10 °C to 30 °C.

The tests shall not be carried out if the wind speed, including gusts, at microphone height exceeds 5 m/s, during the sound measurement interval.

A value representative of temperature, wind speed and direction, relative humidity, and barometric pressure shall be recorded during the sound measurement interval.

6.3 Background noise

Any sound peak which appears to be unrelated to the characteristics of the general sound level of the AWD shall be ignored in taking the readings.

The background noise shall be measured for duration of 10 s immediately before and after a series of tests. The measurements shall be made with the same microphones and microphone locations used during the test. The maximum A-weighted sound pressure level shall be reported.

The background noise (including any wind noise) shall be at least 10 dB below the A-weighted sound pressure level produced by the AWD under test.

6.4 Mounting of the AWD

The AWD to be tested shall be fitted as specified by the manufacturer. A representative tube (e.g. for a handlebar) or other required mounting point shall be rigidly fixed to a solid metallic base, which shall have a mass of at least 15 kg.

Unless otherwise specified by the manufacturer, the bell shall be mounted horizontally. Any tilt shall be stated in the Test Report.

The base shall be so designed that reflections from its faces, or vibrations, do not noticeably affect the measurements results.

6.5 Microphone and AWD positions

The microphone and the AWD shall be located $1,2 \text{ m} \pm 0,05 \text{ m}$ above the ground level.

The reference direction for free field conditions (see IEC 61672-1) shall be horizontal and directed perpendicularly towards the centre of the AWD.

The microphone shall be located at a distance of $2 \text{ m} \pm 0,01 \text{ m}$ from the centre of the bell.

7 Measurement of the sound pressure level

7.1 Actuation of the AWD

The AWD to be tested shall be rung by the operator who activates (push, pull, press) the control device as required by the manufacturer. The presence of this operator shall have no noticeable influence on the test results.

One measurement sequence consists 10 times consecutively over its full travel in $4 \text{ s} \pm 0,5 \text{ s}$.

Five sequences shall be carried out and each sequence has to be interrupted by a pause.

This operation shall be carried out five times.

7.2 Measurement readings and reported values

7.2.1 General

The maximum A-weighted sound pressure level in relation to $2 \times 10^{-5} \text{ Pa}$ (N/m^2), indicated during each sequence of 10 actuations shall be noted, to the first significant digit after the decimal place (for example -XX,X). If a sound peak obviously out of character with the general sound pressure level is observed, the measurement shall be discarded.

Five measurement results, within 2,0 dB, shall be used for the calculation of the final result.

7.2.2 Data compilation

The final value to be reported as the test result is the average value of the 5th result obtained during each of the five sequences.

7.3 Required sound pressure

Measured under the conditions specified above, the final value of the measured sound pressure level of three out of four AWD class I

- shall be equal or greater than 85 dB(A), and
- shall not exceed 95 dB(A).

Measured under the conditions specified above, the final value of the measured sound pressure level of three out of four AWD class II

- shall be equal or greater than 75 dB(A), and
- shall not exceed 85 dB(A).

NOTE 1 An AWD may have two positions: one for normal use and one for quiet area according to AWD class II definition.

NOTE 2 For electronic AWD to have a sound similar to a bell sound, it is recommended also to produce acoustic signature equivalent to mechanical AWD with impact noise following by a tone signal from 1 900 Hz to 4 600 Hz, which decreases in 1 s or 2 s.

7.4 Low battery indicator

The battery-powered AWD system shall include a low battery indicator. This indicator shall be located on the AWD, clearly and easily visible.

The indicator shall be activated at the latest when the requirements given in [7.3](#) are not fulfilled anymore.

8 Test of durability

8.1 Test procedure

Four examples of each model of AWD shall be subjected to the durability test as specified in [8.1.1](#) and [8.1.2](#). The apparatus shall be in new condition and shall not be lubricated during the test.

8.1.1 Stability mechanical test

a) Mechanical AWD

Four AWDs shall be activated 30 000 times over the working travel of the lever at a rate of 100 ± 5 operations per minute.

b) Electric or electronic AWD

The product securely attached, apply a cyclic force of 0 N to (13 ± 1) N (or the force enough to activate the sound, if higher) during 30 000 cycles. The contact duration from 0 to 13 and 13 to 0 shall be 1 s and the pause duration shall be 1 s. The force shall be applied progressively in order to avoid any shock.

The force must be applied at the centre of the button and perpendicular to the tangent of its surface ($\pm 5^\circ$).

Application of the force shall be done with a hemispherical tip made from Polyamide PA2200. [Figure 1](#) shows the dimension of the tip.




Figure 1 — Actuator tip

8.1.2 Corrosion test

Four AWDs shall be subjected to a neutral salt spray test (NSS) for 96 h according to ISO 9227.

This test is only applicable to AWD made of metallic active components.

NOTE As the AWD work in different environmental conditions, other environmental tests may be suitable depending on the material used.

8.2 Test result

After undergoing the tests specified in 8.1, at least three out of four AWDs shall still meet the requirements specified in 7.3.

9 Test report

The test report includes the following information:

- a) a reference to this International Standard, i.e. ISO 14878:2015;
- b) the details of the tests site (noise and durability), site orientation, and weather conditions including wind speed and air temperature, wind direction, barometric pressure, and humidity;
- c) the type of measuring and durability equipment including the windscreen;
- d) the A-weighted sound pressure level typical of the background noise;
- e) the mark and the type of the AWDs and identification of the class;
- f) the mounting and operating conditions;
- g) all valid A-weighted sound pressure level values measured for each test and the final value before and after corrosion tests for the four AWDs.

10 Marking

The AWD shall be visibly and permanently marked with the following class category:

ISO 14878 Class I, or

ISO 14878 Class II.

British Standards Institution (BSI)

BSI is the national body responsible for preparing British Standards and other standards-related publications, information and services.

BSI is incorporated by Royal Charter. British Standards and other standardization products are published by BSI Standards Limited.

About us

We bring together business, industry, government, consumers, innovators and others to shape their combined experience and expertise into standards-based solutions.

The knowledge embodied in our standards has been carefully assembled in a dependable format and refined through our open consultation process. Organizations of all sizes and across all sectors choose standards to help them achieve their goals.

Information on standards

We can provide you with the knowledge that your organization needs to succeed. Find out more about British Standards by visiting our website at bsigroup.com/standards or contacting our Customer Services team or Knowledge Centre.

Buying standards

You can buy and download PDF versions of BSI publications, including British and adopted European and international standards, through our website at bsigroup.com/shop, where hard copies can also be purchased.

If you need international and foreign standards from other Standards Development Organizations, hard copies can be ordered from our Customer Services team.

Subscriptions

Our range of subscription services are designed to make using standards easier for you. For further information on our subscription products go to bsigroup.com/subscriptions.

With **British Standards Online (BSOL)** you'll have instant access to over 55,000 British and adopted European and international standards from your desktop. It's available 24/7 and is refreshed daily so you'll always be up to date.

You can keep in touch with standards developments and receive substantial discounts on the purchase price of standards, both in single copy and subscription format, by becoming a **BSI Subscribing Member**.

PLUS is an updating service exclusive to BSI Subscribing Members. You will automatically receive the latest hard copy of your standards when they're revised or replaced.

To find out more about becoming a BSI Subscribing Member and the benefits of membership, please visit bsigroup.com/shop.

With a **Multi-User Network Licence (MUNL)** you are able to host standards publications on your intranet. Licences can cover as few or as many users as you wish. With updates supplied as soon as they're available, you can be sure your documentation is current. For further information, email bsmusales@bsigroup.com.

BSI Group Headquarters

389 Chiswick High Road London W4 4AL UK

Revisions

Our British Standards and other publications are updated by amendment or revision.

We continually improve the quality of our products and services to benefit your business. If you find an inaccuracy or ambiguity within a British Standard or other BSI publication please inform the Knowledge Centre.

Copyright

All the data, software and documentation set out in all British Standards and other BSI publications are the property of and copyrighted by BSI, or some person or entity that owns copyright in the information used (such as the international standardization bodies) and has formally licensed such information to BSI for commercial publication and use. Except as permitted under the Copyright, Designs and Patents Act 1988 no extract may be reproduced, stored in a retrieval system or transmitted in any form or by any means – electronic, photocopying, recording or otherwise – without prior written permission from BSI. Details and advice can be obtained from the Copyright & Licensing Department.

Useful Contacts:

Customer Services

Tel: +44 845 086 9001

Email (orders): orders@bsigroup.com

Email (enquiries): cservices@bsigroup.com

Subscriptions

Tel: +44 845 086 9001

Email: subscriptions@bsigroup.com

Knowledge Centre

Tel: +44 20 8996 7004

Email: knowledgecentre@bsigroup.com

Copyright & Licensing

Tel: +44 20 8996 7070

Email: copyright@bsigroup.com



...making excellence a habit.™