

BS ISO 15886-1:2012



BSI Standards Publication

# Agricultural irrigation equipment — Sprinklers

Part 1: Definition of terms and classification

**bsi.**

...making excellence a habit.™

**National foreword**

This British Standard is the UK implementation of ISO 15886-1:2012. It supersedes BS ISO 15886-1:2004 which is withdrawn.

The UK participation in its preparation was entrusted to Technical Committee AGE/30, Irrigation and drainage equipment.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2012. Published by BSI Standards Limited 2012

ISBN 978 0 580 70818 3

ICS 65.060.35

**Compliance with a British Standard cannot confer immunity from legal obligations.**

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 30 April 2012.

**Amendments issued since publication**

Date	Text affected
------	---------------

---

---

---

**Agricultural irrigation equipment —  
Sprinklers —**

Part 1:  
**Definition of terms and classification**

*Matériel agricole d'irrigation — Asperseurs —*

*Partie 1: Définition des termes et classification*





**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2012

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.org](mailto:copyright@iso.org)  
Web [www.iso.org](http://www.iso.org)

Published in Switzerland

## Contents

Page

Foreword .....	iv
<b>1 Scope .....</b>	<b>1</b>
<b>2 Terms and definitions .....</b>	<b>1</b>
<b>3 Classification .....</b>	<b>6</b>
<b>3.1 General .....</b>	<b>6</b>
<b>3.2 Physical factors .....</b>	<b>6</b>
<b>3.3 Characteristics of water spray .....</b>	<b>8</b>
<b>3.4 Mechanism for water distribution operation .....</b>	<b>11</b>
<b>3.5 Mechanism for sealing .....</b>	<b>13</b>
<b>3.6 Intended use .....</b>	<b>13</b>
<b>3.7 Additional functions incorporated into the sprinkler .....</b>	<b>14</b>
<b>Bibliography .....</b>	<b>16</b>

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 15886-1 was prepared by Technical Committee ISO/TC 23, *Tractors and machinery for agriculture and forestry*, Subcommittee SC 18, *Irrigation and drainage equipment and systems*.

This second edition cancels and replaces the first edition (ISO 15886-1:2004), which has been technically revised.

ISO 15886 consists of the following parts, under the general title *Agricultural irrigation equipment — Sprinklers*:

- *Part 1: Definition of terms and classification*
- *Part 3: Characterizing of distribution and test methods*

# Agricultural irrigation equipment — Sprinklers —

## Part 1: Definition of terms and classification

### 1 Scope

This part of ISO 15886 defines terms related to irrigation sprinklers and specifies the classification of sprinklers according to the following categories: physical factors; characteristics of the water spray; the mechanism for operation and water distribution; the mechanism for sealing; the intended use; additional functions incorporated into the sprinkler. The scope is intentionally broad to cover the widest possible range of sprinkler construction, performance, and intended-use alternatives.

### 2 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

#### 2.1

**accumulator****pressure accumulator**

hydraulic device that stores fluid under pressure and cushions shock waves

#### 2.2

**anti-drain valve**

valve designed to remain closed whenever the system pressure does not exceed a pre-set value and to open for higher pressures

#### 2.3

**chemigation**

application of chemicals through irrigation systems

#### 2.4

**compression-disk nozzle**

nozzle fitted with an elastic disk that flexes under pressure so as to alter the hydraulic properties of the nozzle

#### 2.5

**cross vane**

flow conditioning vanes, the design of which tends to trap waterborne contaminants

#### 2.6

**constant-acceleration nozzle**

nozzle, the shape of which changes gradually and smoothly so as to cause a constant rate of acceleration in the flow passages

#### 2.7

**constant-flow nozzle**

nozzle, the internal geometry of which does not vary under fixed operating conditions thus maintaining constant hydraulic properties

#### 2.8

**constricting-flow nozzle**

nozzle fitted with elastic sleeves that alter the hydraulic properties of the nozzle in response to changes in operating pressure

**2.9**  
**continuous-move irrigation machine**  
irrigation machine in which the position of sprinklers is fixed on a supply line which moves continuously in a particular direction

EXAMPLES Centre pivot irrigation machine, moving lateral irrigation machine, traveller irrigation machine.

**2.10**  
**controlled-acceleration nozzle**  
nozzle, the shape of which changes gradually and smoothly so as to cause a specific rate or rates of acceleration in the flow passages

**2.11**  
**customized nozzle**  
nozzle, the design of which meets specified hydraulic criteria for acceleration, turbulence and separation

**2.12**  
**element parallel to water flow**  
upstream flow conditioning component, the centreline of which is parallel to the nozzle centreline

**2.13**  
**element not parallel to water flow**  
upstream flow conditioning component, the centreline of which is at an angle to the nozzle centreline

**2.14**  
**spray elevation**  
height to which a spray rises above a horizontal plane passing through the elevation of the nozzle

**2.15**  
**finger spray**  
stream of water directed either as a cohesive or continuous jet or as a concentration of individual drops

**2.16**  
**flexing-orifice nozzle**  
nozzle fabricated from elastic materials that flex under pressure so as to alter the hydraulic properties of the nozzle

**2.17**  
**flow-rate change mechanism**  
mechanism provided that automatically changes hydraulic properties during operation

**2.18**  
**fluidic device**  
device (such as an amplifier or control) that depends for operation on the pressures and flows of a fluid in precisely shaped channels

NOTE Definition based on that for “fluidic” from the Free Merriam-Webster Dictionary, accessed on 2012-01-24. [Available from: [http://www.merriam-webster.com/dictionary/fluidic.](http://www.merriam-webster.com/dictionary/fluidic)]

**2.19**  
**gradual-acceleration nozzle**  
nozzle, the shape of which changes gradually and smoothly so as to cause a gradual, usually linear, acceleration in the flow passages

**2.20**  
**groove along flow passages**  
rifling along flow passages  
flow conditioning element designed to modify hydraulic properties of the flow passage thus increasing flow passage turbulence



**2.21**

**impact arm**

balanced arm of a sprinkler rotating about a vertical axis (usually corresponding to the sprinkler axis) that momentarily intercepts and deflects a portion of the jet so as to provide the torque required to rotate the water distribution component of the sprinkler

**2.22**

**impulse arm**

balanced arm of a sprinkler rotating about a horizontal axis that momentarily intercepts and deflects a portion of the jet so as to provide the torque required to rotate the water distribution component of the sprinkler

**2.23**

**jet-spray**

stream of water issuing from an orifice under pressure

**2.24**

**location of maximum trajectory height**

radial distance from the sprinkler axis at which the maximum trajectory height is reached

**2.25**

**maximum trajectory height**

maximum height, above a sprinkler or a sprayer of the trajectory of the principal water stream discharged from the sprinkler nozzle or sprayer operating at test pressure

**2.26**

**mechanically-controlled stream breakup sprinkler**

sprinkling device with a capability for controlling stream breakup in a series of mechanically pre-set repeatable cyclic patterns

**2.27**

**moveable fixed-grid agricultural system**

irrigation system in which sprinkler set positions are nominally fixed by a supply pipeline, a hydrant, infield access or other infrastructure constraints

EXAMPLES Hand-move system, wheel-move system.

**2.28**

**moving sheet**

sheet spray which moves in a linear fashion or which rotates

**2.29**

**no-variation sprinkler systems**

sprinkler systems that operate on mechanically controlled repeatable cycles

**2.30**

**no-statistical-variation sprinkler systems**

sprinkler systems that operate without fixed mechanical control, but that produce statistically repeatable results

**2.31**

**nominal size**

numerical designation used to refer to the size of a sprinkler which is identical to the nominal diameter of a pipe to which the sprinkler is intended to be connected directly

**2.32**

**nozzle**

aperture or adjutage in a sprinkler through which water is discharged

**2.33**

**off-axis-bore nozzle**

nozzle in which the orifice centreline does not correspond to the nozzle centreline

**2.34**

**open vane nozzle**

nozzle with flow conditioning vanes that are designed to shed waterborne contaminants

**2.35**

**opposed reaction-force driven sprinkling device**

balanced reaction-force driven sprinkling device

sprinkling device driven by hydraulic reaction forces from more than one jet acting in opposite directions such that the rotational torque is balanced to provide speed control and rotational stability

**2.36**

**pop up/pop down mechanism**

mechanism within the sprinkler that automatically raises the nozzle height to improve crop clearance when the system is pressurized and automatically lowers the nozzle to the original position when the system is de-pressurized

**2.37**

**ring orifice**

disk orifice

aperture in a ring or disk placed in the nozzle of a sprinkler normal to the direction of flow

NOTE The ring or disk is readily replaceable to allow for change in the hydraulic performance of the sprinkler.

**2.38**

**rotating sprinkler**

device which by its rotating motion around its vertical axis distributes water over a circular area or part of a circular area

**2.39**

**sheet spray**

water spread out into a flat plane-like spray

EXAMPLE Spray that results when water impinges on a deflector plate.

**2.40**

**space-filling fog spray**

emission from an orifice which fills the air with a "cloud" of ultra-fine droplets the size of which may be specified usually for the purpose of crop cooling

**2.41**

**space-filling mist spray**

emission from an orifice which fills the air with a "cloud" of very fine droplets the size range of which may be specified

**2.42**

**space-filling rain spray**

emission from an orifice which fills the air with a volume of relatively medium to coarse drops the size range of which may be specified

**2.43**

**space-filling spray**

emission from an orifice which fills the air with a "cloud" of relatively fine droplets the size range of which may be specified

**2.44**

**space-filling spray combination sprinkler**

sprinkling device combining a number of space filling spray types

**2.45**

**adjustable-speed sprinkler**

sprinkler that provides mechanically adjustable speed control features

**2.46**

**splash re-direct mechanism**

tube or deflection device mounted on an arm driven sprinkler to re-direct the drive action portion of jet in a direction generally parallel to the main jet

**2.47**

**sprinkler**

water distribution device of a variety of sizes and types for example impact sprinklers, fixed nozzle, sprayers and irrigation guns

**2.48**

**spray**

release of water from a sprinkler

**2.49**

**stationary fixed-grid system**

irrigation system in which sprinkler set positions are rigidly fixed by semi-permanent or permanently installed lateral pipelines

EXAMPLE Portable solid-set irrigation system, buried irrigation system.

**2.50**

**straight-bore nozzle**

nozzle utilizing a cylindrical cross-section approaching the orifice, normally no vena contracta is associated with this design

**2.51**

**taper-bore nozzle**

nozzle utilizing a conical section approaching the orifice

**2.52**

**trajectory angle**

angle above the horizontal plane of the water stream or spray discharged from a sprinkler nozzle or a sprayer operating at test pressure

**2.53**

**trajectory angle change mechanism**

mechanism that automatically changes the trajectory angle during operation

**2.54**

**valve-in-head**

valve mechanism fabricated as an integral part of the sprinkler that adds features independent of the sprinkling operation, to control flow rate

**2.55**

**variable-cycle sprinkler**

sprinkler that operates on fixed mechanically controlled repeatable sequences

NOTE Sequences consist of a number of cycles exhibiting one set of hydraulic properties followed by a number of cycles exhibiting a second set of hydraulic properties.

**2.56**

**variable-geometry nozzle**

nozzle fabricated to a non-regular shape for a specific purpose such as pressure or flow regulation or jet breakup

**2.57**

**variable internal geometry nozzle**

nozzle, the performance of which is significantly affected by the upstream flow passage components

**2.58**

**variable-performance nozzle**

nozzle, the internal geometry of which varies in some repetitive manner under fixed operating conditions to produce variable hydraulic properties

**2.59**

**wobbling sprayer**

nutating sprayer

wobbler

off-centre rotary-action sprinkler

### **3 Classification**

#### **3.1 General**

Sprinklers shall be classified according to the following major categories and their particular characteristics, as specified in 3.2 to 3.7. The intention is to cover all possible sprinkler types, by classifying them according to

- a) physical factors, such as size, materials, operating pressure,
- b) characteristics of the water spray, e.g. type of spray, area of coverage,
- c) the mechanism for operation and water distribution, e.g. methods of spraying and sprinkler drive methods,
- d) the mechanism for sealing, e.g. bearings, washers, O-rings,
- e) the intended use, e.g. agricultural, turf, garden, nursery, greenhouse, frost and dust control, cooling, wastewater utilization,
- f) additional functions incorporated into the sprinkler, e.g. pressure or flow regulation, or pop-up.

#### **3.2 Physical factors**

##### **3.2.1 Size of nozzle**

##### **3.2.2 Flow rate**

##### **3.2.3 Working pressure**

- Minimum working pressure.
- Maximum working pressure.
- Range of working pressure.

##### **3.2.4 Nominal size of inlet connection**

###### **3.2.4.1 Type of connections**

###### **3.2.4.1.1 Type of connections at inlet (ISO 13460)**

- Pipe thread (ISO 7-1:1994):
  - male;

- female.
- “Garden Hose” thread [ANSI/ASME B1.20.7-1991 (R2003)]:
  - male;
  - female.
- Bayonet or quick-coupling.
- Flange (ISO 7005-1:2011 and ISO 7005-2:1988).
- Insert barb (as in micro-sprayers).
- Multiple (choice of vertical and horizontal inlets).
- Flexible (incorporating part or all of a swing joint).
- Other.

#### **3.2.4.1.2 Type of nozzle connections**

- Tapered threads.
- Non-tapered threads:
  - butt seal;
  - O-ring seal;
  - other.
- Bayonet or quick coupling.
- Snap-fit.
- Permanently attached.
- Other.

#### **3.2.4.2 Orientation of sprinkler when connected (flow direction through sprinkler)**

- Up-inlet below nozzle/outlet.
- Down-inlet above nozzle/outlet.

#### **3.2.4.3 Typical or recommended riser or drop tube**

- Height or length.
- Height of nozzle/outlet above the irrigated surface.
- Rigidity of material:
  - rigid (metal);
  - semi-rigid (as lightweight PVC);
  - flexible (as flex-PVC or other elastomer).

#### **3.2.5 Degree of replacement/repair intended**

- None (throw away when no longer serviceable).

- Nozzles (nozzles and related parts such as stream straightener).
- Bearing/washers.
- Major drive parts (arm springs, swirl plates, turbine assemblies).
- Complete (full possibility to disassemble and replace/repair).
- Intended life.

#### **3.2.5.1 Based on hours of operation**

#### **3.2.5.2 Based on cycles of operation or number of actuations**

- Pop-up/pop-down.
- Forward/reverse.
- On/off.

#### **3.2.6 Materials of construction**

- Predominantly metal.
- Predominantly plastics.
- Other.

### **3.3 Characteristics of water spray**

#### **3.3.1 Type of spray**

##### **3.3.1.1 Sheet spray**

- Stationary sheet.
- Moving.

##### **3.3.1.2 Finger spray**

- Stationary finger.
- Moving.

##### **3.3.1.3 Jet-spray**

##### **3.3.1.4 Space-filling spray**

- Space-filling rain-spray.
- Space-filling mist-spray.
- Space-filling fog-spray.

##### **3.3.1.5 Space filling spray combination**

#### **3.3.2 Spray trajectory**

- Trajectory angle.

- Maximum trajectory height.
- Location of maximum trajectory height.

### **3.3.3 Area of coverage**

#### **3.3.3.1 Circular**

##### **3.3.3.1.1 Full-circle**

##### **3.3.3.1.2 Part-circle**

- Fixed-pattern.
- Adjustable-pattern:
  - adjustable in discrete steps;
  - adjustable to an infinite number of settings.

#### **3.3.3.2 Other patterns**

### **3.3.4 Type of nozzle(s)**

#### **3.3.4.1 Circular**

- Ring- or disk-orifice.
- Taper-bore nozzle.
- Straight-bore nozzle.
- Controlled-acceleration nozzle:
  - constant-acceleration nozzle;
  - gradual-acceleration nozzle.
  - customized nozzle.
- Off-axis-bore nozzle.
- Other.

#### **3.3.4.2 Circular with side slots, undercuts, etc.**

#### **3.3.4.3 Noncircular**

- Polygonal (triangle, square, rectangle, hexagon).
- Stellated (as in circular with corners of triangle).
- Rounded noncircular (oval or other).
- Multiple openings in same nozzle housing.
- Other.

#### **3.3.4.4 Variable-geometry nozzles**

- Variable-outlet-geometry:
  - flexing-orifice nozzle;
  - compression-disk nozzle;
  - constricting-passage nozzle;
  - fluidic devices;
  - other.
- Variable internal geometry:
  - constant with fixed operating conditions (nozzles);
  - variable with fixed operating conditions (nozzles).

#### **3.3.4.5 Nozzles incorporating stream-control elements**

- Elements parallel to water flow:
  - open vanes;
  - cross vanes;
  - grooves or rifling along passage;
  - other.
- Elements not parallel to water flow:
  - open vanes;
  - cross vanes;
  - grooves or rifling along passage;
  - other.
- Other.

#### **3.3.5 Variability of application pattern during operation**

##### **3.3.5.1 No variation**

- No actual variation.
- No statistical variation.

##### **3.3.5.2 Variation during individual cycle**

- Speed of rotation changes.
- Flow rate changes.
- Stream breakup changes.
- Trajectory angle changes.

##### **3.3.5.3 Variation between cycles**

- Stream breakup changes.



— Other changes between cycles.

#### **3.3.5.4 Other type of variation**

### **3.4 Mechanism for water distribution operation**

#### **3.4.1 Stationary spray**

##### **3.4.1.1 Direct spray**

##### **3.4.1.2 Splash plate or deflection plate**

#### **3.4.2 Wobbling (nutating) spray**

##### **3.4.2.1 Stationary nozzle into wobbling (nutating) deflector**

##### **3.4.2.2 Flexible whip**

#### **3.4.3 Rotating sprinklers — vertical axis of rotation**

##### **3.4.3.1 Arm-driven**

###### **3.4.3.1.1 Type of arm drive**

- Impulse arm.
- Impact arm.

###### **3.4.3.1.2 Energy storage/damping mechanism or principle**

- Spring:
  - coil;
  - leaf;
  - torsion;
  - elastomer;
  - other.
- Weight/gravity.
- Spring and weight/gravity in combination.
- Other principle.

###### **3.4.3.1.3 Configuration of water engagement part of the arm**

- Spoon and vane:
  - open-spoon;
  - closed-spoon.
- Wedge or V-drive.

- Counter-weighted wedge or V-drive.
- Splash redirect mechanism:
  - with splash redirect mechanism.
  - without splash redirect mechanism.
- Other.

#### **3.4.3.1.4 Arm support**

- Fulcrum pin only.
- Single-bridge.
- Double-bridge.
- Bridge/body combination.
- Other.

#### **3.4.3.2 Driven by motor (internal or external)**

- Turbine — speed control or reduction mechanism or principle:
  - gears;
  - viscous damping;
  - other;
  - uncontrolled.
- Impact:
  - ball-drive;
  - rotating-cam;
  - spin wheel;
  - other.
- Driven by reaction forces:
  - unopposed – spinner;
  - opposed or balanced.

#### **3.4.4 Rotating sprinklers — Horizontal axis of rotation**

##### **3.4.4.1 Mechanism of drive motor**

- Turbine — speed control or reduction mechanism or principle:
  - gears;
  - viscous damping;

- other.
- Impact:
  - ball drive;
  - rotating cam;
  - other.
- Piston.
- External motor.
- Other.

#### **3.4.4.2 Other**

### **3.5 Mechanism for sealing**

#### **3.5.1 Bearing/washer stack**

- Open.
- Protected, closed or internal:
  - O-rings;
  - face seals;
  - other.

### **3.6 Intended use**

#### **3.6.1 Agriculture**

##### **3.6.1.1 Type of system**

- Movable fixed-grid systems.
- Stationary fixed-grid systems.
- Continuous-move systems.

##### **3.6.1.2 Type of crop**

- Plant size, plant spacing, and extent of plant root system:
  - trees;
  - dwarf trees;
  - vines;
  - bushes;
  - row crops;

- continuous cover crops.
- Plant value:
  - high economic return per unit area;
  - medium economic return per unit area;
  - low economic return per unit area.
- Plant sensitivity to water stress:
  - high sensitivity to water stress;
  - medium sensitivity to water stress;
  - low sensitivity to water stress.

### **3.6.2 Turf/landscape**

- Residential and small business.
- Commercial (parks, large industrial, schools, highway landscaping).
- Golf.
- Other athletic fields (soccer, football, tennis, cricket, rugby, etc.).
- Other.

### **3.6.3 Home garden**

### **3.6.4 Nursery/greenhouse**

### **3.6.5 Environmental uses**

- Frost protection.
- Evaporative cooling:
  - to avoid heat stress;
  - to avoid accumulation of degree-days to prolong dormancy.
- Dust suppression.
- Irrigation with, or disposal of effluent water.

### **3.6.6 Chemigation (includes fertilizers and other agronomic chemicals)**

### **3.6.7 Quality of intended water source (as “dirty water” products)**

## **3.7 Additional functions incorporated into the sprinkler**

### **3.7.1 Pop-up/pop-down**

### 3.7.2 Pressure regulation

While 3.3.4.4 dealt with pressure- or flow-regulating nozzles, this subclause covers sprinklers employing pressure-regulating mechanisms other than at the nozzle, which are classified according to their use of either

- elastomeric parts sensitive to pressure, or
- variable internal openings to adjust nozzle pressure which can be
  - spring-controlled,
  - weight/gravity-controlled,
  - rolling-diaphragm, or
  - other.

### 3.7.3 Flow control (ISO 9911:2006)

While 3.3.4.4 dealt with pressure- or flow-regulating nozzles, this subclause covers sprinklers employing flow-regulating mechanisms other than at the nozzle, which are classified according to their use of either

- elastomeric parts sensitive to velocity or pressure loss, or
- variable internal openings to adjust nozzle pressure which can be
  - spring-controlled,
  - weight/gravity-controlled,
  - rolling-diaphragm, or
  - other.

### 3.7.4 Valve-in-head (ISO 9635-3, ISO 9635-5 and ISO 10522)

- Anti-drain valve.
- On/off valve.
- Complex valve (on/off and other functions).

### 3.7.5 Pressure accumulator

### 3.7.6 Volume (water) accumulator

### 3.7.7 Other

## Bibliography

- [1] ISO 7-1:1994, *Pipe threads where pressure-tight joints are made on the threads — Part 1: Dimensions, tolerances and designation*
- [2] ISO 7005-1:2011, *Pipe flanges — Part 1: Steel flanges for industrial and general service piping systems*
- [3] ISO 7005-2:1988, *Metallic flanges — Part 2: Cast iron flanges*
- [4] ISO 7749-1:1995, *Irrigation equipment — Rotating sprinklers — Part 1: Design and operational requirements*
- [5] ISO 8026:2009, *Agricultural irrigation equipment — Sprayers — General requirements and test methods*
- [6] ISO 9635-3:2006, *Agricultural irrigation equipment — Irrigation valves — Part 3: Check valves*
- [7] ISO 9635-5:2006, *Agricultural irrigation equipment — Irrigation valves — Part 5: Control valves*
- [8] ISO 9911:2006, *Agricultural irrigation equipment — Manually operated small plastics valves*
- [9] ISO 10522:1993, *Agriculture irrigation equipment — Direct acting pressure-regulating valves*
- [10] ISO 13460:1998, *Agricultural irrigation equipment — Plastics saddles for polyethylene pressure pipes*
- [11] ANSI/ASME B1.20.7-1991 (R2003), *Hose Coupling Screw Threads — Inch*









# British Standards Institution (BSI)

BSI is the national body responsible for preparing British Standards and other standards-related publications, information and services.

BSI is incorporated by Royal Charter. British Standards and other standardization products are published by BSI Standards Limited.

## About us

We bring together business, industry, government, consumers, innovators and others to shape their combined experience and expertise into standards-based solutions.

The knowledge embodied in our standards has been carefully assembled in a dependable format and refined through our open consultation process. Organizations of all sizes and across all sectors choose standards to help them achieve their goals.

## Information on standards

We can provide you with the knowledge that your organization needs to succeed. Find out more about British Standards by visiting our website at [bsigroup.com/standards](http://bsigroup.com/standards) or contacting our Customer Services team or Knowledge Centre.

## Buying standards

You can buy and download PDF versions of BSI publications, including British and adopted European and international standards, through our website at [bsigroup.com/shop](http://bsigroup.com/shop), where hard copies can also be purchased.

If you need international and foreign standards from other Standards Development Organizations, hard copies can be ordered from our Customer Services team.

## Subscriptions

Our range of subscription services are designed to make using standards easier for you. For further information on our subscription products go to [bsigroup.com/subscriptions](http://bsigroup.com/subscriptions).

With **British Standards Online (BSOL)** you'll have instant access to over 55,000 British and adopted European and international standards from your desktop. It's available 24/7 and is refreshed daily so you'll always be up to date.

You can keep in touch with standards developments and receive substantial discounts on the purchase price of standards, both in single copy and subscription format, by becoming a **BSI Subscribing Member**.

**PLUS** is an updating service exclusive to BSI Subscribing Members. You will automatically receive the latest hard copy of your standards when they're revised or replaced.

To find out more about becoming a BSI Subscribing Member and the benefits of membership, please visit [bsigroup.com/shop](http://bsigroup.com/shop).

With a **Multi-User Network Licence (MUNL)** you are able to host standards publications on your intranet. Licences can cover as few or as many users as you wish. With updates supplied as soon as they're available, you can be sure your documentation is current. For further information, email [bsmusales@bsigroup.com](mailto:bsmusales@bsigroup.com).

## BSI Group Headquarters

389 Chiswick High Road London W4 4AL UK

## Revisions

Our British Standards and other publications are updated by amendment or revision.

We continually improve the quality of our products and services to benefit your business. If you find an inaccuracy or ambiguity within a British Standard or other BSI publication please inform the Knowledge Centre.

## Copyright

All the data, software and documentation set out in all British Standards and other BSI publications are the property of and copyrighted by BSI, or some person or entity that owns copyright in the information used (such as the international standardization bodies) and has formally licensed such information to BSI for commercial publication and use. Except as permitted under the Copyright, Designs and Patents Act 1988 no extract may be reproduced, stored in a retrieval system or transmitted in any form or by any means – electronic, photocopying, recording or otherwise – without prior written permission from BSI. Details and advice can be obtained from the Copyright & Licensing Department.

## Useful Contacts:

### Customer Services

**Tel:** +44 845 086 9001

**Email (orders):** [orders@bsigroup.com](mailto:orders@bsigroup.com)

**Email (enquiries):** [cservices@bsigroup.com](mailto:cservices@bsigroup.com)

### Subscriptions

**Tel:** +44 845 086 9001

**Email:** [subscriptions@bsigroup.com](mailto:subscriptions@bsigroup.com)

### Knowledge Centre

**Tel:** +44 20 8996 7004

**Email:** [knowledgecentre@bsigroup.com](mailto:knowledgecentre@bsigroup.com)

### Copyright & Licensing

**Tel:** +44 20 8996 7070

**Email:** [copyright@bsigroup.com](mailto:copyright@bsigroup.com)



...making excellence a habit.™