

BS ISO 17063:2003



BSI Standards Publication

**Earth-moving machinery —  
Braking systems of pedestrian-  
controlled machines —  
Performance requirements and  
test procedures**

**National foreword**

This British Standard is the UK implementation of ISO 17063:2003.

The UK participation in its preparation was entrusted to Technical Committee B/513/1, Earth moving machinery (International).

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2016. Published by BSI Standards Limited 2016

ISBN 978 0 580 95532 7

ICS 53.100

**Compliance with a British Standard cannot confer immunity from legal obligations.**

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 August 2016.

**Amendments issued since publication**

Date	Text affected
------	---------------

---

INTERNATIONAL  
STANDARD

**ISO**  
**17063**

First edition  
2003-11-15

---

---

**Earth-moving machinery — Braking  
systems of pedestrian-controlled  
machines — Performance requirements  
and test procedures**

*Engins de terrassement — Dispositifs de freinage des engins à  
conducteur accompagnant — Exigences de performance et modes  
opératoires d'essai*



Reference number  
ISO 17063:2003(E)

© ISO 2003

**PDF disclaimer**

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

© ISO 2003

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.org](mailto:copyright@iso.org)  
Web [www.iso.org](http://www.iso.org)

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 17063 was prepared by Technical Committee ISO/TC 127, *Earth-moving machinery*, Subcommittee SC 2, *Safety requirements and human factors*.



# Earth-moving machinery — Braking systems of pedestrian-controlled machines — Performance requirements and test procedures

## 1 Scope

This International Standard specifies minimum performance criteria and tests for braking systems, enabling uniform assessment of the braking capability of pedestrian-controlled, self-propelled earth-moving machinery (as specified in ISO 6165) with a machine mass greater than 115 kg and a travel speed of less than 6 km/h. It is applicable to both service and parking brakes.

## 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 6014, *Earth-moving machinery — Determination of ground speed*

ISO 6016, *Earth-moving machinery — Methods of measuring the masses of whole machines, their equipment and components*

ISO 6165, *Earth-moving machinery — Basic types — Vocabulary*

## 3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 6165 and the following apply.

### 3.1

#### **pedestrian controlled machine**

self-propelled crawler or wheeled machine designed to be controlled by a person that does not ride on the machine

### 3.2

#### **braking system**

components which combine together to stop and/or hold machine, consisting of the **brake** (3.3.1), **brake actuation system** (3.3.2) and **brake control** (3.3.3)

#### 3.2.1

##### **service brake**

primary system used for stopping and holding machine

#### 3.2.2

##### **parking brake**

system used to hold stopped machine in a stationary position

### 3.3 braking system components

#### 3.3.1 brake

component(s) which directly applies a force to oppose movement of machine

NOTE Brakes may, for example, be of friction, electrical, or hydrostatic or other fluid types.

#### 3.3.2 brake actuation system

all components between **brake control** (3.3.3) and **brake(s)** (3.3.1) which connect the brake control and brake(s) functionally

#### 3.3.3 brake control

component directly activated by operator to apply the **braking system** (3.2)

### 3.4 machine mass

maximum operating mass of machine as specified by machine manufacturer

NOTE See ISO 6016.

### 3.5 stopping distance

distance travelled by machine from point on **test course** (3.7) at which machine brake control actuation begins to point on test course where machine is fully stopped

### 3.6 maximum machine level surface speed

machine speed determined in accordance with ISO 6014

### 3.7 test course

surface upon which the test is carried out

NOTE See Clause 5.

## 4 General requirements

### 4.1 Braking systems

Pedestrian controlled machines shall be fitted with means for satisfying the requirements of a service brake system and a parking brake system.

Ground drive systems, including hydrostatic drives, which satisfy the braking requirements of 6.1 and 6.2 are acceptable as the braking means.

The braking system shall not contain a disconnect, such as a clutch or shiftable gear box, which allows the brake(s) to be disabled. Disconnects designed to allow movement of disabled machines shall be located outside the operator's position.

### 4.2 Brake controls

Braking system controls shall be capable of being applied by the operator from the normal operating position(s), as specified by the manufacturer.



The force to actuate the brake control shall not exceed 20 N for finger (flip levers and switches) actuation and 220 N for hand grasp actuation.

## **5 Test conditions**

Immediately prior to performing the brake tests, machine systems recommended by the manufacturer shall be at normal operating temperature.

The test machine shall be configured for operating in the manufacturer's recommended transport position and the mass shall be the machine mass (3.4).

The test course shall consist of a hard, dry surface with a well-compacted base and a slope no greater than 3 % transversely. The slope in the direction of travel shall be as specified for the test being conducted.

Manufacturers' precautions shall be observed while carrying out performance tests.

## **6 Test and performance criteria**

### **6.1 Service brake**

#### **6.1.1 Requirements**

A means shall be provided for stopping and holding the machine's motion in both forward and reverse directions.

#### **6.1.2 Test procedure**

##### **6.1.2.1 Stopping**

The machine stopping distance shall be determined at maximum forward and maximum reverse speeds. When testing a machine equipped with separate clutch and brake controls, the clutch shall be disengaged simultaneously with brake engagement. The test course shall be in accordance with Clause 5 with no more than 1 % slope in the direction of travel.

##### **6.1.2.2 Holding**

The holding performance shall be determined by placing the machine on a 25 % test slope, or if less, the maximum slope the machine can ascend in both forward and reverse directions.

An alternative test method is to apply a pulling force to the stationary machine on a level surface with the service brake system applied. The pulling force shall be applied horizontally below the centre of gravity to achieve a minimum force equivalent to the slope. For a slope of 25 %, the equivalent force in newtons is 2,38 times the machine mass in kilograms.

For machines using the hydrostatic drive system as a service brake, hydraulic power may be used to prevent creeping.

#### **6.1.3 Performance acceptance**

##### **6.1.3.1 Stopping distance**

The braking system shall stop the machine from its maximum machine level surface speed in both forward and reverse directions. The stopping distance in metres shall be less than or equal to 0,2 of the maximum surface speed measured in kilometres per hour.

### 6.1.3.2 Holding performance

With the service brake system applied, the machine shall hold in both forward and reverse directions when tested according to 6.1.2.2. Creep rate without use of hydraulic power (refer 6.1.2.2) shall not exceed 2 m/min.

## 6.2 Parking brake

### 6.2.1 Requirements

A means shall be provided for holding the machine stationary unless it can be manually turned perpendicular to a 20 % slope. The parking brake may be in combination with the service brake.

After being applied, the system shall not be dependent upon an exhaustible energy source. The control shall be fixable in its actuated position or automatically applied in case of loss of energy. The likelihood of accidental release shall be reduced. If the ground drive system serves as the parking brake, actuation of a control with the engine off shall not result in machine movement on the test slope unless the control can be immediately reapplied and stop the machine.

When chocks are used to meet parking brake requirements, instructions for their use and storage on the machine shall be provided.

### 6.2.2 Test procedure

Position the machine on a 20 % test slope with the parking brake system applied. Alternatively, apply a pulling force to the stationary machine on a level surface with the parking brake system applied. Apply the pulling force horizontally below the centre of gravity to achieve a minimum force equivalent to the 20 % slope. The equivalent force in newtons is 1,92 times the machine mass in kilograms.

### 6.2.3 Performance acceptance

The parking brake system shall hold the machine stationary with the engine off and the ground drive in neutral (if applicable) in both forward and reverse directions.

## 7 Test report

The test report shall contain the following information:

- a) reference to this International Standard (i.e. ISO 17063);
- b) type of machine;
- c) model and serial number of the test machine;
- d) mass of the machine as tested;
- e) manufacturer's approved maximum machine mass;
- f) tyre or track size;
- g) description of the brakes;
- h) type of braking system;
- i) slope of the test course or force applied;
- j) results of all brake tests;

- k) force levels applied to the controls;
- l) machine maximum level surface speed;
- m) date test was performed;
- n) signature of person performing the test;
- o) manufacturer of machine.

---

---

**ICS 53.100**

Price based on 5 pages



# British Standards Institution (BSI)

BSI is the national body responsible for preparing British Standards and other standards-related publications, information and services.

BSI is incorporated by Royal Charter. British Standards and other standardization products are published by BSI Standards Limited.

## About us

We bring together business, industry, government, consumers, innovators and others to shape their combined experience and expertise into standards-based solutions.

The knowledge embodied in our standards has been carefully assembled in a dependable format and refined through our open consultation process. Organizations of all sizes and across all sectors choose standards to help them achieve their goals.

## Information on standards

We can provide you with the knowledge that your organization needs to succeed. Find out more about British Standards by visiting our website at [bsigroup.com/standards](http://bsigroup.com/standards) or contacting our Customer Services team or Knowledge Centre.

## Buying standards

You can buy and download PDF versions of BSI publications, including British and adopted European and international standards, through our website at [bsigroup.com/shop](http://bsigroup.com/shop), where hard copies can also be purchased.

If you need international and foreign standards from other Standards Development Organizations, hard copies can be ordered from our Customer Services team.

## Copyright in BSI publications

All the content in BSI publications, including British Standards, is the property of and copyrighted by BSI or some person or entity that owns copyright in the information used (such as the international standardization bodies) and has formally licensed such information to BSI for commercial publication and use.

Save for the provisions below, you may not transfer, share or disseminate any portion of the standard to any other person. You may not adapt, distribute, commercially exploit, or publicly display the standard or any portion thereof in any manner whatsoever without BSI's prior written consent.

## Storing and using standards

Standards purchased in soft copy format:

- A British Standard purchased in soft copy format is licensed to a sole named user for personal or internal company use only.
- The standard may be stored on more than 1 device provided that it is accessible by the sole named user only and that only 1 copy is accessed at any one time.
- A single paper copy may be printed for personal or internal company use only.

Standards purchased in hard copy format:

- A British Standard purchased in hard copy format is for personal or internal company use only.
- It may not be further reproduced – in any format – to create an additional copy. This includes scanning of the document.

If you need more than 1 copy of the document, or if you wish to share the document on an internal network, you can save money by choosing a subscription product (see 'Subscriptions').

## Reproducing extracts

For permission to reproduce content from BSI publications contact the BSI Copyright & Licensing team.

## Subscriptions

Our range of subscription services are designed to make using standards easier for you. For further information on our subscription products go to [bsigroup.com/subscriptions](http://bsigroup.com/subscriptions).

With **British Standards Online (BSOL)** you'll have instant access to over 55,000 British and adopted European and international standards from your desktop. It's available 24/7 and is refreshed daily so you'll always be up to date.

You can keep in touch with standards developments and receive substantial discounts on the purchase price of standards, both in single copy and subscription format, by becoming a **BSI Subscribing Member**.

**PLUS** is an updating service exclusive to BSI Subscribing Members. You will automatically receive the latest hard copy of your standards when they're revised or replaced.

To find out more about becoming a BSI Subscribing Member and the benefits of membership, please visit [bsigroup.com/shop](http://bsigroup.com/shop).

With a **Multi-User Network Licence (MUNL)** you are able to host standards publications on your intranet. Licences can cover as few or as many users as you wish. With updates supplied as soon as they're available, you can be sure your documentation is current. For further information, email [subscriptions@bsigroup.com](mailto:subscriptions@bsigroup.com).

## Revisions

Our British Standards and other publications are updated by amendment or revision.

We continually improve the quality of our products and services to benefit your business. If you find an inaccuracy or ambiguity within a British Standard or other BSI publication please inform the Knowledge Centre.

## Useful Contacts

### Customer Services

**Tel:** +44 345 086 9001

**Email (orders):** [orders@bsigroup.com](mailto:orders@bsigroup.com)

**Email (enquiries):** [cservices@bsigroup.com](mailto:cservices@bsigroup.com)

### Subscriptions

**Tel:** +44 345 086 9001

**Email:** [subscriptions@bsigroup.com](mailto:subscriptions@bsigroup.com)

### Knowledge Centre

**Tel:** +44 20 8996 7004

**Email:** [knowledgecentre@bsigroup.com](mailto:knowledgecentre@bsigroup.com)

### Copyright & Licensing

**Tel:** +44 20 8996 7070

**Email:** [copyright@bsigroup.com](mailto:copyright@bsigroup.com)

### BSI Group Headquarters

389 Chiswick High Road London W4 4AL UK