

Manually portable forest machinery — Recyclability and recoverability — Calculation method

ICS 65.060.80

National foreword

This British Standard is the UK implementation of ISO 17314:2008.

The UK participation in its preparation was entrusted to Technical Committee AGE/29, Forestry machinery.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 March 2008

© BSI 2008

ISBN 978 0 580 59063 4

Amendments/corrigenda issued since publication

Date	Comments

INTERNATIONAL
STANDARD

ISO
17314

First edition
2008-03-01

**Manually portable forest machinery —
Recyclability and recoverability —
Calculation method**

*Machines forestières portatives à main — Recyclabilité et possibilité de
récupération — Méthodes de calcul*



Reference number
ISO 17314:2008(E)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 17314 was prepared by Technical Committee ISO/TC 23, *Tractors and machinery for agriculture and forestry*, Subcommittee SC 17, *Manually portable forest machinery*.

Introduction

End-of-life machines contribute to the total volume of waste to be treated. As part of the machine life cycle, it is essential that recovery issues be taken into consideration during the design phase to ensure environmentally sound treatment.

Today, recycling has to be taken into account in addition to safety, emissions and fuel consumption when designing a machine. Consequently, there is need for an indicator to evaluate the ability and potential of new machines to be recovered/recycled.

The method for calculating recyclability and recoverability rates specified by this International Standard (similar to the method specified in ISO 22628:2002 for road vehicles) is based on four main stages inspired by the treatment of end-of-life machines. Recyclability/recoverability rates depend on the design and material properties of new machines and on the consideration of proven technologies — those technologies which have been successfully tested, at least on a laboratory scale, in this context.

The calculation method of this International Standard cannot in detail reflect the real process that will be applied to the machine at the end of its life.

Manually portable forest machinery — Recyclability and recoverability — Calculation method

1 Scope

This International Standard specifies a method for calculating the recyclability rate and the recoverability rate of manually portable forest machinery, with each rate being expressed as a percentage by mass (mass fraction in percent) of the machine.

The calculation can be performed by the machine manufacturer when a machine is initially put on the market. It does not include fluids.

2 Terms and definitions

For the purposes of this document, the following terms and definitions apply. See Figure 1.

2.1

re-use, noun

any operation by which component parts of end-of-life machines are used for the same purpose for which they were conceived

NOTE 1 Adapted from ISO 22628:2002, definition 3.2.

NOTE 2 See Figure 1.

2.2

recycling

reprocessing in a production process of the waste materials for the original purpose or for other purposes, excluding processing as a means of generating energy

[ISO 22628]

NOTE See Figure 1.

2.3

recovery

reprocessing in a production process of the waste materials for the original purpose or for other purposes, together with processing as a means of generating energy

[ISO 22628]

NOTE See Figure 1.

2.4

dismantlability

ability of component parts to be removed from the machine

NOTE Adapted from ISO 22628:2002, definition 3.5.

2.5

reusability

ability of component parts that can be diverted from an end-of-life stream to be reused

[ISO 22628]

2.6

recyclability

ability of component parts, materials or both that can be diverted from an end-of-life stream to be recycled

NOTE Adapted from ISO 22628:2002, definition 3.7.

2.7

recyclability rate

R_{cyc}
percentage by mass (mass fraction in percent) of the new machine potentially able to be recycled, reused or both

NOTE 1 Adapted from ISO 22628:2002, definition 3.8.

NOTE 2 See Figure 1.

2.8

recoverability

ability of components or materials that can be diverted from an end-of-life stream to be recovered

NOTE Adapted from ISO 22628:2002, definition 3.9.

2.9

recoverability rate

R_{cov}
percentage by mass (mass fraction in percent) of the new machine potentially able to be recovered or reused

NOTE 1 Adapted from ISO 22628:2002, definition 3.10.

NOTE 2 See Figure 1.

	Recovery		Residue
(Component parts) Re-use^a	(Materials) Recycling	(Materials) Energy recovery	(Materials)
Recyclability rate ^b			
Recoverability rate ^b			
Machine mass			

^a For machines covered by this International Standard, there are normally no components for re-use.

^b As a percentage of machine mass.

Figure 1 — Key terms — Overview

3 Masses and their symbols

Table 1 describes the symbols of the mass variables used in calculating the recyclability and recoverability rates.

Table 1 — Masses and symbols

Symbol	Description
$m_{D,R}$	mass of materials taken into account for recycling at the dismantling step
$m_{D,E}$	mass of materials taken into account for energy recovery at the dismantling step
$m_{S,R}$	mass of materials taken into account for recycling at the shredding step
$m_{S,E}$	mass of materials taken into account for energy recovery at the shredding step
m_{Tot}	total mass of the complete machine with empty tanks, including cutting tool and cover and, if available, extra equipment such as a spiked bumper for chain saws ^a
NOTE 1	All masses are expressed in kilograms.
^a	Under normal circumstances, the tanks of portable forest machinery that is left to be recycled will be <i>approximately</i> empty.

4 Calculation method

4.1 General

The recyclability and recoverability rates of a new machine are calculated through the following two steps, with components or materials able to be taken into account at each step.

Step 1: dismantling ($m_{D,R}$ and $m_{D,E}$).

Step 2: shredding ($m_{S,R}$ and $m_{S,E}$).

For the determination of partial mass only, mass fractions of 10 g or more are reported.

NOTE The dismantlability of the machines is usually limited to easily accessible components such as the cutting equipment. For metals separation and non-metallic residue of the remaining parts of a product, shredding is deemed to be the predominant method.

4.2 Materials breakdown

The materials breakdown of the machine is established by classifying all the materials composing the machine into the following three categories:

- a) metals;
- b) non-metals;
- c) other — components, materials or both, for which a detailed material breakdown cannot be established (compounds, electronics, electrics).

This breakdown may be done at each step of the calculation for each partial mass mentioned in 4.1.

4.3 Calculation of recyclability/recoverability rate

4.3.1 Recyclability rate

Calculate the recyclability rate, R_{cyc} , of the machine, as a percentage by mass (mass fraction in percent), using the formula:

$$R_{\text{cyc}} = \frac{m_{\text{D,R}} + m_{\text{S,R}}}{m_{\text{Tot}}} \times 100$$

4.3.2 Recoverability rate

Calculate the recoverability rate, R_{cov} , of the machine, as a percentage by mass (mass fraction in percent), using the formula:

$$R_{\text{cov}} = \frac{m_{\text{D,R}} + m_{\text{S,R}} + m_{\text{D,E}} + m_{\text{S,E}}}{m_{\text{Tot}}} \times 100$$

NOTE Technologies for energy recovery of polymers and elastomers are industrialized on a large scale worldwide. Therefore, polymers, elastomers and other modified organic natural materials can potentially be recovered through those technologies.

Annex A (informative)

Example of recyclability and recoverability calculations for a mid-sized chain saw

A.1 Mass fractions of the chain-saw

Table A.1 presents an example of mass fractions calculated for different materials in the case of a typical mid-sized chain saw with a total machine mass, m_{Tot} , of 8,10 kg.

Table A.1 — Mass fractions, in kilograms, for different materials

		Recycling	Energy recovery	Residue
Step 1: dismantling				
Cutting equipment, steel		1,50		
Cutting equipment cover, PE			0,35	
Cylinder cover, PA			0,20	
	Sum $m_{D,R}$	1,50		
	Sum $m_{D,E}$		0,55	
Step 2: shredding				
Steel		2,26		
Aluminium		1,24		
Magnesium		0,96		
Copper		0,07		
Plastics:	PA		1,15	
	PBT		0,02	
	PE		0,02	
	POM		0,12	
	PVC		0,08	
Rubber			0,08	
	Sum $m_{S,R}$	4,53		
	Sum $m_{S,E}$		1,47	
Recyclability rate:		$R_{cyc} = \frac{1,5 + 4,53}{8,10} \times 100 = 74 \%$		
Recoverability rate:		$R_{cov} = \frac{1,5 + 4,53 + 0,55 + 1,47}{8,10} \times 100 = 99 \%$		
NOTE Normally, there are some materials missing in the above total material balance.				

Bibliography

- [1] ISO 22628:2002, *Road vehicles — Recyclability and recoverability — Calculation method*

BSI — British Standards Institution

BSI is the independent national body responsible for preparing British Standards. It presents the UK view on standards in Europe and at the international level. It is incorporated by Royal Charter.

Revisions

British Standards are updated by amendment or revision. Users of British Standards should make sure that they possess the latest amendments or editions.

It is the constant aim of BSI to improve the quality of our products and services. We would be grateful if anyone finding an inaccuracy or ambiguity while using this British Standard would inform the Secretary of the technical committee responsible, the identity of which can be found on the inside front cover.
Tel: +44 (0)20 8996 9000. Fax: +44 (0)20 8996 7400.

BSI offers members an individual updating service called PLUS which ensures that subscribers automatically receive the latest editions of standards.

Buying standards

Orders for all BSI, international and foreign standards publications should be addressed to Customer Services. Tel: +44 (0)20 8996 9001.
Fax: +44 (0)20 8996 7001. Email: orders@bsi-global.com. Standards are also available from the BSI website at <http://www.bsi-global.com>.

In response to orders for international standards, it is BSI policy to supply the BSI implementation of those that have been published as British Standards, unless otherwise requested.

Information on standards

BSI provides a wide range of information on national, European and international standards through its Library and its Technical Help to Exporters Service. Various BSI electronic information services are also available which give details on all its products and services. Contact the Information Centre.
Tel: +44 (0)20 8996 7111. Fax: +44 (0)20 8996 7048. Email: info@bsi-global.com.

Subscribing members of BSI are kept up to date with standards developments and receive substantial discounts on the purchase price of standards. For details of these and other benefits contact Membership Administration.
Tel: +44 (0)20 8996 7002. Fax: +44 (0)20 8996 7001.
Email: membership@bsi-global.com.

Information regarding online access to British Standards via British Standards Online can be found at <http://www.bsi-global.com/bsonline>.

Further information about BSI is available on the BSI website at <http://www.bsi-global.com>.

Copyright

Copyright subsists in all BSI publications. BSI also holds the copyright, in the UK, of the publications of the international standardization bodies. Except as permitted under the Copyright, Designs and Patents Act 1988 no extract may be reproduced, stored in a retrieval system or transmitted in any form or by any means – electronic, photocopying, recording or otherwise – without prior written permission from BSI.

This does not preclude the free use, in the course of implementing the standard, of necessary details such as symbols, and size, type or grade designations. If these details are to be used for any other purpose than implementation then the prior written permission of BSI must be obtained.

Details and advice can be obtained from the Copyright & Licensing Manager.
Tel: +44 (0)20 8996 7070. Fax: +44 (0)20 8996 7553.
Email: copyright@bsi-global.com.