

BS ISO 18421:2016



BSI Standards Publication

Ships and marine technology — Inland navigation vessels — Lifebuoy housings

bsi.

...making excellence a habit.™

National foreword

This British Standard is the UK implementation of ISO 18421:2016. It supersedes BS ISO 18421:2013 which is withdrawn.

The UK participation in its preparation was entrusted to Technical Committee SME/32, Ships and marine technology - Steering committee.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2016.
Published by BSI Standards Limited 2016

ISBN 978 0 580 90175 1

ICS 47.060

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 30 April 2016.

Amendments/corrigenda issued since publication

Date	Text affected
------	---------------

INTERNATIONAL
STANDARD

ISO
18421

Second edition
2016-03-15

**Ships and marine technology —
Inland navigation vessels — Lifebuoy
 housings**

*Navires et technologie maritime — Bateaux de navigation intérieure
— Coffres à bouée de sauvetage*



Reference number
ISO 18421:2016(E)



COPYRIGHT PROTECTED DOCUMENT

© ISO 2016, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Requirements	1
4.1 Dimensions.....	1
4.2 Design.....	2
4.2.1 Interior.....	2
4.2.2 Cover.....	2
4.2.3 Mounting.....	2
4.3 Material.....	2
4.4 Resistance.....	2
4.5 Temperature stability.....	2
4.6 Colour.....	2
4.7 Operational status check and seal ability.....	3
4.8 Resistance.....	3
5 Testing	3
5.1 Scope and testing.....	3
5.2 Visual inspection and functional test.....	3
5.3 Resistance.....	3
5.4 Strength test.....	3
5.5 Mounting instruction.....	3
6 Designation	3
7 Marking	4

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: [Foreword - Supplementary information](#).

The committee responsible for this document is ISO/TC 8, *Ships and marine technology*, Subcommittee SC 7, *Inland navigation vessels*.

This second edition cancels and replaces the first edition (ISO 18421:2013), which has been technically revised with the following changes:

- dimensions have been changed;
- operational status check and seal ability is optional;
- strength test has been changed;
- temperature test has been deleted.

Introduction

The housing protects the lifebuoy against permanent exposure to the elements and acts as a deterrent against theft and vandalism of therein contained life-saving equipment.

Lifebuoy housings reduce the frequency of failure of the lifebuoys.

Ships and marine technology — Inland navigation vessels — Lifebuoy housings

1 Scope

This International Standard specifies the construction and dimensions of housing for lifebuoys.

The housing serves to encase a lifebuoy to protect it against deterioration from the elements and against vandalism.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 2768-1, *General tolerances — Part 1: Tolerances for linear and angular dimensions without individual tolerance indications*

ISO 18422, *Ships and marine technology — Inland navigation vessels — Plate with instructions for rescue, resuscitation and first aid for drowning persons*

IEC 60945, *Maritime navigation and radiocommunication equipment and systems — General requirements — Methods of testing and required test results*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

lifebuoy

buoyant ring provided with *grab lines* (3.2) and reflective strips

Note 1 to entry: A lifebuoy enables a person to keep himself above water, marks the location of the emergency, and aids recovery. Lifebuoys can be fitted with lines and light sources in accordance with official regulations.

3.2

grab line

fibre rope for seizing and grabbing the *lifebuoy* (3.1) in water

4 Requirements

4.1 Dimensions

General tolerances: ISO 2768-c

Edges shall be rounded with: min. $R = 0,3$ mm.

NOTE Radius is given to prevent clothing getting caught.

The internal dimensions are to be chosen so that a lifebuoy of 760 mm outer diameter, 440 mm inner diameter and of 103 mm thickness with a grab line at its outer edge and a floatable line with a diameter of 8 mm to 11 mm and 30 m length, with or without throw line, fits into the housing.

4.2 Design

4.2.1 Interior

The interior of the housing shall be designed so that neither the lifebuoy nor the life-line will fall off when the cover is opened and at the same time allows quick and easy access to both.

4.2.2 Cover

The housing shall have a cover with bolting. The cover shall have a captive connection to the housing. The closing latches shall keep the door shut, but allow quick and easy access the lifebuoy.

The design of the cover shall allow an easy access of the life buoy.

The cover of the housing shall have a lifebuoy symbol to the outside and the plate with directions for rescue and resuscitation of drowning persons in accordance with ISO 18422 shall be fastened inside the inner circle of the lifebuoy symbol.

4.2.3 Mounting

The housing for lifebuoys shall be manufactured in such a way that it can be fixed to masts, posts and poles or onto walls or railings.

These requirements are met if there are four bolt holes for the fixing of the housing through which threaded bolts can be inserted.

4.3 Material

The housing shall be of a suitable material, e.g.:

- plastics (Pl);
- seawater-resistant aluminium (Al);
- hot-dip galvanised steel (HDG);
- stainless steel (Stst).

4.4 Resistance

The housing shall comply with the requirements in accordance with IEC 60945 regarding the following:

- a) rain and spray water;
- b) sun radiation;
- c) resistance against oil;
- d) corrosion.

4.5 Temperature stability

The utilizability of the housing shall remain constant at air temperatures of $-25\text{ }^{\circ}\text{C}$ to $+65\text{ }^{\circ}\text{C}$.

4.6 Colour

The external surface of the housing shall be orange or red.

4.7 Operational status check and seal ability

The housing may be fitted with an indicating device at the front, whether a lifebuoy is inside the housing or not.

The housing may allow for an indicating seal to be used.

4.8 Resistance

The housing shall have sufficient strength. Testing shall be according to [5.4](#).

5 Testing

5.1 Scope and testing

Type approval test on one housing shall be carried out.

The tests shall include the following individual tests as described below. The test is performed by visual inspection, function test and measuring.

5.2 Visual inspection and functional test

The performance, the quality of the surface, the colour, the functioning of the indicating device, if applicable, and the feasibility to attach an indicating seal, if applicable, shall be tested by visual inspection and function test.

5.3 Resistance

The manufacturer shall present certificates proving that the relevant requirements in [4.4](#) and [4.5](#) are fulfilled.

5.4 Strength test

The test shall be carried out at an ambient temperature of $+20\text{ °C} \pm 5\text{ °C}$.

Prior to the test the housing shall be fixed according to the manufacturer's instruction. The housing shall be filled with lifebuoy and the line as described in [4.1](#) and closed.

Then a textile belt of a width of $35\text{ mm} \pm 5\text{ mm}$ with means for attaching the test weight shall be placed around the housing. With this, the test weight of 100 kg shall be applied to the belt and maintained for 60 s.

During and after the test, the housing shall neither become loosened from the fixation nor show any malfunction nor permanent deformation or damage.

5.5 Mounting instruction

The manufacturer shall provide mounting instructions.

6 Designation

For the designation of material, the material abbreviation in [4.3](#) shall be used.

Designation of a lifebuoy housing in accordance with this International Standard, material plastic PI (PI):

Lifebuoy housing ISO 18421 — PI

7 Marking

The housing shall be permanently marked with the following details:

- a) a reference to this International Standard, i.e. ISO 18421;
- b) year of manufacture.

British Standards Institution (BSI)

BSI is the national body responsible for preparing British Standards and other standards-related publications, information and services.

BSI is incorporated by Royal Charter. British Standards and other standardization products are published by BSI Standards Limited.

About us

We bring together business, industry, government, consumers, innovators and others to shape their combined experience and expertise into standards-based solutions.

The knowledge embodied in our standards has been carefully assembled in a dependable format and refined through our open consultation process. Organizations of all sizes and across all sectors choose standards to help them achieve their goals.

Information on standards

We can provide you with the knowledge that your organization needs to succeed. Find out more about British Standards by visiting our website at bsigroup.com/standards or contacting our Customer Services team or Knowledge Centre.

Buying standards

You can buy and download PDF versions of BSI publications, including British and adopted European and international standards, through our website at bsigroup.com/shop, where hard copies can also be purchased.

If you need international and foreign standards from other Standards Development Organizations, hard copies can be ordered from our Customer Services team.

Subscriptions

Our range of subscription services are designed to make using standards easier for you. For further information on our subscription products go to bsigroup.com/subscriptions.

With **British Standards Online (BSOL)** you'll have instant access to over 55,000 British and adopted European and international standards from your desktop. It's available 24/7 and is refreshed daily so you'll always be up to date.

You can keep in touch with standards developments and receive substantial discounts on the purchase price of standards, both in single copy and subscription format, by becoming a **BSI Subscribing Member**.

PLUS is an updating service exclusive to BSI Subscribing Members. You will automatically receive the latest hard copy of your standards when they're revised or replaced.

To find out more about becoming a BSI Subscribing Member and the benefits of membership, please visit bsigroup.com/shop.

With a **Multi-User Network Licence (MUNL)** you are able to host standards publications on your intranet. Licences can cover as few or as many users as you wish. With updates supplied as soon as they're available, you can be sure your documentation is current. For further information, email bsmusales@bsigroup.com.

BSI Group Headquarters

389 Chiswick High Road London W4 4AL UK

Revisions

Our British Standards and other publications are updated by amendment or revision.

We continually improve the quality of our products and services to benefit your business. If you find an inaccuracy or ambiguity within a British Standard or other BSI publication please inform the Knowledge Centre.

Copyright

All the data, software and documentation set out in all British Standards and other BSI publications are the property of and copyrighted by BSI, or some person or entity that owns copyright in the information used (such as the international standardization bodies) and has formally licensed such information to BSI for commercial publication and use. Except as permitted under the Copyright, Designs and Patents Act 1988 no extract may be reproduced, stored in a retrieval system or transmitted in any form or by any means – electronic, photocopying, recording or otherwise – without prior written permission from BSI. Details and advice can be obtained from the Copyright & Licensing Department.

Useful Contacts:

Customer Services

Tel: +44 845 086 9001

Email (orders): orders@bsigroup.com

Email (enquiries): cservices@bsigroup.com

Subscriptions

Tel: +44 845 086 9001

Email: subscriptions@bsigroup.com

Knowledge Centre

Tel: +44 20 8996 7004

Email: knowledgecentre@bsigroup.com

Copyright & Licensing

Tel: +44 20 8996 7070

Email: copyright@bsigroup.com