

BS ISO 19357:2016



BSI Standards Publication

Ships and marine technology — Marine cranes — Design requirements for low temperature operation

National foreword

This British Standard is the UK implementation of ISO 19357:2016.

The UK participation in its preparation was entrusted to Technical Committee SME/32, Ships and marine technology - Steering committee.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2016.

Published by BSI Standards Limited 2016

ISBN 978 0 580 85261 9

ICS 47.020.40

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 30 November 2016.

Amendments/corrigenda issued since publication

| Date | Text affected |
|------|---------------|
|------|---------------|

INTERNATIONAL
STANDARD

BS ISO 19357:2016

ISO
19357

First edition
2016-11-15

**Ships and marine technology —
Marine cranes — Design requirements
for low temperature operation**

*Navires et technologie maritime — Grues marines — Exigences de
conception pour une exploitation à basses températures*



Reference number
ISO 19357:2016(E)

© ISO 2016



COPYRIGHT PROTECTED DOCUMENT

© ISO 2016, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

Page

| | |
|--|----------|
| Foreword | v |
| 1 Scope | 1 |
| 2 Normative references | 1 |
| 3 Terms and definitions | 2 |
| 4 Design parameters of cranes | 2 |
| 4.1 Design classification grade..... | 2 |
| 4.2 Design temperature..... | 2 |
| 5 Force and load | 3 |
| 5.1 General..... | 3 |
| 5.2 Snow load..... | 3 |
| 5.3 Ice load..... | 3 |
| 5.4 Other load..... | 3 |
| 6 Selection of materials | 3 |
| 6.1 Rolled steel..... | 3 |
| 6.1.1 General..... | 3 |
| 6.1.2 Impact properties..... | 3 |
| 6.1.3 Others..... | 4 |
| 6.2 Forgings..... | 4 |
| 6.2.1 General..... | 4 |
| 6.2.2 Slewing ring..... | 5 |
| 6.2.3 Connecting bolt of slewing support..... | 5 |
| 6.2.4 Hook, ring, shackle, chain, shaft and pin..... | 5 |
| 6.3 Castings..... | 5 |
| 6.4 Welding materials..... | 5 |
| 6.4.1 Selection of welding materials..... | 5 |
| 6.5 Hydraulic sealing materials..... | 6 |
| 6.6 Low-freezing grease..... | 6 |
| 6.6.1 Hydraulic oil..... | 6 |
| 6.6.2 Gear oil..... | 6 |
| 6.6.3 Lubricating grease..... | 6 |
| 7 Structure design | 6 |
| 8 Design of power plant, mechanism and operating system | 6 |
| 8.1 General..... | 6 |
| 8.2 Power unit..... | 7 |
| 8.3 Mechanical unit..... | 7 |
| 8.4 Electric control unit..... | 7 |
| 9 Design of safety and protection system | 7 |
| 9.1 Safety protection of marine crane..... | 7 |
| 9.2 System heating and insulation protection..... | 7 |
| 9.2.1 Insulation protection of tower body structure..... | 7 |
| 9.2.2 Protection of cabin..... | 7 |
| 9.2.3 Protection against moisture in navigation..... | 7 |
| 9.2.4 Heating before working..... | 8 |
| 9.3 Surface protection at low temperature..... | 8 |
| 9.4 Platform and passage..... | 8 |
| 10 Rope and removable parts | 8 |
| 10.1 Rope..... | 8 |
| 10.2 Sheave (pulley block)..... | 8 |
| 10.2.1 Material of sheave..... | 8 |
| 10.2.2 Bearing and lubrication..... | 8 |

| | | |
|-----------|---|-----------|
| 11 | Inspection and acceptance | 8 |
| 11.1 | General..... | 8 |
| 11.2 | Functional and performance tests..... | 8 |
| 11.3 | Visual and surface protective inspection..... | 9 |
| | Bibliography | 10 |

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

The committee responsible for this document is ISO/TC 8, *Ships and marine technology*, Subcommittee SC 4, *Outfitting and deck machinery*.

Ships and marine technology — Marine cranes — Design requirements for low temperature operation

1 Scope

This document specifies the requirements for design, construction, safety, performance, acceptance test and operation of marine cranes for low temperature operation.

This document is applicable to marine cranes of the following types, which are exposed to and operated in low temperatures:

- deck cranes mounted on ships for handling cargo or containers in harbour or sheltered water conditions;
- floating cranes or grab cranes mounted on barges or pontoons for operating in harbour conditions or sheltered water conditions;
- engine room cranes and provision cranes, etc. mounted on ships (including floating docks) for handling equipment and stores in harbour conditions.

This document is not applicable to the following:

- minimum ambient operating temperatures no less than -20 °C ;
- maximum ambient operating temperatures above $+45\text{ °C}$;
- transport, assembly, dismantling and decommissioning of cranes;
- lifting accessories, i.e. any item between the crane and the load;
- lifting operations involving more than one crane;
- hand powered cranes;
- emergency rescue operations;
- shore-side cargo handling cranes;
- portable cranes on board;
- lifting appliances for lifeboats, liferafts accommodation ladders and pilot ladders;
- launching appliances for survival craft and rescue boats;
- gangways, accommodation and pilot ladders and their handling appliances.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 19354, *Ships and marine technology — Marine cranes — General requirements*

ISO 19355, *Ships and marine technology — Marine cranes — Structural requirements*

ISO 19356, *Ships and marine technology — Marine cranes — Test specification and procedures*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 4306-1, ISO 3828 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

3.1 mean daily low temperature MDLT

mean value of the daily low temperature for each day of the year over a minimum of ten-year period

Note 1 to entry: A data set acceptable to the administration may be used if ten years of data is not available.

3.2 polar service temperature PST

temperature specified for a ship which is intended to operate in low air temperature, which shall be set at least 10 °C below the lowest *MDLT* (3.1) for the intended area and season of operation in polar waters

3.3 marine crane intend to operate in low temperature

crane which is intended to work in the areas where the lowest *mean daily low temperature (MDLT)* (3.1) is below -10 °C

3.4 design service temperature DST

temperature specified for a ship which is intended to judge the performance of material, machinery and system in low air temperature

Note 1 to entry: Note1 to entry: It is usually decided by the ship-owner according to the use and service condition of the ship. It shall be set at least 10 °C below the lowest *MDLT* (3.1) for the intended area and season of operation in polar waters.

Note 2 to entry: Design service temperature (DST) equal to *polar service temperature (PST)* (3.2).

4 Design parameters of cranes

4.1 Design classification grade

The classification grade of low temperature operating cranes may be in accordance with ISO regulations on common marine cranes.

4.2 Design temperature

Design temperature would decide the steel grade. Hydraulic, electric and lubrication system should be reliable for cranes operated at design temperature and the cranes should stay undamaged at the minimum anticipated temperature.

Design temperature of cranes for low temperature operation is equal to the polar service temperature (PST) of the intended ship.

PST should be decided by ship-owner or ship designer according to mean daily low temperature (MDLT) of the intended operation area. PST would be obtained with reliable temperature records excluding those which occurred at a rate below 2,5 %.

Minimum anticipated temperature should be confirmed by ship-owner or ship designer. If the minimum anticipated temperature data could not be achieved, it should be at least 10 °C below the PST.

5 Force and load

5.1 General

Force and load shall be in accordance with ISO 19354. Snow and ice loads shall be taken into account at the storage condition.

5.2 Snow load

For movable parts, maximum surface area that can occur shall be taken into account for calculation of snow load. Snow load shall be calculated with 3 kg/m².

Only the upper surface or equal cast shadow shall be considered for calculation.

NOTE Both two type snow loads might exist at the same time.

5.3 Ice load

The whole surface area of the crane shall be taken into account with ice coverage. Ice load shall be calculated with 30 kg/m².

5.4 Other load

Ice breaking vibration load should be taken into consideration at the storage condition and effective fixation should be designed for the movable components.

6 Selection of materials

6.1 Rolled steel

6.1.1 General

Mechanical property, chemical composition, deoxidization, heat treatment process and inspection method of rolled steel shall be in accordance with related requirements of common marine cranes.

6.1.2 Impact properties

Requirements for impact test temperatures of materials shall be determined according to design temperature (T_D) and the material thickness (t). Impact test temperatures of steel are given in [Table 1](#) for welded structure.

Table 1 — Impact test temperatures

| Material thickness (<i>t</i>) mm | Design temperature (T_D) °C | | | | | |
|---------------------------------------|------------------------------------|-----------|-----------|-----------|-----------|-----------|
| | -23 ~ -27 | -28 ~ -32 | -33 ~ -38 | -39 ~ -48 | -49 ~ -58 | -59 ~ -68 |
| $t \leq 10$ | +20 | +20 | 0 | -20 | -20 | -40 |
| $10 < t \leq 20$ | 0 | 0 | -20 | -20 | -40 | -40 |
| $20 < t \leq 30$ | 0 | -20 | -20 | -40 | -40 | -60 |
| $30 < t \leq 40$ | -20 | -20 | -40 | -40 | -60 | -60 |
| $40 < t \leq 45$ | -20 | -20 | -40 | -60 | -60 | — |
| $45 < t \leq 50$ | -40 | -40 | -40 | -60 | -60 | — |

The steel grade of materials shall be determined according to design temperature (T_D) and the material thickness (t), as required in [Table 2](#).

Table 2 — Steel grade requirements

| Material thickness (<i>t</i>) mm | Design temperature (°C) | | | | | | | | | | | |
|---------------------------------------|-------------------------|----|-----------|----|-----------|----|-----------|----|-----------|----|-----------|----|
| | -23 ~ -27 | | -28 ~ -32 | | -33 ~ -38 | | -39 ~ -48 | | -49 ~ -58 | | -59 ~ -68 | |
| | MS | HT | MS | HT | MS | HT | MS | HT | MS | HT | MS | HT |
| $t \leq 10$ | A | AH | A | AH | B | AH | D | DH | D | DH | E | EH |
| $10 < t \leq 20$ | B | AH | B | AH | D | DH | D | DH | E | EH | E | EH |
| $20 < t \leq 30$ | B | AH | D | DH | D | DH | E | EH | E | EH | — | FH |
| $30 < t \leq 40$ | D | DH | D | DH | E | EH | E | EH | — | FH | — | FH |
| $40 < t \leq 45$ | D | DH | D | DH | E | EH | — | FH | — | FH | — | — |
| $45 < t \leq 50$ | E | EH | E | EH | E | EH | — | FH | — | FH | — | — |

MS — Mild Steel
HT — High Tensile

6.1.3 Others

For members which bearing tensile stress in thickness direction, Z-grade material should be selected with thickness above 50 mm.

6.2 Forgings

6.2.1 General

All forgings used by low temperature operating cranes shall be made from fully deoxidation steel.

Heat treatment, test, inspection and defect repair of forgings should be carried out in accordance with related requirements of common marine cranes.

Impact test temperatures of forgings are given in [Table 3](#).

Table 3 — Impact test temperatures

| Design temperature (°C) | | | |
|-------------------------|-----------|-----------|-----------------------|
| -23 ~ -27 | -28 ~ -32 | -33 ~ -38 | -39 ~ -48 |
| -20 | -20 | -40 | Special consideration |

For steel with yield stress below 305 N/mm², minimum average Akv should be no less than 27 J. For steel with yield stress above 305 N/mm², minimum average Akv should be no less than 34 J.

6.2.2 Slewing ring

The slewing ring shall be made of forgings. The impact test temperatures of material shall comply with the specification of [Table 3](#) while the impact energy (J) should comply with the [Table 4](#).

Table 4 — Performance requirements of slewing ring

| | | |
|-------------------|----------------|-----|
| Impact energy (J) | Average | ≥42 |
| | Single minimum | ≥27 |

6.2.3 Connecting bolt of slewing support

Connecting bolts of slewing support shall be in accordance with ISO 19355.

Requirements in [6.2.1](#) should be adopted.

6.2.4 Hook, ring, shackle, chain, shaft and pin

Forgings of hooks, rings, shackles, chains, shafts and pins shall be made from fully deoxidization steel and fine-grain treated non-ageing steel. Mechanical properties of such steel forgings shall comply with the specification in [Table 5](#) while the impact test temperatures shall comply with [Table 3](#).

Table 5 — Impact requirements (longitudinal value) for hooks, rings, shackles, chains, shafts and pins

| Yield strength (N/mm ²) | | 235 ≤ R _{eH} < 300 | 300 ≤ R _{eH} < 355 | 355 ≤ R _{eH} < 500 | 500 ≤ R _{eH} < 690 | R _{eH} ≥ 690 |
|--|---------------|-----------------------------|-----------------------------|-----------------------------|-----------------------------|-----------------------|
| Tensile strength (N/mm ²) | | 400 to 560 | ≤620 | ≤770 | ≤940 | >940 |
| Yield strength to tensile strength ratio | | | ≤0,85 | ≤0,85 | ≤0,9 | |
| Elongation (%) | | ≥22 | ≥20 | ≥16 | ≥14 | |
| Reduction in area (%) | | ≥40 | ≥35 | ≥35 | ≥35 | |
| Impact energy (J) | Average | ≥42 | ≥42 | ≥42 | ≥42 | ≥42 |
| | Minimum value | ≥27 | ≥27 | ≥27 | ≥27 | ≥27 |

6.3 Castings

For main stressed structures of ice operating cranes, steel castings shall not be used.

For non-main stressed parts, steel which made of fully deoxidization steel castings can be used.

6.4 Welding materials

6.4.1 Selection of welding materials

6.4.1.1 Toughness requirements of main welds shall be considered for important stressed components and the low-hydrogen basic welding materials should be selected.

NOTE Important stressed components means components which could determine the structural safety and evaluation for safe operation of crane, including jib, post, slewing ring, eye plate, etc.

6.4.1.2 Welding material matching for welding structures is, in principle, equal matching. When welding steels with different steel grades and strength grades, overmatching is applicable to Grades 235 to 345 (including Grade 235) and undermatching is, in principle, applicable to the grade above Grade 345.

6.5 Hydraulic sealing materials

Hydraulic seals such as oil seal and O-ring shall use the components with low flexibility and good brittleness in cold condition.

6.6 Low-freezing grease

6.6.1 Hydraulic oil

Hydraulic oil shall be selected according to extreme low temperatures in the route and the minimum start-up oil temperature of the system, while considering the maximum design working oil temperature of the system. It shall meet the following requirements.

- a) Freezing points of hydraulic oil shall be lower than the extreme low temperature in the route.
- b) Viscosity of hydraulic oil for the minimum oil temperature of the system shall be less than the allowable start-up range of the system and components.

6.6.2 Gear oil

For closed gear oil, appropriate lubricating oil shall be selected according to the features of drive gear. It shall meet the following requirements.

- a) The pour point of gear oil shall be lower than extreme low temperature in the route.
- b) Features of gear oil such as little moisture, low frothiness and small growth rate of viscosity ensure that viscosity within the allowable working temperature range of the crane can meet the working requirements of the gear.
- c) For open gear oil, the lubricating oil with viscosity index meeting the requirements shall be selected, with the high temperature in the navigation zone during the ship navigation taken into account.

6.6.3 Lubricating grease

For lubricating grease, low-freezing and extreme pressure lubricating grease shall be selected.

7 Structure design

Structure design shall be in accordance with ISO 19355. Fatigue analysis should be carried out.

8 Design of power plant, mechanism and operating system

8.1 General

Power plants, mechanisms and operating devices shall be arranged in a well-closed tower body structure and cabin to the maximum extent. If some mechanisms are unable to be arranged in the house or cab, a proper means of insulation shall be provided.

Power plants, mechanisms and operating devices need not to comply with the crane design temperature. Effective heating device is essential. However, these parts should stay in good condition at the design temperature or min anticipated temperature.

8.2 Power unit

The power system shall be designed such that the features in a low temperature condition are taken into full account; for the hydraulic system, features of hydraulic oil shall be taken into full account and low speed high torque hydraulic components shall be preferred.

The hydraulic oil tank shall be enlarged appropriately in the design, with the volume change rate considered.

8.3 Mechanical unit

Mechanical units include actuating mechanisms with hoisting, pitching and slewing operations. Unless otherwise specified herein, the design may be conducted in accordance with common marine cranes.

8.4 Electric control unit

Electric components, including cables and lights, shall be selected such that they have the capacity of withstanding extreme low temperatures in the navigation zone.

9 Design of safety and protection system

9.1 Safety protection of marine crane

Safety protection shall be in accordance with the relevant parts in ISO 19354.

9.2 System heating and insulation protection

9.2.1 Insulation protection of tower body structure

The insulation protection of the tower body structure shall meet the following conditions.

- a) Under the minimum working conditions, the heat transfer of the tower body structure shall be no more than the heat produced by the system during the idle running of the crane.
- b) The insulating material attached onto the tower body structure shall have good adhesion and can effectively endure ship swaying and vibration generated on icebreaking route.
- c) The insulating material shall meet the requirements for environmental protection, in addition to safe, environment-friendly, non-toxic, strong flame-retardant, low water absorption, and low dimensional change rate.
- d) The insulating material shall have a certain resistance to salt spray and corrosion, and not have chemical reaction with possible contact media (such as hydraulic oil, gear oil, etc.).

9.2.2 Protection of cabin

For the insulation protection of cabin, the insulating material shall have the same requirements as that of the tower body structure. In addition, comfortability of the operating environment shall be taken into full account.

The glass of the cabin shall be resistant to extremely low temperature in the navigating area, and have anti-fogging function.

9.2.3 Protection against moisture in navigation

Electrical appliances, such as electric motor, control cabinet, etc., shall be provided with a heater.

9.2.4 Heating before working

The tower body structure inside shall be equipped with a heater, which is required to have such ability that can raise the temperature of the tower body structure from the minimum operating ambient temperature to the temperature at which the hydraulic system can start up and operate.

9.3 Surface protection at low temperature

The surface of marine ice operating cranes, especially the external surface exposed to the air, shall have the ability to resist extremely low temperature in the navigating area.

9.4 Platform and passage

Considering the low temperature, platform and passage should be skid-proof. People need to stay or pass the platform and passage conveniently with warm wear.

10 Rope and removable parts

10.1 Rope

The rope of cranes for low temperature operation should be in accordance with related requirements of common marine cranes. However, the lubrication should have a special consideration.

10.2 Sheave (pulley block)

10.2.1 Material of sheave

For the sheave used in cranes for low temperature operation, especially the material of the wire rope sheave, it is preferred to use steel but not cast iron material other than ferrous casting ductile (FCD) which should be complied with the temperature requirement.

10.2.2 Bearing and lubrication

The sheave can use self-lubricating bearing.

If grease lubrication bearing is selected, the lubrication cavity shall be designed to have a leak tight structure and the lubrication at low temperature in ice shall be taken into full consideration.

11 Inspection and acceptance

11.1 General

Manufacturers and purchasers may reach an agreement regarding the required shop test. Before the first actual use of the crane, an overall test and inspection shall be carried out. Ice and snow should be swept out before test, if necessary.

Repeated tests shall be also done regularly after the crane is put into service.

11.2 Functional and performance tests

Functional and performance tests shall be in accordance with ISO 19356.

By means of simulation test, the effect of the insulating device in the cabin should be confirmed.

11.3 Visual and surface protective inspection

After the functional and performance test, check stressed structure and weld of the crane.

Bibliography

- [1] ISO 3828, *Shipbuilding and marine structures — Deck machinery — Vocabulary and symbols*
- [2] ISO 4301-4, *Cranes and related equipment — Classification — Part 4: Jib cranes*
- [3] ISO 4306-1, *Cranes — Vocabulary — Part 1: General*
- [4] ISO 7363, *Cranes and lifting appliances — Technical characteristics and acceptance documents*
- [5] ISO 8686-4, *Cranes — Design principles for loads and load combinations — Part 4: Jib cranes*
- [6] ISO 9927-1, *Cranes — Inspections — Part 1: General*
- [7] ISO 9928-1, *Cranes — Crane operating manual — Part 1: General*
- [8] ISO 10972-4, *Cranes — Requirements for mechanisms — Part 4: Jib cranes*
- [9] ISO 11660-4, *Cranes — Access, guards and restraints — Part 4: Jib cranes*
- [10] ISO 12210-4, *Cranes — Anchoring devices for in-service and out-of-service conditions — Part 4: Jib cranes*
- [11] ISO 12478-1, *Cranes — Maintenance manual — Part 1: General*
- [12] ISO 12482, *Cranes — Monitoring for crane design working period*
- [13] ISO 19359, *Ships and marine technology—Marine cranes—Design methods for drums*
- [14] ISO 19360, *Ships and marine technology—Marine cranes—Technical requirements for rigging applications*
- [15] IMO, *International code for ships operating in polar waters*
- [16] IACS, *Requirements concerning materials and welding for Polar*
- [17] CCS, *Guide for ships operated in Polar Water*
- [18] CCS, *Construction and classification of sea-going steel ships specification*, March 2016
- [19] LR, *Provisional rules for winterisation of ships*, July 2015
- [20] LR, *Lloyd's Register's Code for Lifting Appliances in a Marine Environment*, July 2015

British Standards Institution (BSI)

BSI is the national body responsible for preparing British Standards and other standards-related publications, information and services.

BSI is incorporated by Royal Charter. British Standards and other standardization products are published by BSI Standards Limited.

About us

We bring together business, industry, government, consumers, innovators and others to shape their combined experience and expertise into standards-based solutions.

The knowledge embodied in our standards has been carefully assembled in a dependable format and refined through our open consultation process. Organizations of all sizes and across all sectors choose standards to help them achieve their goals.

Information on standards

We can provide you with the knowledge that your organization needs to succeed. Find out more about British Standards by visiting our website at bsigroup.com/standards or contacting our Customer Services team or Knowledge Centre.

Buying standards

You can buy and download PDF versions of BSI publications, including British and adopted European and international standards, through our website at bsigroup.com/shop, where hard copies can also be purchased.

If you need international and foreign standards from other Standards Development Organizations, hard copies can be ordered from our Customer Services team.

Copyright in BSI publications

All the content in BSI publications, including British Standards, is the property of and copyrighted by BSI or some person or entity that owns copyright in the information used (such as the international standardization bodies) and has formally licensed such information to BSI for commercial publication and use.

Save for the provisions below, you may not transfer, share or disseminate any portion of the standard to any other person. You may not adapt, distribute, commercially exploit, or publicly display the standard or any portion thereof in any manner whatsoever without BSI's prior written consent.

Storing and using standards

Standards purchased in soft copy format:

- A British Standard purchased in soft copy format is licensed to a sole named user for personal or internal company use only.
- The standard may be stored on more than 1 device provided that it is accessible by the sole named user only and that only 1 copy is accessed at any one time.
- A single paper copy may be printed for personal or internal company use only.

Standards purchased in hard copy format:

- A British Standard purchased in hard copy format is for personal or internal company use only.
- It may not be further reproduced – in any format – to create an additional copy. This includes scanning of the document.

If you need more than 1 copy of the document, or if you wish to share the document on an internal network, you can save money by choosing a subscription product (see 'Subscriptions').

Reproducing extracts

For permission to reproduce content from BSI publications contact the BSI Copyright & Licensing team.

Subscriptions

Our range of subscription services are designed to make using standards easier for you. For further information on our subscription products go to bsigroup.com/subscriptions.

With **British Standards Online (BSOL)** you'll have instant access to over 55,000 British and adopted European and international standards from your desktop. It's available 24/7 and is refreshed daily so you'll always be up to date.

You can keep in touch with standards developments and receive substantial discounts on the purchase price of standards, both in single copy and subscription format, by becoming a **BSI Subscribing Member**.

PLUS is an updating service exclusive to BSI Subscribing Members. You will automatically receive the latest hard copy of your standards when they're revised or replaced.

To find out more about becoming a BSI Subscribing Member and the benefits of membership, please visit bsigroup.com/shop.

With a **Multi-User Network Licence (MUNL)** you are able to host standards publications on your intranet. Licences can cover as few or as many users as you wish. With updates supplied as soon as they're available, you can be sure your documentation is current. For further information, email subscriptions@bsigroup.com.

Revisions

Our British Standards and other publications are updated by amendment or revision.

We continually improve the quality of our products and services to benefit your business. If you find an inaccuracy or ambiguity within a British Standard or other BSI publication please inform the Knowledge Centre.

Useful Contacts

Customer Services

Tel: +44 345 086 9001

Email (orders): orders@bsigroup.com

Email (enquiries): cservices@bsigroup.com

Subscriptions

Tel: +44 345 086 9001

Email: subscriptions@bsigroup.com

Knowledge Centre

Tel: +44 20 8996 7004

Email: knowledgecentre@bsigroup.com

Copyright & Licensing

Tel: +44 20 8996 7070

Email: copyright@bsigroup.com

BSI Group Headquarters

389 Chiswick High Road London W4 4AL UK