

BS ISO 21483:2013



BSI Standards Publication

# Determination of solubility in nitric acid of plutonium in unirradiated mixed oxide fuel pellets (U, Pu) O<sub>2</sub>

**bsi.**

...making excellence a habit.™

**National foreword**

This British Standard is the UK implementation of ISO 21483:2013.

The UK participation in its preparation was entrusted to Technical Committee NCE/9, Nuclear fuel cycle technology.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2013. Published by BSI Standards Limited 2013

ISBN 978 0 580 76907 8

ICS 27.120.30

**Compliance with a British Standard cannot confer immunity from legal obligations.**

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 October 2013.

**Amendments issued since publication**

Date	Text affected
------	---------------

---

INTERNATIONAL  
STANDARD

**ISO**  
**21483**

First edition  
2013-11-01

---

---

**Determination of solubility in nitric acid of plutonium in unirradiated mixed oxide fuel pellets (U, Pu) O2**

*Détermination de la solubilité dans l'acide nitrique du plutonium des pastilles (U, Pu) O2 de combustibles d'oxydes mixtes non irradiés*



Reference number  
ISO 21483:2013(E)

© ISO 2013



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2013

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.org](mailto:copyright@iso.org)  
Web [www.iso.org](http://www.iso.org)

Published in Switzerland

# Contents

	Page
<b>Foreword</b> .....	<b>iv</b>
<b>1 Scope</b> .....	<b>1</b>
<b>2 Principle</b> .....	<b>1</b>
<b>3 Interferences</b> .....	<b>1</b>
<b>4 Reagents</b> .....	<b>1</b>
4.1 Concentrated nitric acid.....	1
4.2 Nitric acid high.....	1
4.3 Nitric acid low.....	1
4.4 Concentrated hydrofluoric acid.....	1
4.5 Mixture of acid.....	1
4.6 Sodium hydroxide.....	2
<b>5 Apparatus</b> .....	<b>2</b>
5.1 Analytical balance.....	2
5.2 Dissolution apparatus with total reflux condenser.....	2
5.3 Dissolution apparatus without total reflux condenser.....	2
5.4 Second dissolution apparatus (polytetrafluoroethylene, PTFE, high density polyethylene, HDPE).....	2
5.5 Filter apparatus.....	2
<b>6 Sampling</b> .....	<b>2</b>
<b>7 Procedure</b> .....	<b>3</b>
7.1 Preparation of the sample.....	3
7.2 Dissolution procedure.....	3
7.3 Treatment of the residue.....	3
7.4 Plutonium determination.....	3
7.5 Repeat solubility test.....	3
<b>8 Expression of results</b> .....	<b>4</b>
8.1 Method of calculation.....	4
8.2 Total uncertainty of the Pu measurement.....	4
<b>9 Test report</b> .....	<b>4</b>
<b>Bibliography</b> .....	<b>5</b>

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2. [www.iso.org/directives](http://www.iso.org/directives)

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received. [www.iso.org/patents](http://www.iso.org/patents)

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

The committee responsible for this document is ISO/TC 85, *Nuclear energy, nuclear technologies and radiological protection*, Subcommittee SC 5, *Nuclear fuel cycle*.

This first edition of ISO 21483 cancels and replaces ISO 12184:1994, which has been technically revised.

# Determination of solubility in nitric acid of plutonium in unirradiated mixed oxide fuel pellets (U, Pu) O2

## 1 Scope

This International Standard specifies an analytical method for determining the solubility in nitric acid of plutonium in pellets of unirradiated mixed oxide fuel (light-water reactor fuels). The results provide information about the expected dissolution behaviour of irradiated pellets under industrial reprocessing conditions. In this aspect, the specific conditions (e.g. time of the test) may vary depending upon the need to match to a specific reprocessor's requirements. The test is aimed at determining solubility under equilibrium conditions rather than the kinetics of dissolution and hence allows for a second dissolution period.

## 2 Principle

A specified number of mixed oxide pellets of known plutonium content and mass are dissolved in a boiling nitric acid solution. The initial concentration of the nitric acid, the final content of U, Pu and the boiling time are carefully controlled. The undissolved residue is then dissolved quantitatively by boiling in a mixture of nitric acid and hydrofluoric acid. The plutonium content of this residue is determined by an appropriate analytical method. The solubility is expressed by the ratio of the amount of plutonium dissolved in nitric acid to the amount of plutonium in the sample.

## 3 Interferences

The dissolution apparatus ([Clause 5](#)) and the reagents shall not be contaminated with fluoride, as fluoride can cause an increase in the solubility of the pellets in nitric acid.

## 4 Reagents

Use only reagents of analytical grade and distilled or demineralised water or water of equivalent purity. Prepare the reagents in compliance with the local laboratory safety instructions.

### 4.1 Concentrated nitric acid

$\rho = 1,40$  g/ml or more

### 4.2 Nitric acid high

Solution  $[c(\text{HNO}_3) = 10$  mol/l]

### 4.3 Nitric acid low

Solution  $[c(\text{HNO}_3) = 0,5$  mol/l].

### 4.4 Concentrated hydrofluoric acid

$\rho = 1,13$  g/ml

### 4.5 Mixture of acid

Nitric acid, solution  $[c(\text{HNO}_3) = 14,4$  mol/l] and hydrofluoric acid, solution  $[c(\text{HF}) = 0,05$  mol/l].

## 4.6 Sodium hydroxide

Solution [ $c(\text{NaOH}) = 2 \text{ mol/l}$ ] (optional).

## 5 Apparatus

Usual laboratory apparatus and, in particular, the following.

### 5.1 Analytical balance

Balance with a 0,1 mg accuracy or better.

### 5.2 Dissolution apparatus with total reflux condenser

Consisting of dissolver flask (glass borosilicate or high density polyethylene HDPE are suitable), heater, total reflux condenser and gas inlet tube. The volume capacity of the flask shall reflect the sample size selected in [Clause 6](#).

### 5.3 Dissolution apparatus without total reflux condenser

Consisting of dissolver flask (glass borosilicate or high density polyethylene HDPE are suitable), heater, condenser and gas washer bottle. The volume capacity of the flask shall reflect the sample size selected in [Clause 6](#).

### 5.4 Second dissolution apparatus (polytetrafluoroethylene, PTFE, high density polyethylene, HDPE)

For the dissolution with nitric acid/hydrofluoric acid mixture. This second dissolution is carried out with total reflux condenser ([Clause 5](#)).

### 5.5 Filter apparatus

Apparatus consisting of a vacuum funnel and a nitric-acid-resistant filter of a pore size less or equal to 1 micron (e.g. nitrocellulose or polycarbonate membrane filter 1  $\mu\text{m}$ ).

## 6 Sampling

The sample size shall be large enough to be representative of the lot, both whole and broken pellets are acceptable for this test. The minimum sample size could be chosen as a function of the pellet composition and the laboratory's detection limit. In any way, the minimum size must be equal or greater than 1 pellet.



## 7 Procedure

### 7.1 Preparation of the sample

Weigh the pellets and transfer quantitatively into the dissolver flask (5.2 and 5.3). In order to reach a heavy metal concentration of around 1 mol/l, the total volume  $V$ , in litres, of nitric acid solution (4.2) to be used is given by

$$V = \frac{m}{cM}$$

where

$m$  is the sum of the mass of uranium and plutonium in the sample in grams,

$M$  is the average atomic weights of the metals, in grams per mole;

$c$  is the concentration of the uranium and plutonium in the solution, in moles per litre ( $c = 1$  mol/l). This value corresponds to the practice of the "reprocessing dissolution of spent fuel".

### 7.2 Dissolution procedure

Introduce the calculated volume of nitric acid solution (4.2) into the flask containing the sample pellets. Boil the contents of the flask under reflux for the specified period (examples are 10 h and 18 h). The time required for the solubility test is dependent upon the commercial contract and agreed with the commercial customer. Boiling shall begin within 30 min. Cooling to below around 50 °C should be ended within 30 min. To avoid a delay in cooling, compressed air may be passed through the solution. The arising nitrous vapour may be trapped in a gas washer bottle filled with sodium hydroxide solution (4.6)

### 7.3 Treatment of the residue

Quantitatively transfer the solution and the undissolved residue into the filter apparatus and filter the solution using the vacuum funnel. Thoroughly rinse the residue on the filter with nitric acid solution (4.3)

If the filtered residue is seen to contain fragments of pellets, this may be indicative of a problem with the manufacture of MOX material. Repeat the test using a tared filter to weigh the residue (7.5).

Place the filter and the residue in a dissolver flask (5.4) and add around 25 ml of the nitric acid/hydrofluoric acid (4.5). Heat the acid to its boiling point and pursue ebullition under reflux until the residue is completely dissolved and at least during 2,5 h.

In general, after this duration, no residue still remains with HNO<sub>3</sub>/HF dissolution. If residue still remains, then it is possible to add hydrofluoric acid (0,05 mol/l) in order to obtain total dissolution.

### 7.4 Plutonium determination

Make up the solution resulting from the treatment of the undissolved residue to a known volume or known mass. Take samples and analyse their plutonium content by a suitable method. The method shall have an uncertainty of 20 % or lower, even in the presence of higher level impurities contained in the dissolved material. The spectrophotometry method described in ISO 9463 is adequate. Other methods like mass spectrometry (TIMS or ICPMS) can also be used.

### 7.5 Repeat solubility test

If visible pellet fragments are observed in the residue of the first dissolution test (7.2), perform a new test on a fresh sample. For this test, the test duration (up to 18 h), concentration of nitric acid (up to 10 mol/l)

and U+Pu concentration (0,9 mol/l) shall be defined before carrying out the test. The conditions of each test and its results should be reported.

## 8 Expression of results

### 8.1 Method of calculation

The plutonium solubility,  $L$ , expressed as mass fraction in percent, is calculated according the following equation:

$$L = \left\{ 1 - \frac{m_2}{m_1 W_{Pu}} \right\} \times 100$$

where

$m_1$  is the mass of the sample, in grams;

$m_2$  is the mass of plutonium in the residue, in grams;

$W_{Pu}$  is the mass fraction of the plutonium in the sample.

### 8.2 Total uncertainty of the Pu measurement

The total uncertainty is dependent upon the mass fraction of the plutonium  $W_{Pu}$  and of the analytical method used to determine the plutonium content in the residue. Typically, for a material with a mass fraction greater than 5 % and a sample size of at least 6 g, a total uncertainty of 20 % can be achieved.

## 9 Test report

The test report shall include the following information:

- a) a reference to this International Standard;
- b) date and place of the test carried out;
- c) identification and mass of the sample;
- d) the reference of the analytical method used;
- e) the method of calculation of the results including the boiling time;
- f) the results and their units;
- g) any unusual features observed during the test;
- h) potential increasing of dissolution time;
- i) any operation regarded as optional.

## Bibliography

- [1] ISO 9463, *Nuclear energy — Nuclear fuel technology — Determination of plutonium in nitric acid solutions by spectrophotometry*





# British Standards Institution (BSI)

BSI is the national body responsible for preparing British Standards and other standards-related publications, information and services.

BSI is incorporated by Royal Charter. British Standards and other standardization products are published by BSI Standards Limited.

## About us

We bring together business, industry, government, consumers, innovators and others to shape their combined experience and expertise into standards-based solutions.

The knowledge embodied in our standards has been carefully assembled in a dependable format and refined through our open consultation process. Organizations of all sizes and across all sectors choose standards to help them achieve their goals.

## Information on standards

We can provide you with the knowledge that your organization needs to succeed. Find out more about British Standards by visiting our website at [bsigroup.com/standards](http://bsigroup.com/standards) or contacting our Customer Services team or Knowledge Centre.

## Buying standards

You can buy and download PDF versions of BSI publications, including British and adopted European and international standards, through our website at [bsigroup.com/shop](http://bsigroup.com/shop), where hard copies can also be purchased.

If you need international and foreign standards from other Standards Development Organizations, hard copies can be ordered from our Customer Services team.

## Subscriptions

Our range of subscription services are designed to make using standards easier for you. For further information on our subscription products go to [bsigroup.com/subscriptions](http://bsigroup.com/subscriptions).

With **British Standards Online (BSOL)** you'll have instant access to over 55,000 British and adopted European and international standards from your desktop. It's available 24/7 and is refreshed daily so you'll always be up to date.

You can keep in touch with standards developments and receive substantial discounts on the purchase price of standards, both in single copy and subscription format, by becoming a **BSI Subscribing Member**.

**PLUS** is an updating service exclusive to BSI Subscribing Members. You will automatically receive the latest hard copy of your standards when they're revised or replaced.

To find out more about becoming a BSI Subscribing Member and the benefits of membership, please visit [bsigroup.com/shop](http://bsigroup.com/shop).

With a **Multi-User Network Licence (MUNL)** you are able to host standards publications on your intranet. Licences can cover as few or as many users as you wish. With updates supplied as soon as they're available, you can be sure your documentation is current. For further information, email [bsmusales@bsigroup.com](mailto:bsmusales@bsigroup.com).

## BSI Group Headquarters

389 Chiswick High Road London W4 4AL UK

## Revisions

Our British Standards and other publications are updated by amendment or revision.

We continually improve the quality of our products and services to benefit your business. If you find an inaccuracy or ambiguity within a British Standard or other BSI publication please inform the Knowledge Centre.

## Copyright

All the data, software and documentation set out in all British Standards and other BSI publications are the property of and copyrighted by BSI, or some person or entity that owns copyright in the information used (such as the international standardization bodies) and has formally licensed such information to BSI for commercial publication and use. Except as permitted under the Copyright, Designs and Patents Act 1988 no extract may be reproduced, stored in a retrieval system or transmitted in any form or by any means – electronic, photocopying, recording or otherwise – without prior written permission from BSI. Details and advice can be obtained from the Copyright & Licensing Department.

## Useful Contacts:

### Customer Services

**Tel:** +44 845 086 9001

**Email (orders):** [orders@bsigroup.com](mailto:orders@bsigroup.com)

**Email (enquiries):** [cservices@bsigroup.com](mailto:cservices@bsigroup.com)

### Subscriptions

**Tel:** +44 845 086 9001

**Email:** [subscriptions@bsigroup.com](mailto:subscriptions@bsigroup.com)

### Knowledge Centre

**Tel:** +44 20 8996 7004

**Email:** [knowledgecentre@bsigroup.com](mailto:knowledgecentre@bsigroup.com)

### Copyright & Licensing

**Tel:** +44 20 8996 7070

**Email:** [copyright@bsigroup.com](mailto:copyright@bsigroup.com)



...making excellence a habit.™