

BS 3TA 11:2009



BSI British Standards

AEROSPACE SERIES

**Specification for bar and section
for machining of titanium-
aluminium-vanadium alloy
(Tensile strength 900–1 160 MPa)
(Limiting ruling section 150 mm)**

NO COPYING WITHOUT BSI PERMISSION EXCEPT AS PERMITTED BY COPYRIGHT LAW

raising standards worldwide™

BSI
British Standards

Publishing and copyright information

The BSI copyright notice displayed in this document indicates when the document was last issued.

© BSI 2009

ISBN 978 0 580 65386 5

ICS 49.025.30

The following BSI references relate to the work on this standard:

Committee reference ACE/61

Draft for comment 09/30193250 DC

Publication history

First published 1968

Second edition, May 1974

Third (present) edition, November 2009

Amendments issued since publication

| Date | Text affected |
|-------------|----------------------|
|-------------|----------------------|

Contents

Foreword *ii*

1 Scope 1

2 Normative references 1

3 Technical requirements 1

Bibliography 4

List of tables

Table 1 – Technical requirements for titanium-aluminium-vanadium bar and section 2

Summary of pages

This document comprises a front cover, an inside front cover, pages i to ii, pages 1 to 4, an inside back cover and a back cover.

Foreword

Publishing information

This British Standard is published by BSI and came into effect on 30 November 2009. It was prepared by Panel ACE/61/-/49, *Titanium and its alloys*, under the authority of Technical Committee ACE/61, *Metallic materials for aerospace purposes*. A list of organizations represented on this committee can be obtained on request to its secretary.

Supersession

This British Standard supersedes BS 2TA 11:1974, which is withdrawn.

Information about this document

This is a full revision of BS TA 11, and introduces the following principal changes.

- a) Requirements are stated in tabular format in accordance with EN 4500-1 and EN 4500-4.
- b) Chemical composition has been amended to add requirements for "other" elements.
- c) Melting method details have been deleted and replaced by reference to Section 1 of BS TA 100.

Hazard warnings

WARNING. This British Standard calls for the use of substances and/or procedures that can be injurious to health if adequate precautions are not taken. It refers only to technical suitability and does not absolve the user from legal obligations relating to health and safety at any stage.

Use of this document

It has been assumed in the preparation of this British Standard that the execution of its provisions will be entrusted to appropriately qualified and experienced people, for whose use it has been produced.

Presentational conventions

The provisions of this standard are presented in roman (i.e. upright) type. Its requirements are expressed in sentences in which the principal auxiliary verb is "shall".

Commentary, explanation and general informative material is presented in smaller italic type, and does not constitute a normative element.

Contractual and legal considerations

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

Compliance with a British Standard cannot confer immunity from legal obligations.

1 Scope

This British Standard specifies requirements for titanium-aluminium-vanadium alloy bar and section with a tensile strength of 900 MPa to 1 160 MPa.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

BS TA 100, *Procedure for inspection, testing and acceptance of wrought titanium and titanium alloys*

3 Technical requirements

Material to this standard shall conform to Table 1.

NOTE The format and symbols used in Table 1 are derived from EN 4500-1 and EN 4500-4.

Table 1 Technical requirements for titanium-aluminium-vanadium bar and section

| 1 | Material designation | | | BS TA 11 | | | | | | | | | | |
|------------------------|------------------------------------|-----------------------|----------------|--|------------------------------|------|----------------|----------------|----------------|-------|--------|------|----|------|
| 2 | Chemical composition % | Element | Al | V | Fe | C | O ₂ | N ₂ | H ₂ | Y | Others | | Ti | |
| | | Min. | 5.50 | 3.50 | — | — | — | — | — | — | — | — | — | Base |
| | | Max. | 6.75 | 4.50 | 0.30 | 0.08 | 0.20 | 0.050 | 0.015 | 0.005 | 0.10 | 0.40 | | |
| 3 | Method of melting | | | See Section 1 of BS TA 100 | | | | | | | | | | |
| 4.1 | Form | | | Bar and section ¹⁾ | | | | | | | | | | |
| 4.2 | Method of production | | | Rolled, forged, drawn or extruded | | | | | | | | | | |
| 4.3 | Limit dimension(s) | mm | a or D ≤ 150 | | | | | | | | | | | |
| 5 | Technical specification | | | Sections 1 and 2 of BS TA 100 | | | | | | | | | | |
| 6.1 | Delivery condition | | | Annealed + centreless ground or machined | | | | | | | | | | |
| | Heat treatment | | | 700 °C ≤ θ ≤ 800 °C / t ≥ 1 h / AC or FC ²⁾ | | | | | | | | | | |
| 6.2 | Delivery condition code | | | U | | | | | | | | | | |
| 7 | Use condition | | | Delivery condition | | | | | | | | | | |
| | Heat treatment | | | — | | | | | | | | | | |
| Characteristics | | | | | | | | | | | | | | |
| 8.1 | Test sample(s) | | | See Section 2 of BS TA 100 | | | | | | | | | | |
| 8.2 | Test piece(s) | | | See Section 2 of BS TA 100 | | | | | | | | | | |
| 8.3 | Heat treatment | | | Use condition | | | | | | | | | | |
| 9 | Dimensions concerned | mm | a or D ≤ 150 | | | | | | | | | | | |
| 10 | Thickness of cladding on each face | % | — | | | | | | | | | | | |
| 11 | Direction of test piece | | | L | | | | | | | | | | |
| 12 | Temperature | θ | °C | Ambient | | | | | | | | | | |
| 13 | Proof stress | R _{p0.2} | MPa | ≥ 830 | | | | | | | | | | |
| 14 | T | Strength | R _m | MPa | 900 ≤ R _m ≤ 1 160 | | | | | | | | | |
| 15 | | Elongation | A | % | ≥ 8 | | | | | | | | | |
| 16 | | Reduction of area | Z | % | ≥ 25 | | | | | | | | | |
| 17 | | Hardness | | | — | | | | | | | | | |
| 18 | Shear strength | R _c | MPa | — | | | | | | | | | | |
| 19 | Bending | κ | — | — | | | | | | | | | | |
| 20 | Impact strength | | | — | | | | | | | | | | |
| 21 | Temperature | θ | °C | — | | | | | | | | | | |
| 22 | Time | | | h | — | | | | | | | | | |
| 23 | Stress | σ _a | MPa | — | | | | | | | | | | |
| 24 | C | Elongation | a | % | — | | | | | | | | | |
| 25 | | Rupture stress | σ _R | MPa | — | | | | | | | | | |
| 26 | | Elongation at rupture | A | % | — | | | | | | | | | |
| 27 | Notes (see line 98) | | | 1), 2) | | | | | | | | | | |

Bibliography

Standards publications

For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

BS TA 10, *Specification of titanium-aluminium-vanadium alloy (Tensile strength 960–1 270 MPa)*

BS TA 12, *Specification for forging stock of titanium-aluminium-vanadium alloy (Tensile strength 900–1 160 MPa) (Limiting ruling section 150 mm)*

BS TA 13, *Specification for forgings of titanium-aluminium-vanadium alloy (Tensile strength 900–1 160 MPa) (Limiting ruling section 150 mm)*

BS TA 28, *Specification for forging stock of titanium-aluminium-vanadium alloy (Tensile strength 1 100–1 300 MPa) (Limiting ruling section 20 mm)*

BS TA 56, *Specification for plate of titanium-aluminium-vanadium alloy (Tensile strength 895–1 150 MPa) (Maximum thickness 100 mm)*

EN 4500-1, *Metallic materials – Rules for the drafting and presentation of material standards – Part 1: General rules*¹⁾

EN 4500-4, *Metallic materials – Rules for the drafting and presentation of material standards – Part 4: Specific rules for titanium and titanium alloys*¹⁾

¹⁾ Published as ASD-STAN Prestandard at the date of publication of this standard.

British Standards Institution (BSI)

BSI is the independent national body responsible for preparing British Standards. It presents the UK view on standards in Europe and at the international level.

It is incorporated by Royal Charter.

Revisions

British Standards are updated by amendment or revision. Users of British Standards should make sure that they possess the latest amendments or editions.

It is the constant aim of BSI to improve the quality of our products and services. We would be grateful if anyone finding an inaccuracy or ambiguity while using this British Standard would inform the Secretary of the technical committee responsible, the identity of which can be found on the inside front cover.

Tel: +44 (0)20 8996 9000 Fax: +44 (0)20 8996 7400

BSI offers members an individual updating service called PLUS which ensures that subscribers automatically receive the latest editions of standards.

Buying standards

Orders for all BSI, international and foreign standards publications should be addressed to BSI Customer Services.

Tel: +44 (0)20 8996 9001 Fax: +44 (0)20 8996 7001
Email: orders@bsigroup.com

You may also buy directly using a debit/credit card from the BSI Shop on the website www.bsigroup.com/shop

In response to orders for international standards, it is BSI policy to supply the BSI implementation of those that have been published as British Standards, unless otherwise requested.

Information on standards

BSI provides a wide range of information on national, European and international standards through its Library.

Various BSI electronic information services are also available which give details on all its products and services. Contact the Information Centre.

Tel: +44 (0)20 8996 7111
Fax: +44 (0)20 8996 7048 Email: info@bsigroup.com

Subscribing members of BSI are kept up to date with standards developments and receive substantial discounts on the purchase price of standards. For details of these and other benefits contact Membership Administration.

Tel: +44 (0)20 8996 7002 Fax: +44 (0)20 8996 7001
Email: membership@bsigroup.com

Information regarding online access to British Standards via British Standards Online can be found at www.bsigroup.com/BSOL

Further information about BSI is available on the BSI website at www.bsigroup.com

Copyright

Copyright subsists in all BSI publications. BSI also holds the copyright, in the UK, of the publications of the international standardization bodies. Except as permitted under the Copyright, Designs and Patents Act 1988 no extract may be reproduced, stored in a retrieval system or transmitted in any form or by any means – electronic, photocopying, recording or otherwise – without prior written permission from BSI.

This does not preclude the free use, in the course of implementing the standard of necessary details such as symbols, and size, type or grade designations. If these details are to be used for any other purpose than implementation then the prior written permission of BSI must be obtained. Details and advice can be obtained from the Copyright & Licensing Manager.

Tel: +44 (0)20 8996 7070 Email: copyright@bsigroup.com

BSI Group Headquarters

389 Chiswick High Road London W4 4AL UK

Tel +44 (0)20 8996 9001

Fax +44 (0)20 8996 7001

www.bsigroup.com/standards

raising standards worldwide™

BSI
British Standards