Petroleum products and other liquids — Applicability of test methods on sulfur determination in petrol and diesel fuel

ICS 75.160.20



National foreword

This Published Document is the official English language version of CEN/TR 15139:2005.

The UK participation in its preparation was entrusted to Technical Committee PTI/13, Petroleum testing and terminology, which has the responsibility to:

- aid enquirers to understand the text;
- present to the responsible international/European committee any enquiries on the interpretation, or proposals for change, and keep UK interests informed;
- monitor related international and European developments and promulgate them in the UK.

A list of organizations represented on this committee can be obtained on request to its secretary.

Cross-references

The British Standards which implement international or European publications referred to in this document may be found in the *BSI Catalogue* under the section entitled "International Standards Correspondence Index", or by using the "Search" facility of the *BSI Electronic Catalogue* or of British Standards Online.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

Compliance with a Published Document does not of itself confer immunity from legal obligations.

Summary of pages

This document comprises a front cover, an inside front cover, the CEN/TR title page, pages 2 to 10, an inside back cover and a back cover.

The BSI copyright notice displayed in this document indicates when the document was last issued.

Amendments issued since publication

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 30 December 2005

 $\ \, {\mathbb C}$ BSI 30 December 2005

Amd. No.	Date	Comments

TECHNICAL REPORT RAPPORT TECHNIQUE TECHNISCHER BERICHT

CEN/TR 15139

August 2005

ICS 75.160.20

English Version

Petroleum products and other liquids - Applicability of test methods on sulfur determination in petrol and diesel fuel

Produits pétroliers et autres liquides - Évaluation de méthodes d'essai de détermination de la teneur en soufre dans l'essence et le gazole Mineralölerzeugnisse und andere Flüssigkeiten -Anwendbarkeit von Prüfverfahren für die Schwefelbestimmung in Ottokraftstoffen und Dieselkraftstoffen

This Technical Report was approved by CEN on 14 May 2005. It has been drawn up by the Technical Committee CEN/TC 19.

CEN members are the national standards bodies of Austria, Belgium, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: rue de Stassart, 36 B-1050 Brussels

Cor	ntents	Page
	word	
Intro	duction	
1	Scope	
2	Test methods	5
3	Samples	5
4	Laboratories	5
5	Evaluation of round robin results	6
6	Statistical analysis	
7	Comparison between methods and accuracy	7
8	Applicability to FAME blends	7
9	Conclusions	7
10	Recommendations for updating EN 228 and EN 590	7
11	Test method publication	8
Ackr	nowledgements	9
Bibli	ography	10

Foreword

This Technical Report (CEN/TR 15139:2005) has been prepared by Technical Committee CEN/TC 19 "Gaseous and liquid fuels, lubricants and related products of petroleum, synthetic and biological origin", the secretariat of which is held by NEN.

Introduction

During its 8th meeting held in London on 25 - 26 October 2000, CEN/TC 19/WG 27 "Elemental analysis of petroleum and related products" decided to carry out a second round robin, after the first performed in 1998 - 1999, to define the precision of new test methods in the range 1 mg/kg to 60 mg/kg sulfur. The range of sulfur content was selected to obtain definite and robust precision statements for future sulfur limits. The round robin was carried out in 2001.

The work has formed the basis for sulfur test method standards produced by the following organizations:

- ISO/TC 28 "Petroleum products", and
- CEN/TC 19 "Petroleum products, lubricants and related products".

1 Scope

This Technical Report summarises the activity carried out by CEN/TC 19 to define the precision of new test methods for the determination of low sulfur content in automotive fuels. The full description of the activity can be found in the Working Group Report completed in August 2002, which is an internal CEN/TC 19 document.

2 Test methods

WG 27 identified the most suitable instrumental methods to include in the round robin, also according to the experience gained in the round robin carried out in 1999. The methods available at that time and used in the assessment are listed below (see also Clause 12).

- EN ISO 14596 WDXRF (with internal standard) [1];
- ISO/CD 20846 UVF [2];
- ISO/CD 20847 EDXRF [3];
- ISO/CD 20884 WDXRF (without internal standard) [4];
- prEN ISO/DIS 16591 Oxidative microcoulometry [5].

3 Samples

Eight petrol and ten diesel samples with sulfur content from 1 mg/kg to 55 mg/kg were included in the round robin. Two samples were blends of FAME in diesel (5 % (V/V) FAME) and were included in the round robin to examine the applicability of the methods to FAME blends according to EN 590 specification [6].

Two samples (one petrol and one diesel) were considered as "quality control" samples, to check for accuracy of results, as sulfur content had been determined using Isotope Dilution Mass Spectrometry (ID-MS), the technique employed for the certification of element content in reference materials.

4 Laboratories

European laboratories were contacted to obtain a satisfactory participation for the methods listed above. A total of 102 applications from 11 countries were received. Table 1 shows the distribution of the techniques employed by the laboratories that effectively participated in the round robin.

Table 1 — Final list of participants

	WDXRF a		EDXRF		UVF	Microcoulometry			
	High Power	Lower Power	Polarised	Non-polarised					
Laboratories	40	15	6	17	39	20			
a High power instruments ≥ 3kW, lower power instruments ≤ 1 kW.									

5 Evaluation of round robin results

The results received by the participants were firstly examined by the project leaders of each method for possible non compliance to the test methods (analytical outliers). The experts looked at the technical issues on the basis of the information submitted by the participants. They did not make judgement on the basis of the values submitted or on a statistical basis.

6 Statistical analysis

The statistical process used for the examination of the round robin was the methodology indicated in EN ISO 4259 [7]. Only linear models were chosen for the evaluation of repeatability and reproducibility. Global precision for all fuel samples or specific precision for each fuel was calculated according to the provisions already given in the precision clauses of the methods.

The following results were obtained (X is the mean of two results expressed in mg/kg):

EN ISO 14596 [1]:

All fuels (high power) r = 0.039 9-X + 1.59 R = 0.067 2-X + 2.69

All fuels (lower power) $r = 0.026 9 \cdot X + 2.69$ $R = 0.042 7 \cdot X + 4.27$

ISO/CD 20846 [2]:

Petrol $r = 0.063 \text{ 1} \cdot \text{X} + 0.35$ $R = 0.174 \text{ 9} \cdot \text{X} + 0.96$

Diesel $r = 0.055 \ 3.X + 0.55$ $R = 0.112 \ 0.X + 1.12$

ISO/CD 20847 [3]:

Petrol $r = 0.031 2 \cdot X + 9$ $R = 0.111 6 \cdot X + 11$

Diesel r = 0.018 8.X + 8 R = 0.016 9.X + 12

The precision data of ISO/CD 20847 were obtained by combining the results of the first and second round robin, to cover the complete sulfur range for the scope of the method.

ISO/CD 20884 [4]:

All fuels (high power) r = 0.024 8-X + 1.7 R = 0.120 1-X + 1.9

All fuels (lower power) r = 0.040 8-X + 2.0 R = 0.088 9-X + 4.5

prEN ISO/DIS 16591 [5]:

All fuels $r = 0.045 \text{ 6} \cdot \text{X} + 1.14$ $R = 0.101 \text{ 8} \cdot \text{X} + 2.55$

7 Comparison between methods and accuracy

The comparison, using EN ISO 14596 as the reference method, showed statistically significant differences between the methods, but these differences were certainly very small and could be ignored from a practical point of view.

The accuracy of the methods was verified using the "quality control samples". The results obtained for each test method for these samples were within the limits of the repeatability.

8 Applicability to FAME blends

The maximum difference observed between the sulfur content of the pure diesel fuel and that of the corresponding 5% (V/V) FAME blends was in any case lower than the repeatability of each method.

9 Conclusions

- **9.1** EN ISO 14596: The precision found in the round robin for both high and lower power systems was better than that stated in the method, that refers to high power systems only.
- **9.2** ISO/CD 20846: The precision was better for diesel fuel than for petrol, as observed for other methods. The test method was found suitable for the determination of sulfur content \geq 3 mg/kg (according to 2R rule of EN ISO 4259).
- **9.3** ISO/CD 20847: A substantial improvement was achieved with ISO/CD 20847 compared to EN ISO 8754 [8], and also compared to the results obtained in the 1998-1999 round robin. The current precision showed that the method is suitable for sulfur contents down to around 30 mg/kg. The results indicated that a new generation of EDXRF instruments (polarised source) has the potential to be used at lower sulfur content (< 10 mg/kg).
- **9.4** ISO/CD 20884: The results confirmed the precision stated in the method for low sulfur content, and showed that the new method is suitable for the determination of sulfur content ≥ 5 mg/kg (according to 2R rule of EN ISO 4259), when using high power instruments. On the other hand, the results showed that lower power instrumentation might not achieve adequate precision for sulfur contents of 10 mg/kg and below.
- 9.5 prEN ISO/DIS 16591: The precision found is quite close that stated in current ISO/CD 16591.

10 Recommendations for updating EN 228 and EN 590

According to the results obtained in the round robin, WG 27 recommended the following actions for the 2004 versions of the European specifications on petrol (EN 228 [9]) and diesel (EN 590 [6]):

- EN ISO 14596 to be replaced by ISO/DIS 20884. The new method does not require the addition of the internal standard and shows satisfactory precision at 50 mg/kg and 10 mg/kg;
- EN 24260 [10] to be replaced by ISO/DIS 20846. UVF method, also based on sample combustion, shows satisfactory precision at 50 mg/kg and 10 mg/kg;
- EN ISO 8754 to be replaced by ISO/DIS 20847. EN ISO 8754 cannot be used at 350 mg/kg and 150 mg/kg (2R rule of EN ISO 4259 is not fulfilled), while ISO/DIS 20847 can determine down to 30 mg/kg sulfur.

11 Test method publication

The new precision statements of ISO/CD 20846, ISO/CD 20847 and ISO/CD 20884 were incorporated in the test methods, and the revised versions were forwarded to ISO TC/28 for ballot as ISO/DIS.

The three test methods developed by WG 27 were published by ISO and CEN in March 2004 [2 - 4], without technical changes from the prEN ISO/DIS text that could have impacted the precision, nor the conclusions as indicated in this document.

Acknowledgements

CEN/TC 19 acknowledges the following people and organizations for their contribution to this guide:

- a) P. Tittarelli, Stazione Sperimentali Combustibili, Italy, as author of this guide,
- b) C. Do Marco, Total France, as project leader for the UV Fluorescence method,
- c) R. Hensel, Shell Deutschland, project leader for the Wavelength Dispersive XRF method,
- d) J. Crighton, BP UK, project leader for the Energy Dispersive XRF method,
- e) H. Read, BP UK, project leader of the actual interlaboratory study and former WG convenor, and
- f) the CEN/TC 19/WG 27 "Elemental analysis of petroleum and related products" experts, for guidance and assistance.

Bibliography

- [1] EN ISO 14596:1998, Petroleum products Determination of sulfur content Wavelength dispersive X-ray fluorescence spectrometry (ISO 14596:1998, incl. Cor. 1:1999)
- [2] EN ISO 20846:2004, Petroleum products Determination of sulfur content of automotive fuels Ultraviolet fluorescence method (ISO 20846:2004)
- [3] EN ISO 20847:2004, Petroleum products Determination of sulfur content of automotive fuels Energy-dispersive X-ray fluorescence spectrometry (ISO 20847:2004)
- [4] EN ISO 20884:2004 Petroleum products Determination of sulfur content of automotive fuels Wavelength-dispersive X-ray fluorescence spectrometry (ISO 20884:2004)
- [5] prEN ISO 16591:2000, Petroleum products Determination of the sulfur content Oxidative microcoulometry method (ISO/DIS 16591:2000)
- [6] EN 590:2004, Automotive fuels Diesel Requirements and test methods
- [7] EN ISO 4259, Petroleum products Determination and application of precision data in relation to methods of test (ISO 4259:1992, including Cor. 1: 1993)
- [8] EN ISO 8754:1995, Petroleum products Determination of sulfur content Energy-dispersive X-ray fluorescence spectrometry (ISO 8754:1995)¹⁾
- [9] EN 228:2004, Automotive fuels Unleaded petrol Requirements and test methods
- [10] EN 24260:1994, Petroleum products and hydrocarbons Determination of sulfur content Wickbold combustion method (ISO 4260:1987)

¹⁾ Meanwhile replaced by EN ISO 8754:2003.

icensed copy: Lee Shau Kee Library, HKUST, Version correct as of 03/01/2015, (c) The British Standards Institution 2013

BSI — British Standards Institution

BSI is the independent national body responsible for preparing British Standards. It presents the UK view on standards in Europe and at the international level. It is incorporated by Royal Charter.

Revisions

British Standards are updated by amendment or revision. Users of British Standards should make sure that they possess the latest amendments or editions.

It is the constant aim of BSI to improve the quality of our products and services. We would be grateful if anyone finding an inaccuracy or ambiguity while using this British Standard would inform the Secretary of the technical committee responsible, the identity of which can be found on the inside front cover. Tel: +44 (0)20 8996 9000. Fax: +44 (0)20 8996 7400.

BSI offers members an individual updating service called PLUS which ensures that subscribers automatically receive the latest editions of standards.

Buying standards

Orders for all BSI, international and foreign standards publications should be addressed to Customer Services. Tel: +44 (0)20 8996 9001. Fax: +44 (0)20 8996 7001. Email: orders@bsi-global.com. Standards are also available from the BSI website at http://www.bsi-global.com.

In response to orders for international standards, it is BSI policy to supply the BSI implementation of those that have been published as British Standards, unless otherwise requested.

Information on standards

BSI provides a wide range of information on national, European and international standards through its Library and its Technical Help to Exporters Service. Various BSI electronic information services are also available which give details on all its products and services. Contact the Information Centre. Tel: +44 (0)20 8996 7111. Fax: +44 (0)20 8996 7048. Email: info@bsi-global.com.

Subscribing members of BSI are kept up to date with standards developments and receive substantial discounts on the purchase price of standards. For details of these and other benefits contact Membership Administration.

Tel: +44 (0)20 8996 7002. Fax: +44 (0)20 8996 7001.

Email: membership@bsi-global.com.

Information regarding online access to British Standards via British Standards Online can be found at http://www.bsi-global.com/bsonline.

Further information about BSI is available on the BSI website at http://www.bsi-global.com.

Copyright

Copyright subsists in all BSI publications. BSI also holds the copyright, in the UK, of the publications of the international standardization bodies. Except as permitted under the Copyright, Designs and Patents Act 1988 no extract may be reproduced, stored in a retrieval system or transmitted in any form or by any means—electronic, photocopying, recording or otherwise—without prior written permission from BSI.

This does not preclude the free use, in the course of implementing the standard, of necessary details such as symbols, and size, type or grade designations. If these details are to be used for any other purpose than implementation then the prior written permission of BSI must be obtained.

Details and advice can be obtained from the Copyright & Licensing Manager. Tel: +44 (0)20 8996 7070. Fax: +44 (0)20 8996 7553. Email: copyright@bsi-global.com.

BSI 389 Chiswick High Road London

W4 4AL