

PD IEC/TR 62617:2015



BSI Standards Publication

# Home laundry appliances — Uncertainty reporting of measurements

**bsi.**

...making excellence a habit.™

### **National foreword**

This Published Document is the UK implementation of IEC/TR 62617:2015.

The UK participation in its preparation was entrusted by Technical Committee CPL/59, Performance of household electrical appliances, to Subcommittee CPL/59/1, Dishwashers and washing machines.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2016.

Published by BSI Standards Limited 2016

ISBN 978 0 580 91372 3

ICS 97.060

**Compliance with a British Standard cannot confer immunity from legal obligations.**

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 31 January 2016.

### **Amendments/corrigenda issued since publication**

<b>Date</b>	<b>Text affected</b>
-------------	----------------------

---



# TECHNICAL REPORT

---

## Home laundry appliances – Uncertainty reporting of measurements

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

---

ICS 97.060

ISBN 978-2-8322-3033-6

**Warning! Make sure that you obtained this publication from an authorized distributor.**

## CONTENTS

FOREWORD .....	3
INTRODUCTION .....	5
1 Scope .....	6
2 Normative references .....	6
3 Terms and definitions .....	6
4 The approach to uncertainty measurement .....	7
4.1 The importance of the uncertainty .....	7
4.2 Ways to access uncertainty .....	7
5 Expanded uncertainty calculation .....	8
6 Absolute and relative reproducibility standard deviation .....	8
7 Reporting uncertainty .....	9
8 Expanded uncertainty values .....	10
8.1 General .....	10
8.2 Expanded uncertainty of measurement in IEC 60456:2003 (4 <sup>th</sup> edition) .....	10
8.3 Expanded uncertainty of measurement in IEC 60456:2010 (5 <sup>th</sup> edition) .....	10
8.4 Expanded uncertainty of measurement in IEC 61121:2002 (3 <sup>rd</sup> edition) .....	11
8.5 Expanded uncertainty of measurement in IEC 62512:2012 (1 <sup>st</sup> edition) .....	11
Bibliography .....	14
Table 1 – Expanded uncertainty of measured values of IEC 60456:2003 (4 <sup>th</sup> edition) for horizontal drum washing machine .....	10
Table 2 – Expanded uncertainty of measured values of IEC 60456:2010 (5 <sup>th</sup> edition) for horizontal axis washing machines .....	11
Table 3 – Expanded uncertainty of measured values of IEC 61121:2002 (3 <sup>rd</sup> edition) for condenser tumble dryers .....	11
Table 4 – Expanded uncertainty of measured values of IEC 62512:2012 (1 <sup>st</sup> edition) for horizontal-axis washer-dryer .....	12
Table 5 – Expanded uncertainty of measured values of IEC 62512:2012 (1 <sup>st</sup> edition) for vertical-axis washer-dryer without heater .....	13

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

**HOME LAUNDRY APPLIANCES –  
UNCERTAINTY REPORTING OF MEASUREMENTS**

## FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEC technical committees is to prepare International Standards. However, a technical committee may propose the publication of a technical report when it has collected data of a different kind from that which is normally published as an International Standard, for example "state of the art".

IEC 62617, which is a Technical Report, has been prepared by subcommittee 59D: Performance of household and similar electrical laundry appliances, of IEC technical committee 59: Performance of household and similar electrical appliances.

This second edition cancels and replaces the first edition published in 2010. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- alternative expression of expanded uncertainties in absolute values;
- expanded uncertainty for horizontal drum washing machines according to IEC 60456:2010;

- expanded uncertainties for washer-dryer according to IEC 62512:2012
- clarifications of the examples of expanded uncertainty calculation.

The text of this technical report is based on the following documents:

Enquiry draft	Report on voting
59D/430/DTR	59D/432/RVC

Full information on the voting for the approval of this technical report can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

Words in **bold** in the text are specifically defined in Clause 3.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

## INTRODUCTION

To encourage the efficient use of energy and other resources, National governments and regional authorities have issued regulations, which mandate the provision of information to consumers regarding the energy and water consumption of household appliances and associated performance characteristics. This information is usually conveyed by labels attached to appliances at the point of sale and also by brochures provided by manufacturers.

Methods for measuring declared values for energy and water consumption and performance characteristics should be of sufficient accuracy to provide confidence to governments, consumers and manufacturers. The accuracy of a test method is expressed in terms of bias and precision. Precision, when evaluating test methods, is expressed in terms of two measurement concepts: repeatability and reproducibility. Therefore, standard procedures should be used for determining the repeatability and the reproducibility of test methods developed by technical committee 59 and its subcommittees. The repeatability of a test method should be sufficiently accurate for comparative testing. The reproducibility of a test method should be sufficiently accurate for the determination of values which are declared and for checking these declared values.

Uncertainty reporting is essential to ensure measured data are interpreted in a correct way. Especially when data of measurements are compared between laboratories or when normative requirements are set up, it is necessary to know the uncertainty with which data can be measured.

# HOME LAUNDRY APPLIANCES – UNCERTAINTY REPORTING OF MEASUREMENTS

## 1 Scope

This Technical Report (TR) applies to uncertainty reporting of measurements of home laundry electrical appliances.

It allows to estimate the uncertainty of a measured result and to predict the range of values that may be measured when the same appliance is measured in another laboratory following the same measurement method.

NOTE The provisions in this TR can also be used to evaluate other kinds of products.

## 2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC TR 61923:1997, *Household electrical appliances – Method of measuring performance – Assessment of repeatability and reproducibility*

ISO/IEC Guide 98-3:2008, *Uncertainty of measurement – Part 3: Guide to the expression of uncertainty in measurement (GUM:1995)*

## 3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

### 3.1

#### **repeatability conditions**

conditions where independent test results are obtained with the same method on identical test items in the same laboratory by the same operator using the same equipment within short intervals of time

[SOURCE: IEC TR 61923:1997, 3.6]

### 3.2

#### **repeatability standard deviation**

standard deviation of test results obtained under **repeatability conditions**

[SOURCE: IEC TR 61923:1997, 3.7]

### 3.3

#### **reproducibility conditions**

conditions where test results are obtained with the same method on identical test items in different laboratories with different operators using different equipment

[SOURCE: IEC TR 61923:1997, 3.9]



### 3.4

#### **reproducibility standard deviation**

standard deviation of test results obtained under **reproducibility conditions**

[SOURCE: IEC TR 61923:1997, 3.10]

### 3.5

#### **statistical uncertainty**

**repeatability standard deviation** obtained in one laboratory under **repeatability conditions**

### 3.6

#### **expanded uncertainty**

confidence interval, which allows to calculate the minimum and maximum value where the average measured result may be found when the measurement is re-done at any other laboratory following **reproducibility conditions**

## 4 The approach to uncertainty measurement

### 4.1 The importance of the uncertainty

When a measurement has been performed giving a figure as a result for some quantity (i.e. the measurand), how sure is this figure? In other words:

- if the measurement is repeated, will the same figure be achieved as the result?
- if another group or another laboratory performs the measurement, how close will the results expected to be?

By means of an uncertainty amount an uncertainty interval  $y \pm U$  may be calculated, where  $y$  is the measurement result and  $U$  the **expanded uncertainty** that is determined to give the interval a high probability (often 95%) to cover the true value,  $y$ , of the measurand.  $U$  is said to be the uncertainty associated with the result  $y$ .

The uncertainty interval of a measurement is therefore a basis for qualifying the measurement. The more narrow the confidence interval is desired, i.e. the smaller the value of the uncertainty  $U$  is pursued, the more careful the measurement method, the measuring equipment, the training of the operators and the number of repetitions of the same experiment have to be.

### 4.2 Ways to access uncertainty

There are in principle two ways to estimate uncertainty: a bottom up method and a top down method. The two methods should often be used in parallel to achieve a reliable uncertainty amount.

#### a) The bottom up method (refer to ISO/IEC Guide 98-3:2008, Clause 2)

In this method the test result  $y$  is expressed as a function of input quantities. This function is often the formula used for the calculation of the result.

In the case of home laundry appliances,  $y$  may be one of the final test results like water consumption, energy consumption, washing performance, spin speed, spin drying performance, program duration or rinsing efficiency. The input quantities may be temperature, masses, times, power etc.

The magnitude of all the uncertainty contributions of each input quantity is estimated.

By combining the uncertainties of the input quantities according to the law of propagation of uncertainty (see ISO/IEC Guide 98-3:2008, Clause 2) the uncertainty of the result  $y$  can be calculated.

With this calculation it can be seen how a specific uncertainty contribution from an input quantity does influence the combined uncertainty of the final result and therefore how a

reduction in an uncertainty contribution from an input quantity will influence the combined uncertainty of the final result.

Uncertainties may usually be reduced at some cost by making more measurements, using other methods or other equipment. This means that different approaches can be followed to reduce the uncertainty of the final result in the most cost effective way.

b) The top down method (see IEC TR 61923)

In this method the **reproducibility standard deviation** is estimated from testing of the same machine (or the same model) in different laboratories using the same measurement method. This testing is in general named 'ring test' or 'round robin test'. The **reproducibility standard deviation** of the test results can then be seen as the inherent uncertainty of the measuring method as it may be influenced by remaining differences in the ambient, the people and whatever else may be different between different measurements in different laboratories. In principle it is only valid for the machine investigated in each ring test, but results may be also true for similar type of machines.

Therefore the two methods 'bottom up' and 'top down' may be used in parallel to achieve a reliable uncertainty quantification. But both methods depend on the validity of the model (for the bottom up method) or the data (for the top down method) used.

## 5 Expanded uncertainty calculation

The uncertainty of a measured result has two sources:

- the **statistical uncertainty** of what is measured, as expressed in the **repeatability standard deviation**, showing the accuracy of the measurement in the laboratory having done the measurement;
- the uncertainty of the measuring method itself. This is expressed as **expanded uncertainty** where it is common to set the borders at a 95 % confidence interval, which give the minimum and maximum value where the average measured result may be found when the measurement is re-done at any other laboratory.

To be meaningful, the uncertainty statement shall have an associated confidence level, i.e. it is necessary to state the probability that the true value lies within the range given. The reasons for choosing a 95 % confidence level in this document are as follows:

- it is established practice throughout much of Europe, North America and Asia;
- the ISO/IEC Guide 98-3 (GUM) assumes that the combined uncertainty has a distribution that is a close approximation to a normal distribution. A 95 % confidence level approximates to a range of 2 standard deviations. It is a widely held view that, for most measurement systems, the approximation to a normal distribution for the distribution of the combined uncertainty is reliable up to 2 standard deviations, but beyond that the approximation is less reliable.

If a normal distribution may be assumed the 95 % confidence interval is given by multiplying the **reproducibility standard deviation** by a factor of 2.

## 6 Absolute and relative reproducibility standard deviation

Whatever methodology is used to calculate the **reproducibility standard deviation** it is then the responsibility of experts within the relevant standardisation committee to conclude which **reproducibility standard deviation** is the most realistic expression of the uncertainty for a certain product group.

Different values may be communicated for different product groups within the same product category, if necessary and justified. The decisions and the rationale have to be reported.

The **reproducibility standard deviation** can be a value of absolute or relative nature. Depending on the nature of the error either one or the other shall be preferred:

- absolute values of the **reproducibility standard deviation** shall be preferred when the measurement error is not likely to be influenced by the absolute value of the measurand.
- relative values are preferred when the error will grow or diminish with the absolute magnitude of the measurand.

It is the responsibility of the relevant standardisation committee to conclude in which way the **reproducibility standard deviation** shall be expressed. If expressed in absolute values, the **reproducibility standard deviation** shall be given with the term '(abs)', otherwise in '%'.

## 7 Reporting uncertainty

When reporting test results all information should be given to allow a full judgement of the measurement: average measured value, **repeatability standard deviation** and **expanded uncertainty**.

Example for a repeatability standard deviation of 0,03 kWh and relative expanded uncertainty of 10 %:

- measurement of the energy consumption
 

Average measured:	1,44 kWh
<b>Repeatability standard deviation</b> of measurement:	0,03 kWh
<b>Expanded uncertainty:</b> 10% (of 1,44 kWh = )	0,14 kWh
- reporting of the result
 

Average measured:	1,44 kWh
<b>Repeatability standard deviation:</b>	±0,03 kWh
<b>Expanded uncertainty:</b>	±0,14 kWh
- meaning: testing the same machine in another laboratory following **reproducibility conditions**, the expected average value (at 95 % confidence) is between 1,30 kWh and 1,58 kWh.

Example for a repeatability standard deviation of 0,03 kWh and absolute expanded uncertainty of 0,10 kWh (abs):

- measurement of the energy consumption
 

Average measured:	1,44 kWh
<b>Repeatability standard deviation</b> of measurement:	0,03 kWh
<b>Expanded uncertainty:</b> 0,10 kWh (abs)	0,10 kWh
- reporting of the result
 

Average measured:	1,44 kWh
<b>Repeatability standard deviation:</b>	±0,03 kWh
<b>Expanded uncertainty:</b>	±0,10 kWh
- meaning: testing the same machine in another laboratory following **reproducibility conditions**, the expected average value (at 95 % confidence) is between 1,34 kWh and 1,54 kWh.

## 8 Expanded uncertainty values

### 8.1 General

**Expanded uncertainty** values reported in 8.2 to 8.5 define the level of **expanded uncertainty** as estimated from the results of performed round robin tests. They are only valid for the assessed machine types. Other machine types may behave differently, also affecting the uncertainty values.

Laboratories shall ensure that they meet the requirements of the relevant measurement method and the **reproducibility conditions** of testing and should check their alignment with other laboratories participating in inter-laboratory testing.

The uncertainty figures are established on the basis of the evaluation of round robin tests. Uncertainty figures of different parameters may be based on different round robin tests and will be updated whenever necessary. The respective sources are referred to with the data.

### 8.2 Expanded uncertainty of measurement in IEC 60456:2003 (4<sup>th</sup> edition)

In 2004-2005, a round robin test was performed with 25 laboratories participating from all over Europe. One of the objectives was to check the robustness and precision of IEC 60456:2003 (4<sup>th</sup> edition). Four washing machines, 2 horizontal drum washing machines and 2 reference machines, were tested in a total of eleven different washing cycles. Household washing machines under test were calibrated to be as identical to each other as possible and delivered to all participating laboratories.

Results were analysed by SC59D and **expanded uncertainties**, rounded to integer, were calculated, as shown in Table 1.

**Table 1 – Expanded uncertainty of measured values of IEC 60456:2003 (4<sup>th</sup> edition) for horizontal drum washing machine**

Measured parameter	Relative expanded uncertainty of measured value ( $k=2$ )
Wash performance ratio $q$	4 %
Total energy $W_{\text{total}}$ (in kWh)	10 %
Total water $V_{\text{total}}$ (in L)	5 %
Remaining moisture $RM$ (in %)	5 %
Programme time (in min)	6 %

### 8.3 Expanded uncertainty of measurement in IEC 60456:2010 (5<sup>th</sup> edition)

In 2008, a round robin test was performed with 31 laboratories participating from all over the world. One of the objectives was to check the robustness and precision of IEC 60456:2010 (5<sup>th</sup> edition). Six types of washing machines, 2 horizontal-axis, 2 vertical-axis (agitator type), 2 vertical-axis (impeller type) machines, plus reference machines were tested in four different washing cycles. Household washing machines under test were calibrated to be as identical to each other as possible and delivered to all participating laboratories.

Results were analysed by SC59D and **expanded uncertainties**, rounded to integer, were calculated for horizontal-axis washing machines only, as shown in Table 2.

**Table 2 – Expanded uncertainty of measured values of IEC 60456:2010 (5<sup>th</sup> edition) for horizontal axis washing machines**

Measured parameter	Expanded uncertainty of measured value ( $k=2$ )
Wash performance ratio $q$	0,04 (abs)
Total energy $W_{\text{total}}$ (in kWh)	9 %
Total water $V_{\text{total}}$ (in l)	4 %
Remaining moisture $RM$ (in %)	5 (abs)
Programme time (in min)	5 (abs)
Rinsing performance	0,70 (abs)

#### 8.4 Expanded uncertainty of measurement in IEC 61121:2002 (3<sup>rd</sup> edition)

In 2006, a round-robin test was organised in Europe including 19 laboratories. Three condensation dryers, checked before to behave equal, were sent around and were measured in regular cupboard dry and iron dry programme according to IEC 61121:2002 (3<sup>rd</sup> edition).

Analysis of the data shows no influence of the individual dryer, therefore the 19 laboratories could be considered a set of laboratories fulfilling the requirements of IEC TR 61923:1997, 5.2.

Results were analysed by SC59D, and **expanded uncertainties**, rounded to integer, were calculated as shown in Table 3.

**Table 3 – Expanded uncertainty of measured values of IEC 61121:2002 (3<sup>rd</sup> edition) for condenser tumble dryers**

Measured parameter	Relative expanded uncertainty of measured value ( $k=2$ )
Corrected energy consumption $E$ (in kWh)	4 %
Corrected programme time $t$ (in min)	8 %
Condensation efficiency $C$ (in %)	10 %

#### 8.5 Expanded uncertainty of measurement in IEC 62512:2012 (1<sup>st</sup> edition)

A round-robin test was organised in 2013-2014 in Asian countries including 9 laboratories. Three washer-dryers, two with horizontal axis and one with vertical axis without heater, were tested in two programs according to IEC 62512:2012(1<sup>st</sup> edition)

Results were analysed by SC59D and **expanded uncertainties** were derived as shown in Tables 4 and 5.

**Table 4 – Expanded uncertainty of measured values of IEC 62512:2012 (1<sup>st</sup> edition) for horizontal-axis washer-dryer**

Measured parameter	Relative expanded uncertainty of measured value ( $k=2$ )
Wash performance ratio $q$	0,04 (abs)
(Corrected) energy consumption (in kWh): Washing $E_w$ in interrupted operation cycles	9 %
(Corrected) energy consumption (in kWh): Drying $E_d$ in interrupted operation cycles	10 %
(Corrected) energy consumption (in kWh): Washing and drying $E_{wD}$ in continuous operation cycles	10 %
(Corrected) water consumption (in L): Washing $L_w$ in interrupted operation cycles	4 %
(Corrected) water consumption (in L): Drying $L_d$ in interrupted operation cycles	>20 L: 20 % ≤20 L: 4 L (abs)
(Corrected) water consumption (in L): Washing and drying $L_{wD}$ in continuous operation cycles	>60 L: 10 % ≤60 L: 6 L (abs)
(Corrected) program duration (in min): Washing $t_w$ in interrupted operation cycles	5 min (abs)
(Corrected) program duration (in min): Drying $t_d$ in interrupted operation cycles	15 %
(Corrected) program duration (in min): Washing and drying $t_{wd}$ in continuous operation cycles	15 %
Final moisture content $\mu_f$ (in %)	5 % (abs)
Rinsing performance	Not applicable

**Table 5 – Expanded uncertainty of measured values of  
IEC 62512:2012 (1<sup>st</sup> edition) for vertical-axis washer-dryer without heater**

Measured parameter	Relative expanded uncertainty of measured value ( $k=2$ )
Wash performance ratio $q$	0,06 (abs)
(Corrected) energy consumption (in kWh): Washing $E_w$ in interrupted operation cycles	0,06 (abs)
(Corrected) energy consumption (in kWh): Drying $E_d$ in interrupted operation cycles	10%
(Corrected) energy consumption (in kWh): Washing and drying $E_{wD}$ in continuous operation cycles	10%
(Corrected) water consumption (in L): Washing $L_w$ in interrupted operation cycles	5%
(Corrected) water consumption (in L): Drying $L_d$ in interrupted operation cycles	>20 L: 20% ≤20 L: 4 L (abs)
(Corrected) water consumption (in L): Washing and drying $L_{wD}$ in continuous operation cycles	>60 L: 10% ≤60 L: 6 L (abs)
(Corrected) program duration (in min): Washing $t_w$ in interrupted operation cycles	5 min (abs)
(Corrected) program duration (in min): Drying $t_d$ in interrupted operation cycles	15 %
(Corrected) program duration (in min): Washing and drying $t_{wD}$ in continuous operation cycles	15 %
Final moisture content $\mu_f$ (in %)	7 % (abs)
Rinsing performance	Not applicable

## Bibliography

IEC 60456:2010, *Clothes washing machines for household use – Methods for measuring the performance*

IEC 61121:2002, *Tumble dryers for household use – Methods for measuring the performance*<sup>1</sup>

IEC 62512:2012, *Electric clothes washer-dryers for household use – Methods for measuring the performance*

IEC Guide 115, *Application of uncertainty of measurement to conformity assessment activities in the electrotechnical sector*

ISO/IEC 17025:2005, *General requirements for the competence of testing and calibration laboratories*

ISO 5725 (all parts), *Accuracy (trueness and precision) of measurement methods and results*

---

<sup>1</sup> This is the third edition of IEC 61121. A fourth edition of IEC 61121 was published in 2012.





# British Standards Institution (BSI)

BSI is the national body responsible for preparing British Standards and other standards-related publications, information and services.

BSI is incorporated by Royal Charter. British Standards and other standardization products are published by BSI Standards Limited.

## About us

We bring together business, industry, government, consumers, innovators and others to shape their combined experience and expertise into standards-based solutions.

The knowledge embodied in our standards has been carefully assembled in a dependable format and refined through our open consultation process. Organizations of all sizes and across all sectors choose standards to help them achieve their goals.

## Information on standards

We can provide you with the knowledge that your organization needs to succeed. Find out more about British Standards by visiting our website at [bsigroup.com/standards](http://bsigroup.com/standards) or contacting our Customer Services team or Knowledge Centre.

## Buying standards

You can buy and download PDF versions of BSI publications, including British and adopted European and international standards, through our website at [bsigroup.com/shop](http://bsigroup.com/shop), where hard copies can also be purchased.

If you need international and foreign standards from other Standards Development Organizations, hard copies can be ordered from our Customer Services team.

## Subscriptions

Our range of subscription services are designed to make using standards easier for you. For further information on our subscription products go to [bsigroup.com/subscriptions](http://bsigroup.com/subscriptions).

With **British Standards Online (BSOL)** you'll have instant access to over 55,000 British and adopted European and international standards from your desktop. It's available 24/7 and is refreshed daily so you'll always be up to date.

You can keep in touch with standards developments and receive substantial discounts on the purchase price of standards, both in single copy and subscription format, by becoming a **BSI Subscribing Member**.

**PLUS** is an updating service exclusive to BSI Subscribing Members. You will automatically receive the latest hard copy of your standards when they're revised or replaced.

To find out more about becoming a BSI Subscribing Member and the benefits of membership, please visit [bsigroup.com/shop](http://bsigroup.com/shop).

With a **Multi-User Network Licence (MUNL)** you are able to host standards publications on your intranet. Licences can cover as few or as many users as you wish. With updates supplied as soon as they're available, you can be sure your documentation is current. For further information, email [bsmusales@bsigroup.com](mailto:bsmusales@bsigroup.com).

## Revisions

Our British Standards and other publications are updated by amendment or revision.

We continually improve the quality of our products and services to benefit your business. If you find an inaccuracy or ambiguity within a British Standard or other BSI publication please inform the Knowledge Centre.

## Copyright

All the data, software and documentation set out in all British Standards and other BSI publications are the property of and copyrighted by BSI, or some person or entity that owns copyright in the information used (such as the international standardization bodies) and has formally licensed such information to BSI for commercial publication and use. Except as permitted under the Copyright, Designs and Patents Act 1988 no extract may be reproduced, stored in a retrieval system or transmitted in any form or by any means – electronic, photocopying, recording or otherwise – without prior written permission from BSI. Details and advice can be obtained from the Copyright & Licensing Department.

## Useful Contacts:

### Customer Services

**Tel:** +44 845 086 9001

**Email (orders):** [orders@bsigroup.com](mailto:orders@bsigroup.com)

**Email (enquiries):** [cservices@bsigroup.com](mailto:cservices@bsigroup.com)

### Subscriptions

**Tel:** +44 845 086 9001

**Email:** [subscriptions@bsigroup.com](mailto:subscriptions@bsigroup.com)

### Knowledge Centre

**Tel:** +44 20 8996 7004

**Email:** [knowledgecentre@bsigroup.com](mailto:knowledgecentre@bsigroup.com)

### Copyright & Licensing

**Tel:** +44 20 8996 7070

**Email:** [copyright@bsigroup.com](mailto:copyright@bsigroup.com)

## BSI Group Headquarters

389 Chiswick High Road London W4 4AL UK

