PD ISO/TR 16377:2012



BSI Standards Publication

Further clarification of ISO 28580



National foreword

This Published Document is the UK implementation of ISO/TR 16377:2012.

The UK participation in its preparation was entrusted to Technical Committee AUE/4, Tyres and wheels for motor vehicles.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2012

Published by BSI Standards Limited 2012

ISBN 978 0 580 71450 4

ICS 83.160.01

Compliance with a British Standard cannot confer immunity from legal obligations.

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 31 August 2012.

Amendments issued since publication

Amd. No. Date Text affected

TECHNICAL REPORT

ISO/TR 16377

First edition 2012-07-15

Further clarification of ISO 28580

Précisions concernant l'ISO 28580



PD ISO/TR 16377:2012 **ISO/TR 16377:2012(E)**



COPYRIGHT PROTECTED DOCUMENT

© ISO 2012

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Coi	ntents	Page
	word	
Intro	Introduction	
1	Scope	1
2	General	1
3 3.1 3.2	Clause 3, Terms and definitions Additional definition: candidate machine Definition 3.13: deviation of alignment tyre	1
4 4.1 4.2	Clause 6, Test conditions Subclause 6.2, Table 1, and subclause 6.4, Table 2 Subclause 6.4, Table 2	1
5 5.1 5.2 5.3	Clause 7, Test procedure Subclause 7.4, Table 3 Subclause 7.6.2, Note 1 Subclause 7.6.3, list item a)	2 2
6	Subclause 8.1, Determination of parasitic loss	2
7	Subclause 10.2, Conditions for reference machine, and subclause 10.3, Conditions for candidate machine	3

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

In exceptional circumstances, when a technical committee has collected data of a different kind from that which is normally published as an International Standard ("state of the art", for example), it may decide by a simple majority vote of its participating members to publish a Technical Report. A Technical Report is entirely informative in nature and does not have to be reviewed until the data it provides are considered to be no longer valid or useful.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO/TR 16377 was prepared by Technical Committee ISO/TC 31, Tyres, rims and valves.

Introduction

ISO 28580, Passenger car, truck and bus tyres — Methods of measuring rolling resistance — Single point test and correlation of measurement results, was published in 2009. During the approval process, several suggestions were made for clarification which were supported by ISO/TC 31/WG 6 and are included in this Technical Report.

Further clarification of ISO 28580

1 Scope

This Technical Report seeks to document elements of clarification to ISO 28580:2009 where consensus exists. Other suggestions for clarification will demand further work and consensus building and are not included in this Technical Report. Although it is expected that these clarifications will be adopted in future revisions to ISO 28580, they are intended only as guidance for the user.

2 General

The meaning of terms "larger truck and bus tyres" and "smaller truck and bus tyres" is not clear. It is proposed that the terms "larger" and "smaller", as used in these phrases, be removed, and that the Load Index (LI) reference be used to distinguish these tyre sizes, so that smaller truck and bus tyres are those with LI \leq 121 and larger truck and bus tyres are those with LI > 121.

3 Clause 3, Terms and definitions

3.1 Additional definition: candidate machine

A term and definition should be added as follows:

candidate machine

machine intended to measure new test tyres, with alignment to a reference machine, in accordance with ISO 28580

3.2 Definition 3.13: deviation of alignment tyre

The definition should read: "difference in terms of time compared with the mean rolling resistance coefficient results for a given alignment tyre with the appropriate number of repetitions, after correction for any machine drift".

4 Clause 6, Test conditions

4.1 Subclause 6.2, Table 1, and subclause 6.4, Table 2

In Tables 1 and 2, clarify the column heading "Truck and bus" by replacing "Truck and bus" with "Truck and bus (including C, LT)" in each case.

4.2 Subclause 6.4, Table 2

Footnote a in Table 2 is related to pressure, not load. It should therefore be removed from the value 80 under the column headings "Standard load" and "Reinforced or extra load" and the footnote reference "a" added to the row heading "Inflation pressure".

To be consistent with ISO 4000-1 and 4209-1, the load capacity should be clearly indicated as a tyre load, by wording such as: "maximum single-tyre load-carrying capacity" (in Table 2, including footnotes b and c).

A footnote d should be added to the column heading "Truck and bus" which reads: "If there are multiple values given, the highest load and pressure should be selected, not taking into account additional service markings which may exist in a circle.".

5 Clause 7, Test procedure

5.1 Subclause 7.4, Table 3

In Table 3, clarify the column heading "Truck and bus" by replacing "Truck and bus" with "Truck and bus (including C, LT)" in each case.

5.2 Subclause 7.6.2, Note 1

For clarity, add a sentence at the end of this note which reads: "For the force method, the measured value includes the bearing and aerodynamic losses of the wheel and the tyre.".

5.3 Subclause 7.6.3, list item a)

For completeness, the sentence under list item a) should read: "Remove the tyre from the test surface while running at a speed greater than the test speed.".

6 Subclause 8.1, Determination of parasitic loss

For clarity, the parameters of parasitic loss should be distinguished from those of rolling resistance. Using subscripted "p" to indicate "parasitic" in subclauses 8.1.2, 8.1.3 and 8.1.4 (reproduced below) would clarify the intended meaning.

8.1.2 Force method at tyre spindle

The parasitic losses, F_{pl} , expressed in newtons, are calculated by means of Formula (1):

$$F_{\rm pl} = F_{\rm tp} \, \frac{\left(1 + r_{\rm Lp}\right)}{R} \tag{1}$$

where

 F_{tp} is the tyre spindle force, in newtons (see 7.6.2);

 r_{LD} is the distance from the tyre axis to the drum outer surface under steady-state conditions, in metres;

R is the test drum radius, in metres.

8.1.3 Torque method at drum axis

The parasitic losses, F_{pl} , expressed in newtons, are calculated by means of Formula (2):

$$F_{\mathsf{pl}} = \frac{T_{\mathsf{tp}}}{R} \tag{2}$$

where

 T_{tp} is the input torque, expressed, in newton-metres (see 7.6.2);

R is the test drum radius, expressed in metres.

8.1.4 Power method at drum axis

The parasitic losses, F_{pl} , expressed in newtons, are calculated by means of Formula (3):

$$F_{\text{pl}} = \frac{\left(3,6 \times V_{\text{p}} \times A_{\text{p}}\right)}{U_{\text{p}}} \tag{3}$$

where

- $V_{\rm p}$ is the electrical potential applied to the machine drive, expressed in volts;
- A_{p} is the electric current drawn by the machine drive, expressed in amperes;
- U_{n} is the test drum speed, expressed in kilometres per hour.

7 Subclause 10.2, Conditions for reference machine, and subclause 10.3, Conditions for candidate machine

Clarifications to subclauses 10.2 and 10.3 are shown below in **bold** type.

- 10.2 Conditions for reference machine
- **10.2.1** The laboratory operating the reference machine shall comply with either ISO/TS 16949 or ISO/IEC 17025.
- **10.2.2** Monitoring of the reference machine laboratory control tyre shall be carried out at intervals no greater than one month. Monitoring shall include a minimum of three separate measurements taken during this one-month period. The **averaged value and standard deviation** (σ) of the three measurements taken during a given one-month period shall be evaluated for **machine drift and repeatability** from one monthly evaluation to another. **The reference machine maintains a value of** $\sigma \le 0.05$ **N/kN using the control tyre.**
- **10.2.3** The laboratory shall ensure that, based on **a minimum of** three measurements, the reference machine maintains a value of $\sigma_m \le 0.05$ N/kN. This may be done using the **alignment** tyres (as specified in **10.5.2**).
- 10.3 Conditions for candidate machine
- 10.3.1 The laboratory operating the candidate machine shall comply with either ISO/TS 16949 or ISO/IEC 17025.
- 10.3.2 Monitoring of the candidate machine laboratory control tyre shall be carried out at intervals no greater than one month. Monitoring shall include a minimum of three separate measurements taken during this one-month period. The averaged value and standard deviation (σ) of the three measurements taken during a given one-month period shall be evaluated for machine drift and repeatability from one monthly evaluation to another. The candidate machine maintains the standard deviation (σ) using a control tyre not greater than σ_{m} , measured by alignment procedure.
- **10.3.3** The laboratory shall ensure that, based on **a minimum of** three measurements, the candidate machine maintains the following values of σ_m , as measured **using alignment tyres**:
- $\sigma_{\rm m} \le 0.075$ N/kN for passenger car and small truck and bus tyres (LI ≤ 121);
- $\sigma_{\rm m} \leq 0.060$ N/kN for larger truck and bus tyres (LI > 121).

If the above requirement for $\sigma_{\rm m}$ is not met, the formula specified in Formula (13) shall be applied to determine the minimum number of measurements, n (rounded to the immediate superior integer value), that are required by the candidate machine to qualify for conformance with this International Standard.

$$n = \left(\frac{\sigma_{\mathsf{m}}}{x}\right)^2 \tag{13}$$

where

x = 0.075 for passenger car and small truck and bus tyres (LI \leq 121);

x = 0,060 for larger truck and bus tyres (LI > 121).





British Standards Institution (BSI)

BSI is the national body responsible for preparing British Standards and other standards-related publications, information and services.

BSI is incorporated by Royal Charter. British Standards and other standardization products are published by BSI Standards Limited.

About us

We bring together business, industry, government, consumers, innovators and others to shape their combined experience and expertise into standards -based solutions.

The knowledge embodied in our standards has been carefully assembled in a dependable format and refined through our open consultation process. Organizations of all sizes and across all sectors choose standards to help them achieve their goals.

Information on standards

We can provide you with the knowledge that your organization needs to succeed. Find out more about British Standards by visiting our website at bsigroup.com/standards or contacting our Customer Services team or Knowledge Centre.

Buying standards

You can buy and download PDF versions of BSI publications, including British and adopted European and international standards, through our website at bsigroup.com/shop, where hard copies can also be purchased.

If you need international and foreign standards from other Standards Development Organizations, hard copies can be ordered from our Customer Services team.

Subscriptions

Our range of subscription services are designed to make using standards easier for you. For further information on our subscription products go to bsigroup.com/subscriptions.

With **British Standards Online (BSOL)** you'll have instant access to over 55,000 British and adopted European and international standards from your desktop. It's available 24/7 and is refreshed daily so you'll always be up to date.

You can keep in touch with standards developments and receive substantial discounts on the purchase price of standards, both in single copy and subscription format, by becoming a **BSI Subscribing Member**.

PLUS is an updating service exclusive to BSI Subscribing Members. You will automatically receive the latest hard copy of your standards when they're revised or replaced.

To find out more about becoming a BSI Subscribing Member and the benefits of membership, please visit bsigroup.com/shop.

With a **Multi-User Network Licence (MUNL)** you are able to host standards publications on your intranet. Licences can cover as few or as many users as you wish. With updates supplied as soon as they're available, you can be sure your documentation is current. For further information, email bsmusales@bsigroup.com.

BSI Group Headquarters

389 Chiswick High Road London W4 4AL UK

Revisions

Our British Standards and other publications are updated by amendment or revision.

We continually improve the quality of our products and services to benefit your business. If you find an inaccuracy or ambiguity within a British Standard or other BSI publication please inform the Knowledge Centre.

Copyright

All the data, software and documentation set out in all British Standards and other BSI publications are the property of and copyrighted by BSI, or some person or entity that owns copyright in the information used (such as the international standardization bodies) and has formally licensed such information to BSI for commercial publication and use. Except as permitted under the Copyright, Designs and Patents Act 1988 no extract may be reproduced, stored in a retrieval system or transmitted in any form or by any means – electronic, photocopying, recording or otherwise – without prior written permission from BSI. Details and advice can be obtained from the Copyright & Licensing Department.

Useful Contacts:

Customer Services

Tel: +44 845 086 9001

Email (orders): orders@bsigroup.com
Email (enquiries): cservices@bsigroup.com

Subscriptions

Tel: +44 845 086 9001

Email: subscriptions@bsigroup.com

Knowledge Centre

Tel: +44 20 8996 7004

Email: knowledgecentre@bsigroup.com

Copyright & Licensing

Tel: +44 20 8996 7070 Email: copyright@bsigroup.com

