

PD ISO/TS 19408:2015



BSI Standards Publication

Footwear — Sizing — Vocabulary and terminology

bsi.

...making excellence a habit.TM

National foreword

This Published Document is the UK implementation of ISO/TS 19408:2015.

The UK participation in its preparation was entrusted to Technical Committee TCI/69, Footwear, leather and coated fabrics.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2015

Published by BSI Standards Limited 2015

ISBN 978 0 580 82460 9

ICS 01.040.61; 61.060

Compliance with a British Standard cannot confer immunity from legal obligations.

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 28 February 2015.

Amendments/corrigenda issued since publication

Date	Text affected
------	---------------

TECHNICAL SPECIFICATION

**ISO/TS
19408**

First edition
2015-02-01

Footwear — Sizing — Vocabulary and terminology

Chaussures — Pointures — Vocabulaire et terminologie



Reference number
ISO/TS 19408:2015(E)

© ISO 2015



COPYRIGHT PROTECTED DOCUMENT

© ISO 2015

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

	Page
Foreword	iv
1 Scope	1
2 Terms and definitions	1
2.1 Foot dimensions and shoe sizing	1
2.2 Last dimensions	4
Annex A (informative) Figures	7
Annex B (informative) Index	19
Bibliography	21

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: [Foreword - Supplementary information](#)

The committee responsible for this document is ISO/TC 137, *Footwear sizing designations and marking systems*.

Users are encouraged to share their views on ISO/TS 19408:2015 and their priorities for changes to future editions. Click on the link below to take part in the online survey:

[ISO/TS 19408 online survey](#)

Footwear — Sizing — Vocabulary and terminology

1 Scope

This Technical Specification defines terms commonly used for measuring feet and lasts and for determining the size of footwear.

This vocabulary complements ISO 19952, *Footwear – Vocabulary*.

The term “shoe” means all types of footwear.

2 Terms and definitions

2.1 Foot dimensions and shoe sizing

2.1.1

central line of foot

line that connects the centre of the back of the heel (maximum point of the heel curve) and a point in the forefoot area

Note 1 to entry: See [Figure A.1](#) c) and d), and [Figure A.5](#) b).

Note 2 to entry: There are two methods to define the point in the forefoot:

Method 1: at the end of the second toe;

Method 2: in the middle of the tread width of the foot ([2.1.15](#)).

2.1.2

design allowance

additional allowance to the effective shoe length ([2.1.3](#)) added to the forefoot area of the last

Note 1 to entry: See [Figure A.2](#).

2.1.3

effective shoe length

foot length ([2.1.4](#)) plus a toe allowance ([2.2.16](#))

Note 1 to entry: See [Figures A.2](#) and [A.3](#).

2.1.4

foot length

maximum horizontal distance from the centre of the back of the heel (maximum point of heel curve) to the end of the most prominent toe, with the subject standing with the weight of the body equally distributed on both feet, barefoot or wearing thin hose that does not significantly affect the dimensions of the foot

Note 1 to entry: There are different methods to measure the foot length:

Method 1: measured along the inside tangent ([2.1.6](#)) (see [Figure A.1 a](#)) and b);

Method 2: measured parallel to the central line of foot ([2.1.1](#)). There are two methods of measuring the central line (method 2a and 2b). See [Figure A.1a](#), c) and d).

2.1.5

heel height of shoe

vertical height of the extreme rear end of the heel of the shoe down to the ground plane

Note 1 to entry: See [Figure A.3](#).

Note 2 to entry: Heel height of shoe minus the thickness of the sole in the ball area is equivalent to the “heel height of last” ([2.2.6](#)) see [Figure A.8](#).

2.1.6

inside tangent

vertical plane tangential to the point of maximum inside heel swell and the point of maximum swell at the first metatarsal head

Note 1 to entry: See [Figure A.1 b\)](#) and [Figure A.5a](#)).

2.1.7

instep point of foot

intersection of the vertical (normal) plane at a given percentage of foot length with the highest point on the upper (dorsal) surface of the foot

Note 1 to entry: See [Figure A.16](#).

Note 2 to entry: There are different percentages used to mark the instep point:

Method 1: 50% of foot length;

Method 2: 55% of foot length.

2.1.8

joint girth of the foot

anatomic ball girth of the foot

circumference of the foot in a vertical plane around the heads of the first and fifth metatarsal bones

Note 1 to entry: Measurement is made under the same conditions as foot length ([2.1.4](#)).

Note 2 to entry: See [Figure A.4](#).

2.1.9

length grading interval

difference between adjacent whole shoe sizes

2.1.10

linear width (of the foot, of the last)

maximum horizontal distance, o , between the outside swell of the head of the first metatarsal and outside swell of the head of the fifth metatarsal of the foot (see [Figure A.12](#)) or the corresponding points at the last

Note 1 to entry: Measurement of the foot is made under the same conditions as foot length ([2.1.4](#)). There are two methods to obtain the first and fifth metatarsal head points:

Method 1: the inside tangent ([2.1.6](#)) and the parallel line touching the fifth metatarsal [see [Figure A.5 a](#)

Method 2: the tangent lines which are parallel with the central line of foot ([2.1.1](#)) touching the two points [see [Figure A.5 b](#)].

2.1.11

shoe size

designated size marking of a shoe or last made for a given foot length ([2.1.4](#)) in any given shoe sizing system

2.1.12

shoe width

designated marking indicating the joint/ball girth or width fitting of the footwear or last, usually based on the joint girth or width measurement of the last

Note 1 to entry: Designation can be by letters, e.g. A, B, C, or numbers, e.g. 1, 2, 3.

2.1.13

stick width of the foot (or linear width)

perpendicular distance between the first metatarsal head and the fifth metatarsal head

Note 1 to entry: See [Figure A.12](#).

Note 2 to entry: Measurement is made under the same conditions as foot length ([2.1.4](#)). There are two methods to obtain the first and fifth metatarsal head points:

Method 1: the inside tangent ([2.1.6](#)) and the parallel line touching the fifth metatarsal [see [Figure A.5 a](#)];

Method 2: the tangent lines which are parallel with the central line of foot ([2.1.1](#)) touching the two points. There are two methods of central line (method 2a and 2b) [see [Figure A.5 b](#)].

2.1.14

width grading interval

difference between adjacent girth or width fittings within the same shoe size or from shoe size to shoe size

2.1.15

tread width of ball area of foot

the distance b between the maximum swell of the first metatarsal as a point of the foot line touching the ground and the maximum swell of the fifth metatarsal as a point of the foot line touching the ground

Note 1 to entry: See [Figures A.5](#) and [A.12](#).

2.1.16

long heel girth of foot

Note 1 to entry: circumference around the foot passing through the point at the back of the heel where the foot just touches the ground on which the foot stands and the instep point of foot ([2.1.7](#)).

Note 2 to entry: See [Figure A.16](#).

2.1.17

ankle girth

the smallest horizontal girth, i , at the lower leg over the malleolus

Note 1 to entry: See [Figure A.16](#).

2.1.18

calf girth

the maximum horizontal girth, u , in the calf area of lower leg

Note 1 to entry: See [Figure A.16](#).

2.1.19

under knee girth

the smallest horizontal girth, w , below the knee and above calf

Note 1 to entry: See [Figure A.16](#).

2.1.20

short heel girth of foot

shortest circumference, t_1 , around the foot passing through the point at the back of the heel where the foot just touches surface on which the foot stands

Note 1 to entry: See [Figure A.16](#).

2.2 Last dimensions

2.2.1

bottom pattern length of last last bottom length

the length of the last bottom surface from the heel point [[Figure A.10 a](#)] to the furthermost prominent point of the bottom surface at the feather line and projected on to the central line

Note 1 to entry: See [Figure A.6](#).

2.2.2

central line of last bottom pattern

designed line at the last bottom that connects the heel point [[Figure A.10 a](#)] and a point in the forepart area of the last

Note 1 to entry: There are three methods to design that line:

Method 1: second point in the forepart area is the prominent point of the last top at the feather line [see [Figure A.10 a](#)];

Method 2: second point is in the middle of the tread width of the last ([2.1.15](#)) [see [Figure A.10 b](#)];

Method 3: the line constructed following [Figure A.14](#).

2.2.3

effective last length

the foot length ([2.1.4](#)) value, measured from the back of the heel curve of the last ([2.2.5](#)) and along the bottom of the last, plus toe allowance ([2.2.16](#))

Note 1 to entry: See [Figure A.3](#) and [A.11](#).

2.2.4

feather line

perimeter (edge) of the bottom pattern of the last

Note 1 to entry: See [Figure A.7](#).

2.2.5

heel (or back) curve of last

profile line of the heel part of the lasts

Note 1 to entry: See [Figure A.6](#).

2.2.6

heel height of last

technical heel height

vertical distance between the underside of the extreme end of the last and the ground plane with the last in its normal orientation

Note 1 to entry: See [Figure A.8](#).

2.2.7

heel seat

that section of the last bottom between the extreme rear point of heel and the point where the waist curve begins, with the last in its normal orientation

Note 1 to entry: See [Figure A.11](#).

2.2.8

heel width

(tread width and linear or swell width) measurement of heel that is a distance of a given percentage of foot length

Note 1 to entry: The foot length of the marked shoe size is selected from the conversion table in ISO/TS 19407. The given percentages of this length are measured. The measured distance of the maximum of heel curve is subtracted from this value. This value is then marked at the central line of the last bottom measured from the back of the heel. A line is drawn perpendicular to the central line up to the lateral and medial feather line.

2.2.8.1

tread width of heel

distance, q , between the two points marked concerning heel width ([2.2.8](#))

Note 1 to entry: See [Figure A.13](#).

2.2.8.2

linear width of heel

distance, r , between the lateral and medial points following the contour of the surface of the bottom

Note 1 to entry: Measured by extending the line concerning [2.2.8](#) up to the maximum swell of the heel part.

Note 2 to entry: See [Figure A.13](#).

2.2.9

instep point of last

point at the intersection between a plane and the highest point upper (dorsal) surface of the last

Note 1 to entry: See [Figure A.15](#).

Note 2 to entry: There are three methods to define the plane:

Method 1: perpendicular to the central line of the last bottom at 42 % of effective last length;

Method 2: perpendicular to the central line of the last bottom ant 50 % of the foot length;

Method 3: perpendicular to the last bottom at the point G1 ([Figure A.14](#)).

2.2.10

joint girth of last

ball girth of last

circumference around the last in the forepart corresponding to the approximate position of the ball joint of the foot

2.2.11

last length

sum of the bottom pattern length of last, d , ([2.2.1](#)), measured along the surface of the bottom of the last, maximum of heel curve of the last, a , ([2.2.5](#)) and hang over last top, e , with the last in its normal orientation

Note 1 to entry: See [Figure A.6](#).

Note 2 to entry: The dimension, e , can be zero.

2.2.12

last toe height

the maximum distance between the last bottom and the upper surface of the last measured on a line perpendicular to the last bottom plane and at the effective last length ([2.2.3](#))

Note 1 to entry: See [Figure A.11](#).

2.2.13

last toe spring

the vertical distance between the underside of the last at the extreme toe end and the ground plane with the last in its normal orientation

Note 1 to entry: See [Figure A.8](#).

2.2.14

long heel girth of last

girth t_2 from the point of the middle of the heel at the feather line, crossing the instep point, back to the heel point

Note 1 to entry: See [Figure A.15](#).

2.2.15

stick last length

the longest dimension of the last from the heel to the toe with the last in a flat position (without heel height)

Note 1 to entry: See [Figure A.9](#).

2.2.16

toe allowance

the addition to the foot length ([2.1.4](#)) which is necessary to accommodate the dynamic functioning of the foot

Note 1 to entry: See [Figures A.2](#) and [A.3](#).

2.2.17

tread width of the ball area of last

distance, b , between the maximum swell of the first metatarsal as a point of the last feather line and the maximum swell of the fifth metatarsal as a point of the last feather line

Note 1 to entry: See [Figure A.12](#).

Note 2 to entry: There are different methods of measuring:


Method 1: the inside tangent ([2.1.6](#)) and the parallel line touching the ball points of the last;

Method 2: the tangent lines which are parallel with the central line of foot ([2.1.1](#)) touching the two points;


Method 3: this method uses the points E1 and F1 to find these points ([Figure A.14](#)).

Annex A (informative)


Figures




a — Foot length (method 1 and 2)



b — Foot length (method 1)



c — Foot length (method 2 a)



d — Foot length (method 2 b)

Key


l foot length

y inside tangent

x central line

b tread width of the foot

Figure A.1 — Foot length



Key

- l foot length
- s effective shoe length
- f toe allowance
- g design allowance

Figure A.2 — Design allowance



Key

- s* effective shoe or last length
- l* foot length
- f* toe allowance
- h* heel height of shoe

Figure A.3 — Toe allowance





Figure A.4 — Joint girth of the foot




a) — Stick width of the foot (method 1)

b) — Stick width of the foot (method 2a and 2b)

Key

- b tread width of the foot
- c stick width of the foot
- x central line
- y inside tangent


Figure A.5 — Stick width of the foot



Key

- a* maximum of heel (or back) curve
- d* bottom pattern length
- e* hang over last top


Figure A.6 — Last length



Key

- n* feather line


Figure A.7 — Feather line



Key

- h* heel height of last
k toe spring of last


Figure A.8 — Technical heel height and toe spring




Key

- m* stick last length

Figure A.9 — Stick last length



a) – Central line of last bottom pattern (method 1)




b) - Central line of last bottom pattern (method 2)

Key

- d length of last bottom
- N feather line
- b tread width of last
- 1 heel point at the feather line
- 2 prominent point of the last top at the feather line
- 3 middle point of the tread width


Figure A.10 — Central line of last bottom pattern



Key

- v heel seat
- p toe height
- s effective last length


Figure A.11 — heel seat of last and toe height



Key

- b tread width of foot or last
- o linear width of foot or last

Figure A.12 — linear width and tread width of the ball area of foot or last




Key

q tread width of heel

r linear width of heel


Figure A.13 — Tread width and linear width of heel



Key

- 1 = $90\% \times L - a$
- 2 = $72,5\% \times L - a$
- 3 = $18\% \times L - a$
- 4 = $41\% \times L - a$
- 5 = $63,5\% \times L - a$
- 6 = $78\% \times L - a$
- 7 = $100\% \times L - a$
- L = foot length


Figure A.14 — Method 1 to define the ball points E1 and F1



Key

Parts/positions	
t_2	long heel girth of last
1	instep point of last
Z_2	instep girth of last

Figure A.15 — Long heel girth of last t_2



Key

- t₁ short heel girth of foot
- t₂ long heel girth of foot
- 1 instep point of foot
- 2 throat position
- i ankle girth
- u calf girth
- W under knee girth
- Z₁ instep girth of foot

Figure A.16 — Lower leg dimensions

Annex B (informative)

Index

Foot dimensions and shoe sizing	2.1
anatomic ball girth of the foot	2.1.8
ankle girth	2.1.17
calf girth	2.1.18
central line of foot	2.1.1
design allowance	2.1.2
effective shoe length	2.1.3
foot length	2.1.4
heel height of shoe	2.1.5
inside tangent	2.1.6
joint girth of the foot	2.1.8
length grading interval	2.1.9
linear width	2.1.10
long heel girth of foot	2.1.16
shoe size	2.1.11
shoe width	2.1.12
stick width of the foot	2.1.13
tread width of ball area of foot	2.1.15
under knee girth	2.1.19
width grading interval	2.1.14
Last dimensions	2.2
bottom pattern length of last	2.2.1
central line of last bottom pattern	2.2.2
effective last length	2.2.3
feather line	2.2.4
heel curve of last	2.2.5
heel height of last	2.2.6

heel seat	2.2.7
heel width	2.2.8
joint girth of last	2.2.10
last length	2.2.11
last toe height	2.2.12
last toe spring	2.2.13
linear width of heel	2.2.8.2
long heel girth of last	2.2.14
stick last length	2.2.15
toe allowance	2.2.16
tread width of the ball area of last	2.2.17
tread width of heel	2.2.8.1

Bibliography

- [1] ISO/TS 19407, *Footwear - Sizing - Conversion of major sizing systems*
- [2] ISO 19952, *Footwear — Vocabulary*

This page deliberately left blank

This page deliberately left blank

British Standards Institution (BSI)

BSI is the national body responsible for preparing British Standards and other standards-related publications, information and services.

BSI is incorporated by Royal Charter. British Standards and other standardization products are published by BSI Standards Limited.

About us

We bring together business, industry, government, consumers, innovators and others to shape their combined experience and expertise into standards-based solutions.

The knowledge embodied in our standards has been carefully assembled in a dependable format and refined through our open consultation process. Organizations of all sizes and across all sectors choose standards to help them achieve their goals.

Information on standards

We can provide you with the knowledge that your organization needs to succeed. Find out more about British Standards by visiting our website at bsigroup.com/standards or contacting our Customer Services team or Knowledge Centre.

Buying standards

You can buy and download PDF versions of BSI publications, including British and adopted European and international standards, through our website at bsigroup.com/shop, where hard copies can also be purchased.

If you need international and foreign standards from other Standards Development Organizations, hard copies can be ordered from our Customer Services team.

Subscriptions

Our range of subscription services are designed to make using standards easier for you. For further information on our subscription products go to bsigroup.com/subscriptions.

With **British Standards Online (BSOL)** you'll have instant access to over 55,000 British and adopted European and international standards from your desktop. It's available 24/7 and is refreshed daily so you'll always be up to date.

You can keep in touch with standards developments and receive substantial discounts on the purchase price of standards, both in single copy and subscription format, by becoming a **BSI Subscribing Member**.

PLUS is an updating service exclusive to BSI Subscribing Members. You will automatically receive the latest hard copy of your standards when they're revised or replaced.

To find out more about becoming a BSI Subscribing Member and the benefits of membership, please visit bsigroup.com/shop.

With a **Multi-User Network Licence (MUNL)** you are able to host standards publications on your intranet. Licences can cover as few or as many users as you wish. With updates supplied as soon as they're available, you can be sure your documentation is current. For further information, email bsmusales@bsigroup.com.

BSI Group Headquarters

389 Chiswick High Road London W4 4AL UK

Rewvisions

Our British Standards and other publications are updated by amendment or revision. We continually improve the quality of our products and services to benefit your business. If you find an inaccuracy or ambiguity within a British Standard or other BSI publication please inform the Knowledge Centre.

Copyright

All the data, software and documentation set out in all British Standards and other BSI publications are the property of and copyrighted by BSI, or some person or entity that owns copyright in the information used (such as the international standardization bodies) and has formally licensed such information to BSI for commercial publication and use. Except as permitted under the Copyright, Designs and Patents Act 1988 no extract may be reproduced, stored in a retrieval system or transmitted in any form or by any means – electronic, photocopying, recording or otherwise – without prior written permission from BSI. Details and advice can be obtained from the Copyright & Licensing Department.

Useful Contacts:

Customer Services

Tel: +44 845 086 9001

Email (orders): orders@bsigroup.com

Email (enquiries): cservices@bsigroup.com

Subscriptions

Tel: +44 845 086 9001

Email: subscriptions@bsigroup.com

Knowledge Centre

Tel: +44 20 8996 7004

Email: knowledgecentre@bsigroup.com

Copyright & Licensing

Tel: +44 20 8996 7070

Email: copyright@bsigroup.com



...making excellence a habit.TM