

# INTERNATIONAL STANDARD

# ISO 3402

Fourth edition  
1999-12-15

---

---

## Tobacco and tobacco products — Atmosphere for conditioning and testing

*Tabac et produits du tabac — Atmosphère de conditionnement et d'essai*



Reference number  
ISO 3402:1999(E)

© ISO 1999

**PDF disclaimer**

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

© ISO 1999

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 734 10 79  
E-mail [copyright@iso.ch](mailto:copyright@iso.ch)  
Web [www.iso.ch](http://www.iso.ch)

Printed in Switzerland

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 3.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

International Standard ISO 3402 was prepared by Technical Committee ISO/TC 126, *Tobacco and tobacco products*.

This fourth edition cancels and replaces the third edition (ISO 3402:1991), which has been editorially revised.

## Introduction

During 1988 and 1989, collaborative studies by task forces composed of members of the Cooperation Centre for Scientific Research Relative to Tobacco (CORESTA), "Smoke" and "Technology" groups, have been made on the repeatability and reproducibility of tests on tobacco and tobacco products.

These studies have resulted in the publication of CORESTA Recommended Method No. 21 (see bibliographic reference [1]).

It has since been found that, in practice, the previous tolerances on relative humidity for the test atmosphere were difficult to achieve.

# Tobacco and tobacco products — Atmosphere for conditioning and testing

## 1 Scope

This International Standard specifies the atmosphere for the conditioning and testing of samples and test pieces of tobacco and tobacco products.

It is applicable to tests on tobacco, tobacco products, and materials used in the manufacture of tobacco products for which prior conditioning is necessary. It is not applicable in the case of test methods and test conditions stipulated in other International Standards (see bibliography).

NOTE Atmospheres for conditioning and testing for other tobacco products (e.g. cigars, pipe tobacco or snuff tobacco) may differ from those specified in this International Standard. If required separate standards will be drafted.

## 2 Terms and definitions

For the purposes of this International Standard, the following terms and definitions given in ISO 558:1980 [4] apply.

### 2.1

#### **atmosphere**

ambient conditions defined by one or more of the following parameters:

- temperature
- relative humidity
- pressure

[ISO 558:1980, definition 2.1]

### 2.2

#### **conditioning atmosphere**

atmosphere in which a sample or test piece is kept before being subjected to test

NOTE 1 It is characterized by specified values for one or more of the following parameters: temperature, relative humidity and pressure, which are kept within the prescribed tolerances for a given period of time.

NOTE 2 The term "conditioning" refers to the operation as a whole designed to bring a sample or test piece, before testing, into a specified condition in relation to temperature and humidity, by keeping it for a given period of time in the conditioning atmosphere.

NOTE 3 The conditioning can be done either in the laboratory or in a special enclosure termed "the conditioning chamber", or in the test chamber.

NOTE 4 The chosen values and period of time depend on the nature of the sample or test piece to be tested.

NOTE 5 Adapted from ISO 558:1980, definition 2.2.

### 2.3

#### **test atmosphere**

atmosphere to which a sample or test piece is exposed throughout the test

NOTE 1 It is characterized by specified values for one or more of the following parameters: temperature, relative humidity and pressure, which are kept within the prescribed tolerances.

NOTE 2 The test may be carried out either in the laboratory or in a special chamber termed "the test chamber", or in the conditioning chamber, the choice depending on the nature of the test piece and on the test itself. For example, close control of the test atmosphere may not be necessary if the change of properties of the test piece is insignificant in the test period.

NOTE 3 Adapted from ISO 558:1980, definition 2.3.

## 3 Atmosphere

### 3.1 Conditioning atmosphere

The conditioning atmosphere shall be as follows:

- temperature  $(22 \pm 1)$  °C;
- relative humidity  $(60 \pm 3)$  %.

NOTE Whilst monitoring equipment might indicate the relative humidity is within the  $(60 \pm 3)$  % specification, this tolerance can be comparable with the uncertainty in calibration of the equipment.

The specified tolerances listed above define the atmosphere immediately surrounding the test piece. Therefore, the atmosphere surrounding the test piece shall be maintained at a mean temperature of 22 °C and a mean relative humidity of 60 %.

### 3.2 Test atmosphere

The test atmosphere shall be the same as the conditioning atmosphere but wider tolerances are permissible as follows:

- temperature  $(22 \pm 2)$  °C;
- relative humidity  $(60 \pm 5)$  %.

The atmospheric pressure shall be measured and included in the test report if it is outside the range 86 kPa to 106 kPa.

## 4 Conditioning

### 4.1 Duration of conditioning

In current practice, conditioning for 48 h using a forced air flow is generally found to be sufficient for loose cigarettes. This conditioning time can be insufficient for certain samples or test pieces, for example, for packeted cigarettes in bulk and when loose cigarettes are conditioned without forced air flow. Therefore, in all cases, it should be verified that equilibrium has been properly attained (see 4.2).

It is recommended that the atmospheric relative humidity near the samples or test pieces be verified by the use of a hygrometer calibrated with traceable standards (for details see ISO 4677-1 [5]).

The air flow should be sufficient to condition loose cigarettes in the specified period, but it should be noted that excessive air flow may result in improper conditioning.

If, for any reason, test samples are to be kept for longer than 10 days before conditioning, store them in the original packaging or in airtight containers just large enough to contain the sample. If samples are to be kept for longer than 3 months, it is recommended that they are frozen and stored at, or below,  $-16$  °C until needed.

## 4.2 Checking of equilibrium

Equilibrium shall be considered to be attained when either

- a) the relative variation of the mass of the sample or test pieces is not greater than 0,2 % in 3 h, or
- b) the sample or the test pieces, placed in a closed container of a volume similar to that of the sample or the test pieces, give(s) rise to a relative humidity in the container equal to that of the conditioning atmosphere.

NOTE Suitable apparatus for the measurement of relative humidity in the container is available from Rotronic and Novasina.<sup>1)</sup>

---

1) This information is given for the convenience of users of this International Standard and does not constitute an endorsement by ISO of this product. Equivalent products may be used if they can be shown to lead to the same results.

## Bibliography

- [1] CORESTA Recommended Method No. 21: August 1991, *Atmosphere for conditioning and testing tobacco and tobacco products.*
- [2] ISO 15592-2, *Fine-cut tobacco and smoking articles made from it — Methods of sampling, conditioning and analysis — Part 2: Atmosphere for conditioning and testing (under preparation).*
- [3] ISO 187, *Paper, board and pulps — Standard atmosphere for conditioning and testing and procedure for monitoring the test atmosphere and conditioning of samples.*
- [4] ISO 558:1980, *Conditioning and testing — Standard atmospheres — Definitions.*
- [5] ISO 4677-1, *Atmospheres for conditioning and testing — Determination of relative humidity — Part 1: Aspirated psychrometer method.*
- [6] CORESTA Recommended Method No. 46: May 1998, *Atmosphere for conditioning and testing cigars of all sizes and shapes.*





---

---

**ICS 65.160**

Price based on 4 pages

© ISO 1999 – All rights reserved