

First edition
2003-04-15

**Road vehicles — Injury risk curves for
evaluation of occupant protection in
frontal impact**

*Véhicules routiers — Courbes de risques de blessures pour évaluer la
protection des occupants en choc frontal*



Reference number
ISO/TR 7861:2003(E)

© ISO 2003

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

© ISO 2003

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Injury risk curves	1
3.1 General	1
3.2 Head injury risk curves	1
3.3 Neck injury risk curves	1
3.4 Thoracic injury risk curves	2
3.4.1 General	2
3.4.2 Shoulder belt loading	2
3.4.3 Distributed loading	3
3.5 Lower extremity fracture curves	3
3.5.1 Knee-thigh-hip fractures	3
3.5.2 Tibia shaft fractures	3
3.5.3 Ankle/foot fractures	3
Annex A (normative) Injury risk curves	4
Bibliography	16

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

In exceptional circumstances, when a technical committee has collected data of a different kind from that which is normally published as an International Standard ("state of the art", for example), it may decide by a simple majority vote of its participating members to publish a Technical Report. A Technical Report is entirely informative in nature and does not have to be reviewed until the data it provides are considered to be no longer valid or useful.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO/TR 7861 was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 12, *Passive safety crash protection systems*.

Introduction

A number of researchers have proposed injury risk curves for various dummy measurements, based on their analyses of published biomechanical data. These curves, summarized in this Technical Report, can be used by regulatory authorities as well as car manufacturers to set occupant protection levels based on the injury risks they believe are acceptable for the frontal collision being simulated. No limits are given because it is the view of ISO/TC 22 that the setting of performance levels is a responsibility for regulatory authorities.

© ISO 2003. All rights reserved.

Road vehicles — Injury risk curves for evaluation of occupant protection in frontal impact

1 Scope

This Technical Report presents injury risk curves that can be used for injury risk assessment in the evaluation of occupant protection in road-vehicle frontal impact. The measurements were made on frontal-impact crash test dummies which present acceptable levels of biofidelity response in accordance with ISO/TR 12349-1 and ISO/TR 12349-2 and which are used in the frontal-impact test procedures of existing International Standards.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO TR 12349-1, *Road vehicles — Dummies for restraint system testing — Part 1: Adult dummies*

ISO TR 12349-2, *Road vehicles — Dummies for restraint system testing — Part 2: Child dummies*

3 Injury risk curves

3.1 General

All the injury risk curves, presented in Annex A, are shown plotted on normal probability graph paper. Values for mean value (denoted with a superscript dash over the parameter) and standard deviation (σ) for each risk curve are shown on the graphs.

3.2 Head injury risk curves

Three head injury risk curves are given for forehead impacts. The bases for these curves are discussed by Prasad and Mertz [1] and Mertz et al. [2, 3]. The risk of skull fracture as functions of 15 ms HIC (head impact criteria) and peak acceleration of the centre of gravity of the head are given in Figures A.1 and A.2, respectively. The risk of AIS (abbreviated injury scale) ≥ 4 brain injury as a function of 15 ms HIC is given in Figure A.3.

3.3 Neck injury risk curves

Three normalized risk curves for AIS ≥ 3 neck injury based on measurements made at the occipital condylar joint for tension-extension neck loading are given for CRABI and Hybrid III dummy families. These curves are based on the work described by Mertz et al. [4] and Mertz and Prasad [5] and include a factor for variation in failure stress as a function of age [5]. Figures A.4, A.5 and A.6 are the risk curves for peak normalized neck tension, peak extension moment and an index for the peak combination of tension and extension moment, respectively. Normalizing values for various dummy sizes are listed in the legends of the graphs and correspond to 3 %, 5 % and 2 % risks of AIS ≥ 3 neck injury with minimum passive muscle tone, respectively. These normalizing values are the limit values for out-of-position airbag testing specified in FMVSS 208 [20].

These curves can also be used to estimate injury risk with various amounts of muscle pretension. The procedure for making such estimates is as follows.

- a) Determine the maximum values of each normalized function from the test data.
- b) Subtract from these values the values of loading assumed to be carried by the muscles, or
 - 1) neck tension, F_T/F_3

$$\frac{F_T}{F_3} = \left[\frac{F_T}{F_3} \right]_{\max} - m \left[\frac{F_M}{F_3} \right]$$

- 2) neck extension moment, M_E/M_5

$$\frac{M_E}{M_5} = \left[\frac{M_E}{M_5} \right]_{\max} - m \left[\frac{M_M}{M_5} \right]$$

- 3) combined tension and extension moment, N_{TE}

$$N_{TE} = \left[\frac{M_E}{M_2} + \frac{F_T}{F_2} \right]_{\max} - m \left[\frac{F_M}{F_2} \right]$$

where

F_M, M_M are the maximum tension and extension moment due to pretensing of the neck muscles;

m is the fraction of the maximum passive muscle tensing assumed ($0 \leq m \leq 1$).

These differences are used to estimate the injury risks from the curves of Figures A.4, A.5 and A.6.

Mertz and Prasad [5] provide estimates for the maximum values for tension and extension moment due to pretensioning of the neck muscles for various sizes of dummies based on static strength tests. These values are given in Table A.1. No values are listed for the CRABI infant dummies because it is unreasonable to expect an infant to be aware of an impending collision.

3.4 Thoracic injury risk curves

3.4.1 General

There are two types of thoracic loadings for which injury risk curves have been developed:

- a) shoulder belt loading with and without air bags;
- b) distributed thoracic loading such as is produced by air bags without belts.

3.4.2 Shoulder belt loading

Mertz et al. [6] correlated field accident observations of thoracic injuries of occupants restrained with three-point belts with force-limiting shoulder belts to Hybrid III sternal deflections measured for the simulated accident conditions. These data were used to formulate the AIS ≥ 3 thoracic injury risk curve of Figure A.7 as a function of Hybrid III sternal deflection. This risk curve can be used whenever the torso is restrained by a shoulder belt, even if an air bag is part of the restraint system. Since the field accident data was not normalized for size of occupants, the curve overestimates the injury risk for the 50th percentile adult male at low risk levels.

Foret-Bruno et al. [7] have done a correlation study of field accident observations of thoracic injuries of occupants restrained with three-point belts with force-limiting shoulder belts and head air bags and shoulder belt loads measured in accidents. Figure A.8 is their risk curve for AIS ≥ 3 thoracic injury as a function of shoulder belt load. To use this curve, the belt geometry shall be similar to the simulated tests.

3.4.3 Distributed loading

Figure A.9 gives the injury risk curves for the AIS ≥ 3 thoracic injuries. The normalizing values which correspond to 5 % risk are given in the legend. No AIS ≥ 3 risk curves are given for infants and children. This is because the low bending modulus of their ribs allows them to experience large sternal deflections without rib fractures which is the predominant AIS = 3 thoracic injury. Figure A.10 gives injury risk curves of Mertz et al. [4] for AIS ≥ 4 thoracic injuries for distributed chest loading, such as an air bag, as a function of normalized sternal deflection. Normalizing values which correspond to a 5 % risk for different dummy types are given on the graph.

The curve for AIS ≥ 4 heart/lung injuries as a function of the rate of sternal risk compression that was developed by Mertz et al. [4] is given in Figure A.11. These curves can be used with all dummy sizes since the internal organ stress level is dependent only on the rate of sternal compression and not on size.

Viano et al. [8] hypothesized that heart/lung trauma would be caused by the product of the sternal deflection rate and the normalized sternal deflection: the viscous criterion, V*C. Figure A.12 gives the risk curve of AIS ≥ 4 heart/lung injury as a function of the viscous criterion. Normalizing values are not given for the CRABI family because these dummies are not instrumented to measure sternal compression. Caution must be used when using the viscous criterion since the instrumentation used to process the original biomechanical data lacked the required high frequency fidelity needed to obtain accurate V*C values.

3.5 Lower extremity fracture curves

3.5.1 Knee-thigh-hip fractures

The cadaver data summarized by Morgan et al. [10, 11, 12, 13, 14, 15, 16] for knee impacts were analyzed using the Mertz-Weber technique [17] to obtain a risk curve for knee-thigh-hip fracture as a function of axial compressive knee load, as shown in Figure A.13.

3.5.2 Tibia shaft fractures

Nyquist et al. [18] conducted three-point bending tests on the intact leg of 16 male specimens. Median rank analysis [19] of the maximum bending moments at fracture gave the fracture risk curve shown in Figure A.14.

3.5.3 Ankle/foot fractures

Crandall et al. [19] conducted impact tests to the feet of 50 amputated cadaver lower limbs that produced fractures of the calcaneus, talus and malleoli, as well as ligamentous tears. These data were analyzed using the Mertz-Weber technique [17] to obtain a risk curve for ankle or foot fractures, or both, as a function of the axial compressive tibia shaft load shown in Figure A.15.

Annex A
(normative)

Injury risk curves

Figure A.1 — Risk of AIS \geq 2 skull fracture as function of max. 15 ms HIC

Figure A.2 — Risk of AIS \geq 2 skull fracture as function of the peak resultant acceleration of centre of gravity of head

Figure A.3 — Risk of AIS \geq 4 brain injury as function of max. 15 ms HIC

Dummy	$F_3(N)$
CRABI - 12 mo.	780
HIII - 3 yr.	1 130
HIII - 6 yr.	1 490
HIII - Sm. Fem	2 070
HIII - Mid. Male	3 290
HIII - Lg. Male	3 970

Figure A.4 — Risk of AIS \geq 3 neck injury for CRABI and Hybrid III dummy families as function of peak normalized neck tension

Dummy	$M_5(\text{N}\cdot\text{m})$
CRABI - 12 mo.	11
HIII - 3 yr.	17
HIII - 6 yr.	24
HIII - Sm. Fem	39
HIII - Mid. Male	77
HIII - Lg. Male	102

Figure A.5 — Risk of ≥ 3 neck injury for CRABI and Hybrid III dummy families as function of peak normalized neck extension moment

Dummy	$F_2(N)$	$M_2(N\cdot m)$
CRABI - 12 mo.	1 470	17,0
HIII - 3 yr.	2 130	26,8
HIII - 6 yr.	2 820	38,4
HIII - Sm. Fem	3 900	61,2
HIII - Mid. Male	6 200	122
HIII - Lg. Male	7 480	162

Figure A.6 — Risk of AIS \geq 3 neck injury for CRABI and Hybrid III dummy families as function of peak combined normalized neck extension moment and tension

Figure A.7 — Risk of AIS ≥ 3 thoracic injury due to shoulder belt loading as function of peak Hybrid III sternal deflection

.....

Figure A.8 — Risk of AIS ≥ 2 and ≥ 3 thoracic injury as function of peak shoulder belt load

Dummy	δ_c (mm)
HIII - Sm. Fem	39,0
HIII - Mid. Male	47,7
HIII - Lg. Male	52,9

Figure A.9 — Risk AIS \geq 3 thoracic injury for distributed chest impacts as function of peak normalized sternal deflection

Dummy	δ_c (mm)
CRABI - 12 mo.	31,2
HIII - 3 yr.	35,8
HIII - 6 yr.	39,7
HIII - Sm. Fem	52,5
HIII - Mid. Male	64,3
HIII - Lg. Male	71,2

Figure A.10 — Risk of AIS \geq 4 thoracic injury for distributed chest impacts as function of peak normalized sternal deflection

Dummy	VIV_5 (m/s)
CRABI - 12 mo.	7,6
HIII - 3 yr.	8,0
HIII - 6 yr.	8,5
HIII - Sm. Fem	8,2
HIII - Mid. Male	8,2
HIII - Lg. Male	8,2

Figure A.11 — Risk of AIS \geq 4 heart/lung injury as function of peak rate of sternal compression

Dummy	δ_c (mm)
HIII - 3 yr.	122
HIII - 6 yr.	143
HIII - Sm. Fem	187
HIII - Mid. Male	229
HIII - Lg. Male	254

Figure A.12 — Risk of AIS \geq 4 thoracic injury as function of the peak viscous criterion, V*C

Figure A.13 — Risk of knee-thigh-hip fracture as function of peak knee load

Figure A.14 — Risk of tibia shaft fracture as function of peak mid-shaft bending moment

Figure A.15 — Risk of ankle/foot fracture as function of peak axial compressive tibia load

Table A.1 — Max. passive neck muscle strengths

Dummy	Max. static muscle strengths	
	Tension F_M N	Extension moment M_M N · m
CRABI 6	—	—
CRABI 12	—	—
CRABI 18	—	—
H III — 3 year	378	5,2
H III — 6 year	500	7,4
H III — Sm. Fem.	693	11,9
H III — Mid-Male	1 100	23,7
H III — Lg. Male	1 330	31,5

Bibliography

- [1] PRASAD, P. and MERTZ, H. J., *The Position of the United States Delegates to the ISO Working Group 6 on the Use of HIC in the Automotive Environment*, SAE 851246, 1985
- [2] MERTZ, H. J., PRASAD, P. and NUSHOLTZ, G., *Head Injury Risk Assessment for Forehead Impacts*, SAE 960099, February 1996
- [3] MERTZ, H. J., PRASAD, P. and NUSHOLTZ, G., *Head Injury Risk Assessments Based on 15 ms HIC and Peak Head Acceleration Criteria*, Proceeding of AGARD Meeting on Impact Head Injury, November 7-9, 1996
- [4] MERTZ, H. J., PRASAD, P., and IRWIN, A. L., *Injury Risk Curves for Children and Adults in Frontal and Rear Collisions*, SAE 973318, Forty-First Stapp Car Crash Conference, November 1997
- [5] MERTZ H. J. and PRASAD, P., *Improved Neck Injury Risk Curves for Tension and Extension Moment Measurements of Crash Dummies*, Stapp Car Crash Journal, 00SC05, November 2000
- [6] MERTZ, H. J., HORSCH, J. D., HORN, G., and LOWNE, R. W., *Hybrid III Sternal Deflection Associated with Thoracic Injury Severities of Occupants Restrained with Force-Limiting Shoulder Belts*, SAE 910812, February 1991
- [7] FORET-BRUNO, J.-Y., TROSSEILLE, X., LE COZ, J.-Y., BENDJELLAL, F., STEYER, C., PHALEMPIN, T., VILLEFORCEIX, D., DANDRES, P. and GOT, C., *Thoracic Injury Risk in Frontal Car Crashes with Occupant Restrained with Belt Load Limiter*, SAE 983166, 42nd Stapp Car Crash Conference, November 1998
- [8] VIANO, D. V. and LAU, I. V., *Thoracic Impact: A Viscous Tolerance Criterion, Proceedings of the Tenth Experimental Safety Vehicle Conference*, July 1985
- [9] MELVIN, J. W., and NUSHOLTZ, G. S., *Tolerance and Response of the Knee-Femur-Pelvis Complex to Axial Impacts: Impact Sled Test*, University of Michigan, Highway Safety Research Institute, Ann Arbor, Report No. UM-HSRI-80-27, 1980
- [10] MORGAN, R. M., EPPINGER, R. H. and MARCUS, J. H., *Human Cadaver Patella-Femur-Pelvis Injury due to Dynamic Frontal Loading to the Patella*, 12th ESV, Paper No. 89-4A-0-13, May 1989
- [11] CHENG, R., YANG, K. H., LEVINE, R. S., KING, A. I., and MORGAN, R., *Injuries to the Cervical Spine Caused by a Distributed Frontal Load to the Chest*, Twenty-Sixth Stapp Car Crash Conference, October 1982
- [12] LEUNG, Y. C., HUE, B., FAYON, A., TARRIERE, C., HAMON, H., GOT, C., PATEL, A., and HUREAU, J., *Study of "Knee-Thigh-Hip" Protection Criterion*, Twenty-Seventh Stapp Car Crash Conference, October 1983
- [13] CHENG, R., YANG, K., LEVINE, R. S., and KING, A. I., *Dynamic Impact Loading of the Femur Under Passive Restrained Condition*, Twenty-Eighth Stapp Car Crash Conference, November 1984
- [14] ROBERTS, D. P., DONNELLY, B. R., and MORGAN, R., *Cadaver Response to Axial Impacts of the Femur*, Eleventh International Technical Conference on Experimental Safety Vehicles, May 1987
- [15] DONNELLY, B. R., and ROBERTS, D. P., *Comparison of Cadaver and Hybrid III Dummy Response to Axial Impacts of the Femur*, Thirty-First Stapp Car Crash Conference, November 1987
- [16] MORGAN, R. M., SCHNEIDER, D. C., EPPINGER, R. H., NAHUM, A. M., MARCUS, J. H., AWAD, J., DAINTY, D., and FORREST, S., *Interaction of Human Cadaver and Hybrid III Subjects with a Steering Assembly*, Thirty-First Stapp Car Crash Conference, November 1987

- [17] MERTZ, H. J. and WEBER, D. A., *Interpretations of the Impact Responses of a 3-Year Old Child Dummy Relative to Child Injury Potential*, Proceedings of the Ninth International Technical Conference on Experimental Safety Vehicles, Kyoto, Japan, November 1-4, 1982. (Republished in SAE 826048, SP-736 Automatic Occupant Protection Systems, February 1988)
- [18] NYQUIST G. W., CHEN, R., EL-BOHY, A., and KING, A. I., *Tibia Bending: Strength and Response*, SAE 851728, Twenty-Ninth Stapp Car Crash Conference, October 1985
- [19] CRANDALL, J. R., et al, *Mechanisms of Injury and Injury Criteria for the Human Foot and Ankle*, IRCOBI, September 1997
- [20] FMVSS 208:1997, *Occupant crash protection*
- [21] ISO 3560, *Road vehicles — Frontal fixed barrier or pole impact test procedure*
- [22] ISO 7862¹⁾, *Passenger cars — Sled test procedure for evaluating restraint systems in simulated frontal collisions*
- [23] ISO TR 10982, *Road vehicles — Test procedures for evaluating out-of-position vehicle occupant interactions with deploying air bags*
- [24] ISO TR 14645, *Road vehicles — Test procedures for evaluating child restraint system interactions with deploying air bags*
- [25] ISO 15828²⁾, *Road vehicles — Offset frontal impact test procedure*

1) To be published. (Revision of ISO 7862:1992)
 2) To be published.

Vertical line of small characters or artifacts.

ICS 43.020

Price based on 17 pages