



**INTERNATIONAL STANDARD ISO 10077-2:2012**  
**TECHNICAL CORRIGENDUM 1**

Published 2012-07-15

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION

**Thermal performance of windows, doors and shutters —**  
**Calculation of thermal transmittance —**

**Part 2:**  
**Numerical method for frames**

**TECHNICAL CORRIGENDUM 1**

*Performance thermique des fenêtres, portes et fermetures — Calcul du coefficient de transmission thermique —*

*Partie 2: Méthode numérique pour les encadrements*

*RECTIFICATIF TECHNIQUE 1*

Technical Corrigendum 1 to ISO 10077-2:2012 was prepared by Technical Committee ISO/TC 163, *Thermal performance and energy use in the built environment*, Subcommittee SC 2, *Calculation methods*.

---

*Page 8, 6.3.2.1*

After Equation (1), in definition for  $d$ , replace reference to “Figure 2” with “Figure 4” as follows:

where

$d$  is the dimension of the cavity in the direction of heat flow (see Figure 4).

*Page 10, 6.3.3*

Add the following paragraph at the end of the subclause:

“Cavities with one dimension not exceeding 2 mm or cavities with an interconnection not exceeding 2 mm shall be considered as separate.”