



INTERNATIONAL STANDARD ISO 10262:1998
TECHNICAL CORRIGENDUM 1

Published 2009-07-15

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION

Earth-moving machinery — Hydraulic excavators — Laboratory tests and performance requirements for operator protective guards

TECHNICAL CORRIGENDUM 1

Engins de terrassement — Pelles hydrauliques — Essais de laboratoire et critères de performance des structures de protection de l'opérateur

RECTIFICATIF TECHNIQUE 1

Technical Corrigendum 1 to ISO 10262:1998 was prepared by Technical Committee ISO/TC 127, *Earth-moving machinery*, Subcommittee SC 2, *Safety, ergonomics and general requirements*.

Page 5, 5.2.2

Replace the last sentence of the third unnumbered list element with the following:

“The DLV shall be positioned at the SIP⁵⁾ in accordance with ISO 5353 and ISO 3164 and be fixed firmly to the same part of the machine to which the operator seat is secured;”

Page 10, 8.2

Replace the last sentence with the following, in which “front” has replaced “top”.

“If the test object penetrates through the front guard, it shall be considered to have failed the test.”

Page 10, 8.3

Renumber the second 8.3.1 as 8.3.2, and the existing 8.3.2 to 8.3.4 as 8.3.3 to 8.3.5, respectively.

Page 10, 8.3.2 (corrected numbering)

Replace with the following:

“Bolts used structurally shall be metric property class 8.8, 9.8 or 10.9 in accordance with ISO 898-1. Nuts used structurally shall be metric property class 8 or 10 in accordance with ISO 898-2.”

Page 10, 8.3.4 (corrected numbering)

Replace the last two sentences with the following:

“Specimens from tubular or structural sections shall be taken in accordance with ISO 148 from the middle of the side of greatest dimension and shall not include welds.”