



INTERNATIONAL STANDARD ISO 10599-2:1997
TECHNICAL CORRIGENDUM 1

Published 2005-09-15

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION

Car radios — Coaxial aerial connectors —
Part 2:
Characteristic values, performance requirements and tests

TECHNICAL CORRIGENDUM 1

Autoradios — Connecteurs coaxiaux d'antenne —
Partie 2: Valeurs caractéristiques, performances et essais
RECTIFICATIF TECHNIQUE 1

Technical Corrigendum 1 to ISO 10599-2:1997 was prepared by Technical Committee ISO/TC 22, *Road vehicles*.

Page 5, Subclause 5.1.4

For “Insulation resistance”, change the performance requirement for minimum resistance from “10 m Ω ” to “10 M Ω ”.

Page 5, Subclause 5.2.4

For “Dry heat”, change the performance requirement for insulation resistance measured at the test temperature from “10 m Ω min.” to “10 M Ω min.”

Page 6, Subclause 5.2.5

For “Cyclic damp heat and cold test”, change the performance requirement for maximum resistance at the outer contact from “20 M Ω ” to “20 m Ω ”.