
**Road vehicles — Component test
methods for electrical disturbances from
narrowband radiated electromagnetic
energy —**

Part 1:
General principles and terminology

AMENDMENT 1

*Véhicules routiers — Méthodes d'essai d'un équipement soumis à des
perturbations électriques par rayonnement d'énergie électromagnétique
en bande étroite —*

Partie 1: Principes généraux et terminologie

AMENDEMENT 1



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.



COPYRIGHT PROTECTED DOCUMENT

© ISO 2008

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

Amendment 1 to ISO 11452-1:2005 was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 3, *Electrical and electronic equipment*.

Road vehicles — Component test methods for electrical disturbances from narrowband radiated electromagnetic energy —

Part 1: General principles and terminology

AMENDMENT 1

Page 13, Annex A

Replace the whole of Annex A with the following.

Annex A (normative)

Function performance status classification (FPSC)

A.1 General

This annex provides a general method for defining the acceptable performance of electrical/electronic functions of automotive electrical systems during and after components immunity test for electrical disturbances from narrowband radiated electromagnetic energy. This method is based on the following considerations:

- a) a DUT can include one or several functions (e.g. an electronic unit can manage front wiping, courtesy lighting and low beam lighting);
- b) a function can have one or several operating modes (e.g. low beam ON, low beam OFF, courtesy lighting ON, courtesy lighting OFF);
- c) an operating mode can have several statuses (I, II, III, IV) (e.g. in low beam ON operating mode, the status II can be associated to low beam OFF during disturbance application with automatic recovery of low beam after disturbance suppression).

The functional performance status classification is applicable to each function.

A.2 FPSC approach

The approach is based on the following principles:

- a) functional performance status classification is applicable to each individual function; hence, a DUT is likely to include several functions (e.g. an electronic unit can manage front wiping, courtesy lighting and low beam lighting);
- b) a function can be a simple on-off operation or it can be complex, like data communication on a data bus.

It has to be emphasized that components or systems shall only be tested under the conditions, as described in ISO 11452, that represent the simulated automotive electromagnetic environments to which the devices would actually be subjected. This will help to ensure a technically and economically optimized design for potentially susceptible components and systems.

It should also be noted that this annex is not intended to be a product specification and cannot function as one. It should be used in conjunction with a specific test procedure in ISO 11452. Therefore, no specific values for the test signal severity level are included in this annex since they should be determined by the vehicle manufacturers and component suppliers. Nevertheless, using the concepts described in this annex and by careful application and agreement between manufacturer and supplier, this annex can be used to describe the functional status requirements for a specific device. This can then, in fact, be a statement of how a particular device can be expected to perform under the influence of the specified test signals.

A.3 Essential elements of FPSC

There are two elements, listed below, required to describe a FPSC.

A.3.1 Function performance status

This element defines the expected performance objectives for the function of the device under test subjected to the test conditions. The four function performance statuses of the function (expected behaviour of the function observed during test) are listed below.

NOTE 1 This element is applicable to every single individual function of a DUT and describes the operational status of the defined function during and after a test.

NOTE 2 The minimum functional status is given in each test. An additional test requirement can be agreed between supplier and vehicle manufacturer.

- a) **Status I:** the function performs as designed during and after the test.
- b) **Status II:** the function does not perform as designed during the test, but returns automatically to normal operation after the test.
- c) **Status III:** the function does not perform as designed during the test and does not return to normal operation without a simple driver/passenger intervention, such as turning off/on the DUT, or cycling the ignition switch after the disturbance is removed.
- d) **Status IV:** the function does not perform as designed during and after the test and cannot be returned to proper operation without more extensive intervention, such as disconnecting and reconnecting the battery or power feed. The function shall not have sustained any permanent damage as a result of the testing.

A.3.2 Test severity level

This element defines the specification of test severity level of essential signal parameters. The test severity level is the stress level applied to the device under test for any given test method. The test severity levels should be determined by the vehicle manufacturer and supplier depending on the required operational characteristics of the function.

A.4 FPSC approach example

A.4.1 General example of FPSC application

The following example demonstrates the relationship between the test signal severity levels and their corresponding function performance status classification.

Comments listed in Figure A.1 can be interpreted as follows:

- a) the function should be nominal event No. 1 (Status I) up to test severity level L_1 ;
- b) unexpected event No. 2 is allowed above test severity level L_1 ;
- c) unexpected event No. 3 is allowed above test severity level L_2 .

Users may group functions into categories to allow the use of different test levels.

Test severity levels	Function performance status
L_{4i}	Unexpected event No. 4 (Status IV type, Status I, II and III allowed)
L_{3i}	Unexpected event No. 3 (Status III type, Status I and II allowed)
L_{2i}	Unexpected event No. 2 (Status II type, Status I allowed)
L_{1i}	Nominal function – event No. 1 (Status I type)

Figure A.1 — Illustration of function performance status classification

A.4.2 Classification of test severity levels

Examples of test severity levels are given in each part of ISO 11452.

