



INTERNATIONAL STANDARD ISO 11886:2002
TECHNICAL CORRIGENDUM 1

Published 2006-04-01

INTERNATIONAL ORGANIZATION FOR STANDARDIZATION • МЕЖДУНАРОДНАЯ ОРГАНИЗАЦИЯ ПО СТАНДАРТИЗАЦИИ • ORGANISATION INTERNATIONALE DE NORMALISATION

Building construction machinery and equipment — Pile driving and extracting equipment — Terminology and commercial specifications

TECHNICAL CORRIGENDUM 1

Machines et matériels pour la construction des bâtiments — Matériel de battage et d'extraction — Terminologie et spécifications commerciales

RECTIFICATIF TECHNIQUE 1

Technical Corrigendum 1 to International Standard ISO 11886:2002 was prepared by Technical Committee ISO/TC 195, *Building construction machinery and equipment*.

Page 9, 4.2.1.1

In the fourth point of the list of winch-operated impact hammer characteristics, insert the symbol “ED” between “dimension from axis face of leader” and “(mm)”.

Page 12, 4.2.2.1 and 4.2.2.2

From the last point in the list of electric vibrator characteristics, 4.2.2.1, delete the symbol “F” between “width of the vibrator to the centre” and “(mm)”.

From the last point in the list of hydraulic vibrator characteristics, 4.2.2.2, at the bottom of the page, delete the symbol “A₁” between “width of the vibrator to the centre” and “(mm)”.

Page 14, 4.2.3

In the very last point of the list of static pile pushing/pulling device characteristics, replace “total width, A” by “total length, A”.

ICS 01.040.91; 91.220

Ref. No. ISO 11886:2002/Cor.1:2006(E)

© ISO 2006 – All rights reserved

Printed in Switzerland