INTERNATIONAL STANDARD

ISO 12614-10

First edition 2014-07-01

Road vehicles — Liquefied natural gas (LNG) fuel system components —

Part 10: **Rigid fuel line in stainless steel**

Véhicules routiers — Équipements pour véhicules utilisant le gaz naturel liquéfié (GNL) comme combustible —

Partie 10: Tuyauterie rigide pour combustible en acier inoxydable



Reference number ISO 12614-10:2014(E)



COPYRIGHT PROTECTED DOCUMENT

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Case postale 56 • CH-1211 Geneva 20 Tel. + 41 22 749 01 11 Fax + 41 22 749 09 47 E-mail copyright@iso.org Web www.iso.org

Published in Switzerland

Cor	Lontents					
Fore	word		iv			
1	Scop	oe	1			
2	Norr	mative references	1			
3	Tern	ns and definitions	1			
4	Marl	king	2			
5	Cons	struction and assembly	2			
6	Test.		2			
	6.1	Applicability	2			
	6.2	Hydrostatic strength	3			
	6.3	Bending	3			
Rihli	ngrank	hv	4			

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: Foreword - Supplementary information

The committee responsible for this document is ISO/TC 22, Road vehicles, Subcommittee SC 25, Vehicles using gaseous fuels.

ISO 12614 consists of the following parts, under the general title *Road vehicles — Liquefied natural gas* (LNG) fuel system components:

- Part 1: General requirements and definitions
- Part 2: Performance and general test methods
- Part 3: Check valve
- Part 4: Manual valve
- Part 5: Tank pressure gauge
- Part 6: Pressure regulator
- Part 7: Pressure relief valve
- Part 8: Excess flow valve
- Part 9: Gas-tight housing and ventilation hose
- Part 10: Rigid fuel line in stainless steel
- Part 11: Fittings
- Part 12: Rigid fuel line in copper and its alloys
- Part 13: Pressure control regulator
- Part 14: Differential pressure fuel content gauge
- Part 15: Capacitance fuel content gauge

- Part 16: Heat exchanger vaporizer
- Part 17: Natural gas detector
- Part 18: Gas temperature sensor

Road vehicles — Liquefied natural gas (LNG) fuel system components —

Part 10:

Rigid fuel line in stainless steel

1 Scope

This part of ISO 12614 specifies tests and requirements for the rigid fuel line, a liquefied natural gas fuel system component intended for use on the types of motor vehicles defined in ISO 3833. This part of ISO 12614 is not applicable to the following:

- a) fuel containers;
- b) stationary gas engines;
- c) container mounting hardware;
- d) electronic fuel management;
- e) refuelling receptacles.

NOTE 1 It is recognized that miscellaneous components not specifically covered herein can be examined to meet the criteria of this part of ISO 12614 and tested according to the appropriate functional tests.

NOTE 2 All references to pressure in this part of ISO 12614 are to be considered gauge pressures unless otherwise specified.

NOTE 3 This part of ISO 12614 is based upon a working pressure for natural gas as a fuel of 1,6 MPa (16 bar). (1 bar = 0,1 MPa = 105 Pa; 1 MPa = 1 N/mm².) Other working pressures can be accommodated by adjusting the pressure by the appropriate factor (ratio). For example, a 2 MPa (20 bar) working pressure system will require pressures to be multiplied by 1,25.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 1127, Stainless steel tubes — Dimensions, tolerances and conventional masses per unit length

ISO 12614-1, Road vehicles — Liquefied natural gas (LNG) fuel system components — Part 1: General requirements and definitions

ISO 12614-2, Road vehicles — Liquefied natural gas (LNG) fuel system components — Part 2: Performance and general test methods

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 12614-1 apply.

Marking 4

Marking of the component shall provide sufficient information to allow the following to be traced:

- the manufacturer's or agent's name, trademark, or symbol;
- the model designation (part number);
- the working pressure or pressure and temperature range.

The following additional markings are recommended:

- the type of fuel;
- electrical ratings (if applicable); b)
- the symbol of the certification agency;
- d) the type approval number;
- the serial number or date code; e)
- a reference to this part of ISO 12614 (i.e. ISO 12614-10:2014). f)

This information can be provided by a suitable identification code on at least one part of the component when it consists of more than one part.

5 Construction and assembly

The rigid fuel line shall comply with the applicable provisions of ISO 12614-1 and ISO 12614-2, and with the tests specified in Clause 6.

The stainless steel rigid fuel line shall be a seamless cold-worked austenitic stainless steel tube complying with ISO 1127.

Test

6.1 Applicability

The tests required to be carried out are indicated in <u>Table 1</u>.

Table 1 — Tests applicable

Test	Applicable	Test procedure as required by ISO 12614-2	Specific test requirements of this part of ISO 12614
Hydrostatic strength	X	X	X (see <u>6.2</u>)
Leakage	X	X	
Excess torque resistance			
Bending moment			
Continued operation	X	X	
Corrosion resistance	X	X	
Oxygen ageing			
Electrical overvoltages			
Non-metallic material immersion			
Vibration resistance			

Table 1 (continued)

Test	Applicable	Test procedure as required by ISO 12614-2	Specific test requirements of this part of ISO 12614
Brass material compatibility			
Bending	X		X (see <u>6.3</u>)
Conductivity			

6.2 Hydrostatic strength

The rigid fuel line shall be tested according to the procedure for testing hydrostatic strength specified in ISO 12614-2.

Test pressure shall be 4 times the working pressure.

NOTE The higher hydrostatic test pressure for the rigid fuel line than the other ISO 12614 series components is due to the necessary provisions to cope for eventual damage or abrasions under normal operation.

6.3 Bending

Test the rigid fuel line according to the following procedure and acceptance criterion.

- a) Select a mandrel with a diameter according to <u>Table 2</u>.
- b) Bend the rigid fuel line over this mandrel once, forming a "U" shape.
- c) Close the rigid fuel line's ends and pressurize it to 4 times its working pressure. The rigid fuel line shall not leak.

Table 2 — Rigid fuel line external (RFLE) and mandrel diameters

RFLE diameter	Mandrel diameter
≤8 mm	3 × RFLE diameter
>8 mm	5 × RFLE diameter

Bibliography

 $[1] \hspace{0.5cm} \textbf{ISO 3833, Road vehicles} - \textit{Types} - \textit{Terms and definitions}$



ICS 43.060.40

Price based on 4 pages