
Graphical symbols for diagrams —

**Part 10:
Fluid power converters**

Symboles graphiques pour schémas —

*Partie 10: Convertisseurs pour transmissions hydrauliques et
pneumatiques*



Reference number
ISO 14617-10:2002(E)

© ISO 2002

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

© ISO 2002

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.ch
Web www.iso.ch

Printed in Switzerland

Contents

Page

Foreword	iv
Introduction.....	v
1 Scope.....	1
2 Normative references.....	1
3 Terms and definitions	1
4 Devices for conversion of mechanical energy to fluid energy or vice versa.....	2
5 Devices for conversion of fluid or mechanical energy by an intermediate fluid step	10
6 Linear fluid motors, fluid cylinders	11
Bibliography.....	13

.....

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 3.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this part of ISO 14617 may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 14617-10 was prepared by Technical Committee ISO/TC 10, *Technical product documentation*, Subcommittee SC 10, *Process plant documentation and tpd-symbols*.

ISO 14617 consists of the following parts, under the general title *Graphical symbols for diagrams*:

- *Part 1: General information and indexes*
- *Part 2: Symbols having general application*
- *Part 3: Connections and related devices*
- *Part 4: Actuators and related devices*
- *Part 5: Measurement and control devices*
- *Part 6: Measurement and control functions*
- *Part 7: Basic mechanical components*
- *Part 8: Valves and dampers*
- *Part 9: Pumps, compressors and fans*
- *Part 10: Fluid power converters*
- *Part 11: Devices for heat transfer and heat engines*
- *Part 12: Devices for separating, purification and mixing*
- *Part 15: Installation diagrams and network maps*

Other parts are under preparation.

Introduction

The purpose of ISO 14617 in its final form is the creation of a library of harmonized graphical symbols for diagrams used in technical applications. This work has been, and will be, performed in close cooperation between ISO and IEC. The ultimate result is intended to be published as a standard common to ISO and IEC, which their technical committees responsible for specific application fields can use in preparing International Standards and manuals.

www.iso.org

Vertical line of text on the right side of the page.

Graphical symbols for diagrams —

Part 10: Fluid power converters

1 Scope

This part of ISO 14617 specifies graphical symbols for fluid power conversion units such as pumps and motors in diagrams (for pumps used mainly for transportation, see ISO 14617-9).

For the fundamental rules of creation and application of graphical symbols in diagrams, see ISO 81714-1.

For an overview of ISO 14617, information on the creation and use of registration numbers for identifying graphical symbols used in diagrams, rules for the presentation and application of these symbols, and examples of their use and application, see ISO 14617-1.

2 Normative references

The following normative documents contain provisions which, through reference in this text, constitute provisions of this part of ISO 14617. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this part of ISO 14617 are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. For undated references, the latest edition of the normative document referred to applies. Members of ISO and IEC maintain registers of currently valid International Standards.

ISO 5598:1985, *Fluid power systems and components — Vocabulary*

ISO 14617-1:2002, *Graphical symbols for diagrams — Part 1: General information and indexes*

ISO 14617-2:2002, *Graphical symbols for diagrams — Part 2: Symbols having general application*

ISO 81714-1:1999, *Design of graphical symbols for use in the technical documentation of products — Part 1: Basic rules*

3 Terms and definitions

For the purposes of this part of ISO 14617, the following terms and definitions apply.

NOTE The list has been restricted to terms whose meaning is not obvious and which have not been defined elsewhere in an International Standard, or which have been defined in various ways in different standards. In preparing these definitions, ISO and IEC standards on terminology have been consulted; see the references in parentheses. However, most of the definitions in those standards were prepared by different technical committees within a restricted scope. This means that many terms so defined have to be given more general or neutral definitions when applied in the context of graphical symbols.

**3.1
(positive) displacement pump**

pump in which the fluid energy is increased in a working chamber that increases and decreases in volume

[ISO 5598]

**3.2
rotodynamic pump**

pump in which the fluid energy is increased by a rotating impeller

[ISO 5598]

NOTE The term “centrifugal pump” is sometimes used instead, but that term corresponds to a rotodynamic pump with radial liquid flow.

**3.3
capacity
displacement
swept volume**

volume absorbed or displaced per stroke or cycle

[ISO 5598]

**3.4
over-centre pump**

pump in which the direction of flow may be reversed without changing the direction of rotation of the drive shaft

[ISO 5598]



**3.5
uni-flow pump**









pump in which the direction of flow is independent of the direction of rotation of the drive shaft







[ISO 5598]

4 Devices for conversion of mechanical energy to fluid energy or vice versa

4.1 Symbols of a basic nature

4.1.1	2401		Hydraulic pump
4.1.2	2402		Pneumatic pump, compressor



4.1.3	2403		Hydraulic pump with alternative directions of flow
4.1.4	2404		Pneumatic pump, compressor with alternative directions of flow
4.1.5	2405		Hydraulic motor
4.1.6	2406		Pneumatic motor
4.1.7	2407		Hydraulic motor with alternative directions of flow
4.1.8	2408		Pneumatic motor with alternative directions of flow
4.1.9	2409		Hydraulic pump/motor The device can act as a pump or as a motor.
4.1.10	2410		Pneumatic pump/motor The device can act as a pump or a motor with the same direction of flow.








4.1.11	2411		Hydraulic pump/motor acting as pump in one direction of flow and as motor in other direction of flow
4.1.12	2412		Pneumatic pump/motor acting as pump in one direction of flow and motor in other direction of flow
4.1.13	2413		Hydraulic pump/motor acting as pump with alternative directions of flow or motor with alternative directions of flow
4.1.14	2414		Pneumatic pump/motor acting as pump with alternative directions of flow or motor with alternative directions of flow
4.1.15	2415		Hydraulic semi-rotary motor
4.1.16	2416		Pneumatic semi-rotary motor

4.2 Application rule for the symbols in 4.1

None.

4.3 Symbols giving supplementary information


4.3.1	201		Adjustability See R201 (4.4.1) and R2311 (4.4.3).
4.3.2	203		Pre-set adjustability See R201 (4.4.1) and R2311 (4.4.3).







4.3.3	221	Form 1 	Constant force, motion or flow See R221 (4.4.2).
4.3.4	222	Form 2 	
4.3.5	224		Sinusoidal force, motion or flow
4.3.6	225		Pulse-shaped force, motion or flow
4.3.7	233		Stepping function
4.3.8	2321		Positive displacement type
4.3.9	2322		Rotodynamic type







4.4 Application rules for the symbols in 4.3







4.4.1	R201	The symbol should cross the centre of the symbol to which it is added. For examples, see X201 (2-5.5.1) to X206 (2-2.5.6) and X2401 (4.5.1) and X2402 (4.5.2). If the symbol consists of an outline in the form of a square, rectangle or circle and a symbol inside indicating the function, another location could be more appropriate. For an example, see X207 (2-5.5.7).
4.4.2	R221	Form 2 may be used if confusion is unlikely.
4.4.3	R2311	Applied to symbols for pumps and compressors, the symbol indicates adjustability of capacity as defined in ISO 5598, if not otherwise indicated.







4.5 Application examples

4.5.1	X2401	 201, 402, 2321, 2401	Hydraulic pump of positive displacement type with adjustable capacity
-------	-------	---	---

<p>4.5.2</p>	<p>X2402</p>	 <p>201, 402, 403, 721, 2321, 2401</p>	<p>Hydraulic pump of positive displacement type with adjustable capacity</p> <p>Actuating device shown.</p>
<p>4.5.3</p>	<p>X2403</p>	 <p>402, 2061, 2401</p>	<p>Hydraulic pump of rotodynamic type</p> <p>External leakage connection shown.</p>
<p>4.5.4</p>	<p>X2404</p>	 <p>201, 402, 2401</p>	<p>Hydraulic pump driven by shaft with adjustable speed</p>
<p>4.5.5</p>	<p>X2405</p>	 <p>255, 402, 2401</p>	<p>Hydraulic pump with clockwise rotation when seen towards shaft end</p> <p>For the interpretation of the arrow, see R249 (2-7.2.8).</p>
<p>4.5.6</p>	<p>X2406</p>	 <p>255, 402, 2401</p>	
<p>4.5.7</p>	<p>X2407</p>	 <p>201, 255, 402, 2403</p>	<p>Over-centre hydraulic pump with adjustable capacity</p> <p>Clockwise rotation shown.</p>






<p>4.5.8</p>	<p>X2408</p>	 <p>256, 263, 402, 2403</p>	<p>Reversible hydraulic pump</p> <p>Corresponding directions of rotation and directions of flow indicated.</p>
<p>4.5.9</p>	<p>X2409</p>	 <p>256, 402, 2401</p>	<p>Hydraulic pump with one direction of flow independent of direction of rotation; uni-flow pump</p>
<p>4.5.10</p>	<p>X2410</p>	 <p>225, 402, 2321, 2401</p>	<p>Hydraulic pump of positive displacement type with pulsating flow</p>
<p>4.5.11</p>	<p>X2411</p>	 <p>224, 402, 2321, 2401</p>	<p>Hydraulic pump of positive displacement type with sinusoidal flow</p>
<p>4.5.12</p>	<p>X2412</p>	 <p>256, 261, 402, 2405</p>	<p>Hydraulic semi-rotary motor</p> <p>Alternative to 2415 (4.1.15), composed by several symbols.</p>
<p>4.5.13</p>	<p>X2413</p>	 <p>201, 402, 2321, 2405</p>	<p>Hydraulic motor of positive displacement type with adjustable capacity</p>

<p>4.5.14</p>	<p>X2414</p>	 <p>402, 2322, 2405</p>	<p>Hydraulic motor of rotodynamic type</p> <p>EXAMPLE Water turbine.</p>
<p>4.5.15</p>	<p>X2415</p>	 <p>201, 402, 2405</p>	<p>Hydraulic motor whose rotational speed is achieved by adjustment of flow rate</p>
<p>4.5.16</p>	<p>X2416</p>	 <p>255, 402, 2405</p>	<p>Hydraulic motor with anti-clockwise rotation when seen towards shaft end</p> <p>For the interpretation of the arrow, see R249 (2-7.2.8).</p>
<p>4.5.17</p>	<p>X2417</p>	 <p>255, 402, 2405</p>	
<p>4.5.18</p>	<p>X2418</p>	 <p>256, 402, 2405</p>	<p>Hydraulic motor reversible by built-in device</p>
<p>4.5.19</p>	<p>X2419</p>	 <p>255, 402, 2407</p>	<p>Hydraulic motor with anticlockwise rotation independent of direction of flow</p>

<p>4.5.20</p>	<p>X2420</p>	 <p>256, 263, 402, 2407</p>	<p>Hydraulic motor reversible by applying alternative directions of flow</p> <p>Corresponding directions of flow and direction of rotation indicated.</p>
<p>4.5.21</p>	<p>X2421</p>	 <p>233, 402, 2405</p>	<p>Stepping hydraulic motor</p>
<p>4.5.22</p>	<p>X2422</p>	 <p>255, 402, 2409</p>	<p>Hydraulic pump/motor with anticlockwise rotation when seen towards shaft end</p> <p>For the interpretation of the arrow, see R249 (2-7.2.8).</p>
<p>4.5.23</p>	<p>X2423</p>	 <p>255, 402, 2409</p>	
<p>4.5.24</p>	<p>X2424</p>	 <p>402, 2322, 2406</p>	<p>Pneumatic motor of rotodynamic type</p> <p>EXAMPLE Wind turbine.</p>
<p>4.5.25</p>	<p>X2425</p>	 <p>2401, IEC</p>	<p>Hydraulic pump with built-in electric motor (wet rotor)</p>

5 Devices for conversion of fluid or mechanical energy by an intermediate fluid step


5.1 Symbols of a basic nature

5.1.1	2431		Linear pneumatic-hydraulic converter
5.1.2	2435		Continuous pneumatic-hydraulic converter
5.1.3	2432		Linear pneumatic-hydraulic pressure intensifier
5.1.4	2436		Continuous pneumatic-hydraulic pressure intensifier
5.1.5	2434		Hydraulic rotary torque converter

5.2 Application rule for the symbols in 5.1

None.


5.3 Symbol giving supplementary information

5.3.1	201		Adjustability See R201 (4.4.1).
-------	-----	---	------------------------------------

5.4 Application rule for the symbol in 5.3

None.

5.5 Application example

5.5.1	X2431	 <p>201, 243, 402, 2434</p>	Adjustable hydraulic rotary torque converter
-------	-------	--	--

6 Linear fluid motors, fluid cylinders

6.1 Symbols of a basic nature

6.1.1	2441		Single-acting hydraulic extension cylinder with single-ended piston rod
6.1.2	2445		Single-acting pneumatic extension cylinder with single-ended piston rod
6.1.3	2446		Single-acting hydraulic retraction cylinder with single-ended piston rod
6.1.4	2447		Single-acting pneumatic retraction cylinder with single-ended piston rod
6.1.5	2442		Double-acting hydraulic cylinder with single-ended piston rod
6.1.6	2448		Double-acting pneumatic cylinder with single-ended piston rod
6.1.7	2443		Single-acting hydraulic telescopic cylinder
6.1.8	2449		Single-acting pneumatic telescopic cylinder
6.1.9	2450		Double-acting hydraulic telescopic cylinder
6.1.10	2451		Double-acting pneumatic telescopic cylinder
6.1.11	2444		Cushion

6.2 Application rule for the symbols in 6.1

None.





6.3 Symbol giving supplementary information

None.

6.4 Application rule for the symbol in 6.3

None.

6.5 Application examples

<p>6.5.1</p>	<p>X2441</p>	 <p>2441</p>	<p>Single-acting hydraulic extension cylinder with single-ended piston rod and drain</p>
<p>6.5.2</p>	<p>X2442</p>	 <p>2002, 2446</p>	<p>Single-acting hydraulic retraction cylinder with single-ended piston rod and automatic return by spring</p>
<p>6.5.3</p>	<p>X2443</p>	 <p>402, 2448</p>	<p>Double-acting pneumatic cylinder with double-ended piston rod</p>
<p>6.5.4</p>	<p>X2444</p>	 <p>201, 2442, 2444</p>	<p>Double-acting hydraulic cylinder with single-ended piston rod, adjustable cushions at both sides and piston area ratio of 2:1</p>

Bibliography

- [1] ISO 14617-9:2002, *Graphical symbols for diagrams — Part 9: Pumps, compressors and fans*

ICS 01.080.30

Price based on 13 pages

© ISO 2002 – All rights reserved