
**Small craft — Liquid-fuelled galley
stoves and heating appliances**

*Petits navires — Réchauds de cuisine et appareils de chauffage
alimentés par un combustible liquide*



COPYRIGHT PROTECTED DOCUMENT

© ISO 2016, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

	Page
Foreword	iv
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 General	2
5 Installation	3
6 Stove design and construction	5
7 Heater design and construction	5
8 Marking	6
Annex A (normative) Information for stoves to be included in the craft owner's manual	9
Annex B (normative) Information for heaters to be included in the craft owner's manual	10

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT), see the following URL: [Foreword — Supplementary information](#).

The committee responsible for this document is ISO/TC 188, *Small craft*.

This second edition cancels and replaces the first edition (ISO 14895:2000), which has been technically revised.

The revision covers the following main changes:

- widening the scope to include heating appliances; subsequently, requirements applicable to heaters and stoves are combined or differentiated by type of appliance;
- the above scope extension required a modification of general, installation and requirements for design and construction of appliances;
- a new clause on design and construction of heating appliances, as well as an annex on the information on heaters required for the craft owner's manual;
- references to ISO 7840, ISO 13297 and ISO 21487 have also been added.

Small craft — Liquid-fuelled galley stoves and heating appliances

1 Scope

This International Standard specifies the design, construction and installation of permanently installed galley stoves and heating appliances using fuels which are liquid at atmospheric pressure on small craft up to 24 m length of hull (L_H according to ISO 8666). It includes open flame galley stoves, ceramic hobs, blown air heaters and water heating appliances.

Cooking and heating appliances solely designed or intended as portable self-contained camping stoves or heaters are not covered. Other permanently installed cooking and heating appliances (such as solid-fuelled and liquid-fuelled natural draft stoves) are outside the scope of this International Standard and therefore covered by ISO 9094.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 7840, *Small craft — Fire-resistant fuel hoses*

ISO 8469:2013, *Small craft — Non-fire-resistant fuel hoses*

ISO 9094, *Small craft — Fire protection*

ISO 10088:2013, *Small craft — Permanently installed fuel systems*

ISO 10133, *Small craft — Electrical systems — Extra-low-voltage d.c. installations*

ISO 10239, *Small craft — Liquefied petroleum gas (LPG) systems*

ISO 10240, *Small craft — Owner's manual*

ISO 12217-1, *Small craft — Stability and buoyancy assessment and categorization — Part 1: Non-sailing boats of hull length greater than or equal to 6 m*

ISO 12217-2, *Small craft — Stability and buoyancy assessment and categorization — Part 2: Sailing boats of hull length greater than or equal to 6 m*

ISO 12217-3, *Small craft — Stability and buoyancy assessment and categorization — Part 3: Boats of hull length less than 6 m*

ISO 13297, *Small craft — Electrical systems — Alternating current installations*

ISO 21487, *Small craft — Permanently installed petrol and diesel fuel tanks*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1 galley stove
appliance designed for cooking that makes use of burners, an oven, a broiler or any combination of these items, by means of combusting liquid fuel

Note 1 to entry: Referred to as “stove” within the text.

3.2 heating appliance
appliance designed to heat air or water or a solid medium by means of combusting liquid fuel

Note 1 to entry: Referred to as “heater” within the text.

3.3 liquid fuel
fuel which is liquid at atmospheric pressure

EXAMPLE Kerosene and diesel fuel.

3.4 readily accessible
capable of being reached for operation, inspection or maintenance without removal of any craft structure or use of any tools

3.5 habitable space
space surrounded by permanent craft structure in which there is provision for activities such as sleeping, cooking, eating, washing/toilet, navigation, steering

Note 1 to entry: Spaces intended exclusively for storage, open cockpits with or without canvas enclosures and engine rooms are not included.

3.6 overheating
condition that exists when the manufacturer’s safe operating temperature is exceeded

3.7 open flame stove
galley stove where direct bodily contact with an exposed open flame is possible during normal operation

4 General

NOTE For the purposes of this International Standard, the term “appliances” will be used if deemed to cover both heaters and stoves.

4.1 Appliances shall be installed in accordance with the instructions supplied by the appliance manufacturer and in conformity with this International Standard.

4.2 Appliances using petrol as fuel or for priming, in any liquid or semi-liquid form, shall not be installed. Petrol is considered to be a hydrocarbon fuel, or blends thereof, which is liquid at atmospheric pressure and is used in spark ignition engines (in this context, kerosene is not regarded as petrol).

4.3 Heaters and their exhaust systems shall be installed outside areas where flammable vapours can accumulate.

4.4 Design and installation of the appliances shall consider their use in the marine environment, for example vibration, craft movements, temperatures, humidity and corrosion.

4.5 Appliance operating control(s) shall be readily accessible, and located to minimize possible injury from burners and/or hot components when being used.

4.6 Heaters shall be installed so that outgoing products of combustion pass through sealed ductwork terminating outside the craft.

4.7 Where user awareness for the safe operation of an appliance is required, a durable, permanently legible sign covering the operation, including the refuelling procedure if applicable, and any unique hazards involved with its use, shall be provided on or in the immediate vicinity. See [8.1](#), [8.2](#) and [8.3](#).

4.8 For appliances with electrical systems requiring connection to the craft's electrical system, the connections shall conform to the requirements of ISO 10133, or ISO 13297.

4.9 Appliances requiring priming shall be fitted with a readily accessible drip pan to contain any fuel overflowing from the priming fuel container under conditions of pitch and heel as applicable (see [6.8](#) for stoves and [7.1](#) for heaters). The drip pan shall be at least 20 mm deep.

4.10 Appliances shall not feature open flame pilot lights. If pilot lights are integral then they shall be installed so that outgoing products of combustion pass through sealed ductwork terminating outside the craft.

5 Installation

5.1 Appliances and any associated remote fuel tanks shall be securely fastened to the craft.

5.2 Every reasonable precaution should be taken in positioning appliances to minimize the risk of injury or damage.

5.3 The heater and/or heater exhaust components shall not constitute a risk of fire, even in the case of overheating. This requirement can be achieved by use and/or combination of

- adequate distance to hot parts,
- suitable ventilation to hot parts,
- fire resistant materials, and
- heat shields.

5.4 For stoves, a readily accessible shut-off valve, not integral with the stove, shall be located near remote, i.e. non-integral, fuel tanks. The valve shall be designed to close against the flow of fuel and shall indicate the off and on positions and the closing direction. If the valve is outside the galley, a second valve shall be fitted in the fuel line in the galley space in a readily accessible location without reaching above the burners and outside Zone II, as defined in ISO 9094. This requirement does not apply where the tank is located lower than the stove and there is no possibility of back siphoning or where a fire or fusible valve that prevents fuel from continuing to flow to an appliance in the event of a fire is installed in the appliance or near to the final fuel supply joint to it. Electrically operated shut-off devices such as fuel pumps, which are interrupting the fuel flow when not activated, are permitted.

For heaters, a fuel shut-off device shall be located near remote, i.e. non-integral, fuel tanks. The device shall be designed to close against the flow of fuel and in case of a manually operated valve shall indicate the off and on positions and the closing direction. Electrically operated shut-off devices such as fuel pumps which are interrupting the fuel flow when not activated are permitted.

ISO 14895:2016(E)

5.5 Remote tanks installed in the compartment with the stove shall be located outside Zone II, as defined in ISO 9094.

5.6 For appliance fuel systems installed in engine rooms or machinery spaces, ISO 10088:2013 shall apply with the exception of 5.3.1, 5.3.9, 5.3.11, 5.4.2, 5.6 and 5.7.

5.7 Fuel-supply lines shall be solid drawn metallic piping or flexible hose and tube meeting the test requirements in ISO 8469:2013, Clause 5. If installed in the engine compartment, the hose or tube shall be fire resistant type A1 or A2, according to ISO 7840:2013.

5.8 The number of joints in fuel distribution pipes or hoses other than those required to connect required fuel line components (e.g. filters and bulkhead connections) shall be kept to a minimum.

5.9 The provisions for filling remote tanks shall be outside Zone II, as defined in ISO 9094.

5.10 The combustion air inlet shall be positioned or guarded so that it cannot be blocked.

5.11 The heating air supply may be fresh air or re-circulated air and shall be drawn from a clean area not likely to be contaminated by exhaust fumes emitted either by the propulsion engine, the heater or any other exhaust source. Any ductwork shall be securely fastened.

5.12 If the appliance consumes air for combustion from habitable spaces and no other means of ventilation is provided to the habitable space, then fixed ventilation shall be provided of size equal to or greater than the appliance's combustion air intake.

5.13 Exhaust outlet shall be located to avoid emissions from entering the habitable space(s) of the craft.

5.14 Any ducting used to route the hot heating air through the vessel shall be so positioned or protected that no injury or damage could be caused if it were to be touched.

5.15 Protection shall be provided to prevent human contact with exposed parts of the heating system exceeding a surface temperature of 110 °C. Examples of how this requirement can be met are by

- thermal insulation and or shielding,
- installation in a machinery room or a locker, and
- enclosure.

5.16 The heater or the heated medium shall not be liable to cause burns to persons. The surface temperature of any part of the heating system likely to come into contact with any person during normal craft operation shall not exceed a temperature of 85 °C.

5.17 Any brackets or ties used to support or secure such parts shall be of a suitable heat resistant material. If the heater is installed in a locker, then suitable steps shall be taken to protect any surrounding material and contents from heat damage.

5.18 The duplicate label (see [Clause 8](#)) shall be affixed where it is clearly visible if the original appliance label is obscured.

5.19 If a portable tank is used, it shall be of suitable design and labelled for the type of fuel used and shall have provisions to be secured on-board the craft.

6 Stove design and construction

6.1 Liquid-fuel priming pans or troughs shall be secured to the burner or heat generator so that their relationship is maintained.

6.2 Priming pans or troughs shall be designed to contain fuel without spillage under conditions of pitch or roll of the craft to 15° in any direction.

6.3 Pressurized liquid-fuel tanks integral with a stove shall be equipped with a pressure relief valve designed to release at not more than twice the vapour pressure of the fuel used at 60 °C.

6.4 Pressurized liquid-fuel tanks integral with a stove shall be shielded or insulated so that, under continuous operation at maximum heat, the pressure in the tank will not exceed 50 % of the relief valve setting.

6.5 Pressurized liquid-fuel tanks integral with a stove shall be designed to withstand four times the relief-valve setting.

6.6 Pressurized liquid-fuel tanks integral with a stove shall be tested to withstand a minimum internal pressure of two times the design working pressure or 700 kPa, whichever is greater.

6.7 Stoves shall be capable of operating during periods of craft pitch or heel at angles up to 15° in any direction sustained at the maximum angle for at least 15 s. Stoves in monohull sailing craft shall be capable of operation at sustained angles of heel of 30°. This may be obtained by the use of gimbals.

6.8 Means shall be provided on or adjacent to stove-top cooking surfaces to prevent both deep and shallow cooking utensils from sliding across or off the stove, at

- pitch angles of up to 15° for all craft, and
- heel angles of
 - 15° for engine-driven craft and sailing multihulls; and
 - 30° for monohull sailing craft.

This may be obtained by the use of gimbals.

6.9 Oven doors shall be provided with a means to prevent unintentional opening due to force from sliding food and utensils.

6.10 Operating, maintenance and installation instructions shall be supplied with every stove, drawing particular attention to set up, maintenance, regular operation, prevention of risks and risk management.

7 Heater design and construction

7.1 Heaters shall be designed and constructed to meet the following general requirements:

- be suitable for marine use;
- be able to operate at angles of 15° heel or pitch in any direction;
- have overheat control devices.

7.2 Heaters shall not pollute the heating air. The combustion circuit of the heat exchanger shall be subjected to a leakage test to ensure that exhaust gasses cannot enter the heated air intended for the habitable space.

7.3 The temperature of the heated air entering the habitable space shall not exceed 150 °C to be measured at the centre of the heating air outlet.

7.4 An integral flame failure device shall be installed in every heater. This device shall recognize a flame failure and shut the heater down in a controlled manner.

7.5 In the event of a failed start the heater shall be designed to avoid any fuel overflowing. This may be achieved by supplying a safety lock out system following a pre-determined number of failed start attempts or by supplying of return lines.

7.6 If a combustion air blower is fitted, a delayed shut-off shall be provided, even in the event of overheating or in the event of an interrupted fuel supply.

7.7 A clearly visible tell-tale shall be provided and shall indicate when the combustion heater is switched on or off.

7.8 Operating, maintenance and installation instructions shall be supplied with every heater, drawing particular attention to set up, maintenance, regular operation, prevention of risks and risk management.

8 Marking

8.1 Each appliance shall be permanently marked or labelled with the following information:

- manufacturer's name or trademark;
- model number;
- rated heating output (for heaters);
- serial number;
- fuel type(s) on integral tanks at the opening used for filling or heater ID plate;
- operating voltage (where relevant).

A duplicate label shall be provided by the manufacturer.

NOTE For designing the general warning sign in the labels in [8.2](#) to [8.4](#), see symbol W001 in ISO 7010.

8.2 A permanent, legible warning label, in language acceptable in the country of use, shall be affixed on or adjacent to open flame stoves. It shall contain at least the following informational elements.



8.3 Stoves with integral fuel tanks shall have a permanent, legible warning label on, or adjacent to, the stove with the following informational elements in language acceptable in the country of use.



8.4 Non-pressurized stoves with integral tanks, having fuel held in absorbent material, which are designed to have the fuel container removed for filling, shall have a permanent, legible warning label with the following informational elements in language acceptable in the country of use.



8.5 Openings for filling fuel tanks shall be identified to indicate the type of fuel to be used with the system. The word "FUEL" alone shall not be used.

NOTE The collection of ISO safety signs and additional information on their use is available at <http://www.iso.org/obp>.

Annex A (normative)

Information for stoves to be included in the craft owner's manual

The following information shall be included in the boat owner's manual. See ISO 10240.

- a) Instructions to read the stove's owner's manual.
- b) Instructions for priming, lighting and use of the stove, also for turning off the stove and fuel supply.
- c) Type of fuel used (such as alcohol type, diesel, kerosene) and cautions and possible hazards with other fuels that are not suitable for use.
- d) Instructions for the refuelling procedure, including possible hazard warnings concerning fire and explosion.
- e) Cleaning and maintenance of the stove and fuel system.
- f) Warnings and cautions with at least the following informational elements:
 - open-flame stoves consume oxygen and to draw the owner's attention to the warning label required in [8.2](#);
 - insufficient oxygen supply can cause asphyxiation;
 - maintain ventilation open when stove is in use;
 - do not use the open-flame stove for space or comfort heating;
 - stove exhaust components can be hot during and directly after operation;
 - ensure stove inlets and exhaust outlets are not obstructed while stove is in operation;
 - turn stove off during refuelling.
- g) Recommendations for storage of spare fuel:
 - keep spare fuel to a minimum and in containers of corrosion-resistant material;
 - keep stowed outside the accommodation spaces;
 - keep stowed in areas where the temperature cannot exceed 60 °C.

Annex B (normative)

Information for heaters to be included in the craft owner's manual

The following information shall be included in the boat owner's manual. See ISO 10240.

- a) Instructions to read the heater's owner's manual.
- b) Instructions for use of the heater, also for turning off and fuel supply. These instructions shall include ensuring heater's cool down cycle is not interrupted and turning off heater fuel supply if manual valve is fitted.
- c) Type of fuel used (such as alcohol type, diesel, kerosene) and cautions and possible hazards with other fuels that are not suitable for use.
- d) Instructions for the refuelling procedure, including possible hazard warnings concerning fire and explosion.
- e) Specify inspection and/or maintenance intervals.
- f) Warnings and cautions with at least the following information elements:
 - heater and its components can be hot during and directly after heater operation and might cause injury when touched;
 - air temperature at heater outlets can be hot and might cause injury when exposed to hot air flow over time;
 - ensure all combustion, exhaust or heating air outlets or intakes are kept clear during heater operation;
 - turn heater off during refuelling;
 - do not store flammable material near heater.
- g) Recommendations for storage of spare fuel:
 - keep spare fuel to a minimum and in containers of corrosion-resistant material;
 - keep stowed outside the accommodation spaces;
 - keep stowed in areas where the temperature cannot exceed 60 °C.

